IPC ASSOCIATION CONNECT ELECTRONICS INDUSTR	Material Compo © Copyright 2005. IP international and Pan-	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.			nder both	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lowe level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.									
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Form Type Distribute				e *	* Declaration Class * Class 6 - RoHS Yes/No. Homogeneous Materi					ials and Mfg Information			
upplier Infor	mation				·										
Company name*			Company unique ID			ī	Unique ID Authority				Respo	Response Date*			
onsemi											2024-0	2024-05-05			
Contact Name		Title - Contact]	Phone - Contact*				Email	Email - Contact*				
Product-Env-Stev	wards		Product Enviro Compliance				NA				Prod	Product-Env-Stewards@onsemi.com			
Authorized Representative*			Title - Representative			1	Phone - Representative*				Email	Email - Representative*			
Product-Env-Stewards			Product Enviro Compliance				NA				Prod	Product-Env-Stewards@onsemi.com			
Reques	ster Item Number			Mfr Item Name			Effective Dat	te Versi	ion	Manufacturing Site		Weight*	UOM	Unit Type	
				ZEN PWMITE RI	ZEN PWMITE REG 3.2W 6.2V		2024-05-05			MY1		16.3	mg	Each	
Ianufacturing	g Proccess Informati	ion											·		
Terminal Plating / Grid Array Material			Terminal Base Alloy J-STD-020 MS		SL Rating	Peak Process Body Temperat		ire Max Time at Pe	ak Tempe	rature Num	ber of Reflow Cyc	eles			
Matte Tin (Sn) - annealed			CU Alloy 1				260		C	30	sec	onds 3			
omments															
vel 1 - maximum	ı time at peak temperatur	e during sol	dering is 10-3	30 seconds											
or more informa	tion regarding material c	omposition	please refer t	page 3											

RoHS Material Composition Declaration			Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).									
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its uppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusivesource of the Supplier's liability and the Company's remedies for issues that arise regarding information the Supplier provi										
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted substance	es per the definition above except for selected exemp	otions Supplier Acceptance	* Accepted						
Exemption: 7a: Lead in high melting temperature type solders (i.e. lead based solder alloys containing 85% by weight or more lead).										
Exemption List Version	EL-2011/534/EU									
Declaration Signature										
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.										
Supplier Digital Signature Ra	astislav Drska	-6_								

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.16	mg	Supplier	Silicon (Si)	7440-21-3		0.16	mg
Die Attach Solder	0.34	mg	Supplier	Silver (Ag)	7440-22-4		0.0085	mg
			A	Lead (Pb)	7439-92-1	7a	0.3145	mg
			Supplier	Tin (Sn)	7440-31-5		0.017	mg
Lead Frame	5.38	_	Supplier	Zinc (Zn)	7440-66-6		0.0054	mg
			Supplier	Iron (Fe)	7439-89-6		0.1291	mg
			Supplier	Copper (Cu)	7440-50-8		5.2455	mg
Mold Compound-Black	9.69	mg	Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.969	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0484	mg
			Supplier	Aluminum Hydroxide (Al(OH)3)	21645-51-2		1.405	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		6.2985	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.969	mg
Plating	0.73	mg	Supplier	Tin (Sn)	7440-31-5		0.73	mg