IPC ASSOCIATION ELECTRONICS	© Copyright 2005.	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.			nder both	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lowe level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.									
752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Typhttp://www.ipc.org/IPC-175x Distribute				Form Type 'Distribute	*	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					ials and Mfg Information			
Supplier	Information														
Company	name*	Company un	Company unique ID			Unique ID Authority					Response Date*				
nsemi												2024-05-16			
Contact Na	ame	Title - Contact			I	Phone - Contact*					Email - Contact*				
Product-E	Inv-Stewards		Product Enviro Compliance				NA					Product-Env-Stewards@onsemi.com			
uthorized	l Representative*		Title - Representative			I	Phone - Representative*				Email - Representative*				
Product-E	inv-Stewards	Product Enviro Compliance				NA					Product-Env-Stewards@onsemi.com				
	Requester Item Number Mfr Item		n Number Mfr Item Name				Effective Date	ve Date		ng Site	V	/eight*	UOM	Unit Type	
		HCPL3700SM 8PW AC/DC INT		8PW AC/DC INTI	FSMD		2024-05-16		тнн		4	73.871	mg	Each	
Ianufac	cturing Proccess Informa	ation													·
	Terminal Plating / Grid Array Material		Terminal Base Alloy J-STD-02		-STD-020 MSL	Rating	Peak Process Body Temperat		Temperatui	e Max Tir	ne at Peak T	Гетрегаtu	re Numb	er of Reflow Cyc	cles
Matte Tin (Sn) - annealed		CU Alloy 1			260 C 30		30		second	s 3					
omments															
vel 1 - ma	aximum time at peak temperat	ture during sol	dering is 10-3	30 seconds											
or more i	nformation regarding materia	l composition	please refer to	page 3											

RoHS Material Composition Declaration			Declaration Type *	Detail	ed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on informationprovided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the						

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	d Weight Unit of Measure Level Substance		Substance	CAS	Exempt	Weight	Unit of Measure	
Coupling Gel	4.37	mg	Supplier	Dimethyl Cyclosiloxanes	69430-24-6		0.437	mg
			Supplier	Trimethoxy(methyl)silane (C4H12O3Si)	1185-55-3		3.933	mg
Die	3.753	mg	В	Gallium Arsenide (AsGa)	1303-00-0		0.263	mg
			Supplier	Silicon (Si)	7440-21-3		3.49	mg
Die Attach	0.423	mg	Supplier	Silver (Ag)	7440-22-4		0.3173	mg
			Supplier	Phenolic Resin-2	54208-63-8		0.1058	mg
Lead Frame	117.616	mg	Supplier	Silver (Ag)	7440-22-4		0.74	mg
			Supplier	Zinc (Zn)	7440-66-6		0.141	mg
			Supplier	Iron (Fe)	7439-89-6		2.7	mg
			Supplier	Copper (Cu)	7440-50-8		114	mg
			Supplier	Phosphorus (P)	7723-14-0		0.035	mg
Mold Compound-Black	343.7	mg	Supplier	2,6-dibromo-4-[1-(3-bromo-4-hydroxyphenyl)-1-methylethyl]phenol	6386-73-8		13.7	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		68.7001	mg
			В	Antimony Trioxide (Sb2O3)	1309-64-4		10.3	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		250.9999	mg
Plating	3.81	mg	Supplier	Tin (Sn)	7440-31-5		3.81	mg
Wire Bond - Au	0.199	mg	Supplier	Gold (Au)	7440-57-5		0.199	mg