IPC ASSOCIATION CONNE	© Copyright 2005.	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.			der both	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.										
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				*	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					ials and Mfc Information				
upplier Info	ormation								,							
Company name*			Company unique ID			J	Unique ID Authority				Response Date*					
nsemi											2024-05-20					
Contact Name		Title - Contact			I	Phone - Contact*				Email - Contact*						
Product-Env-St	Stewards		Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com					
uthorized Rep	presentative*	Title - Representative			I	Phone - Representative*			Email - Representative*							
Product-Env-St	Stewards	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com						
Requ	uester Item Number	Mfr Item Number		Mfr Item Name			Effective Date	Version	M	lanufacturing Site	1	Weight*	UOM	Unit Type		
		LC70920 01TBG)4FXE-	Fuel Gauge			2024-05-20		PI	НМ	2	2.4485	mg	Each		
Ianufacturi	ing Proccess Informa	ntion														
Termi	Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 M				STD-020 MSL	Rating	Peak Proce	ess Body Ter	nperature	Max Time at Peak	Temperat	ure Numb	er of Reflow Cyc	eles		
SnAgCu		CU Alloy 1				260	C 30		30	secon	ds 3					
omments																
vel 1 - maximu	um time at peak temperat	ure during sol	dering is 10-3	30 seconds												
or more inform	mation regarding material	composition	nlease refer to	n nage 3												

RoHS Material Composition Declaration			Declaration Type *	Detail	ed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier have provided as part of that agreement, will be the sole and exclusivesource of the Supplier's liability and the Company's remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale appl											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the						

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Backside Protection Film	0.1064	mg		Epoxy resin	proprietary data		0.0223	mg
			Supplier	Carbon Black (C)	1333-86-4		0.002	mg
			Supplier	Acrylic resins	Proprietary Data		0.0223	mg
			Supplier	Silica (SiO2)	14464-46-1		0.0599	mg
Die	1.3554	mg	Supplier	Silicon (Si)	7440-21-3		1.3554	mg
Protection coat	0.0512	mg		Polyimide	proprietary data		0.0512	mg
RDL	0.0059	mg	Supplier	Titanium (Ti)	7440-32-6		0.0012	mg
			Supplier	Copper (Cu)	7440-50-8		0.0047	mg
RDL Cu 100	0.1985	mg	Supplier	Copper (Cu)	7440-50-8		0.1985	mg
Solder Ball	0.7311	mg	Supplier	Silver (Ag)	7440-22-4		0.0292	mg
			Supplier	Tin (Sn)	7440-31-5		0.6982	mg
			Supplier	Copper (Cu)	7440-50-8		0.0037	mg