ABSOCIATION CONNECTING ELECTRONICS INDUSTRIES® INDUSTRIES®	burn, Illinois, All rights reserved up	nder both This docur level parts,	nent is a declaratio the declaration en	n of the substance compasses all low	es within the manufacture er level materials for wh	er listed item. Note: if hich the manufacturer	the item is an as has engineering	sembly with lower responsibility.	
IPC Web Site for Information on http://www.ipc.org/IPC-175x	IPC-1752 Standard	Form Type * Distribute		ration Class * 6 - RoHS Yes/No	o, Homogeneous Materia	ls and Mfg Information			
Supplier Information									
Company name*	Company unique ID		Unique ID Authority			Response Date*			
onsemi						2024-05-16			
Contact Name	Title - Contact		Phone - Contact*			Email - Contact*			
Product-Env-Stewards	Product Enviro Compliance		NA			Product-Env-Stewards@onsemi.com			
Authorized Representative*	rized Representative* Title - Representative		Phone - Representative*			Email - Representative*			
Product-Env-Stewards Product Enviro Compliance			NA			Product-Env-Stewards@onsemi.com			
Requester Item Number Mfr Iter	n Number Mfr Item Name		Effective Date	Version	Manufacturing Site	Weight*	UOM	Unit Type	
MMUN	2111LT3G SS SOT23 BR XS	STR PNP 50V	2024-05-16		CN1	8.02	mg	Each	
Manufacturing Proccess Information									
Terminal Plating / Grid Array Material	Terminal Base Alloy J	-STD-020 MSL Rating	Peak Proces	s Body Temperat	ure Max Time at Peak	Temperature Number	er of Reflow Cyc	cles	
Matte Tin (Sn) - annealed CU Alloy 1		1	260	С	30	seconds 3			
Comments									
evel 1 - maximum time at peak temperature during so	oldering is 10-30 seconds								
for more information regarding material composition	please refer to page 3								

RoHS Material Composition Declaration				Declaration Type *	Detailed				
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Dibutyl phthalate (DIBP).								
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of				
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted				
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all				
Exemption List Version	EL-2011/534/EU								
Declaration Signature									
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the				
Supplier Digital Signature Ra	stislav Drska	Le							

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.05	mg	Supplier	Silicon (Si)	7440-21-3		0.05	mg
Lead Frame	2.92	mg	В	Nickel (Ni)	7440-02-0		1.06	mg
			Supplier	Iron (Fe)	7439-89-6		1.4658	mg
			Supplier	Copper (Cu)	7440-50-8		0.3942	mg
Mold Compound-Black	4.9	mg	Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.49	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0245	mg
			Supplier	Aluminum Hydroxide (Al(OH)3)	21645-51-2		0.7105	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		3.185	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.49	mg
Plating	0.14	mg	Supplier	Tin (Sn)	7440-31-5		0.14	mg
Wire Bond	0.01	mg	Supplier	Palladium (Pd)	7440-05-3		0.0001	mg
			Supplier	Copper (Cu)	7440-50-8		0.0099	mg