ABBOCIATION CONNECTING ELECTRONICS INDUSTRIES® International and Pan-American	kburn, Illinois. All rights	s reserved under both	This docume level parts, th	ent is a declaration he declaration end	n of the substance compasses all low	es within the manufactur ver level materials for wl	er listed item. Note hich the manufactu	e: if the item is an as irer has engineering	ssembly with lower responsibility.		
IPC Web Site for Information of http://www.ipc.org/IPC-175x	IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute			* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials and Mfg Information							
Supplier Information											
Company name*	pany name* Company unique ID			Unique ID Authority			Response Date*				
onsemi								2024-04-30			
Contact Name	Title - Contact]	Phone - Contact*			Email - Contact*				
Product-Env-Stewards	Stewards Product Enviro Compliance			NA			Product-Env-Stewards@onsemi.com				
thorized Representative* Title - Representative		e]	Phone - Representative*			Email - Representative*				
Product-Env-Stewards	pliance	NA			Product-Env-Stewards@onsemi.com						
Requester Item Number Mfr Ite	m Number Mfr Ite	Mfr Item Name		Effective Date	Version	Manufacturing Site	Weight*	UOM	Unit Type		
NCP1	CP1117STAT3G ANA SOT223 800MA			2024-04-30		MY1	108.86	mg	Each		
Manufacturing Proccess Information				·			·	· · · · · · · · · · · · · · · · · · ·			
Terminal Plating / Grid Array Material	Terminal Base Alloy J-STD-0		L Rating	Peak Process Body Temperature Max Time at		ure Max Time at Peak	k Temperature Number of Reflow Cycles				
Matte Tin (Sn) - annealed CU Alloy 1			260	С	30	seconds 3					
Comments											
evel 1 - maximum time at peak temperature during	oldering is 10-30 second	ds									
For more information regarding material composition	n please refer to page 3	;									

RoHS Material Composition Declaration				Declaration Type *	Detailed
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth	
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the
Supplier Digital Signature Ra	stislav Drska	Le			

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	1.1	mg	Supplier	Silicon (Si)	7440-21-3		1.1	mg	
Die Attach	0.74	mg		Resin	proprietary data		0.0592	mg	
			Supplier	Silver (Ag)	7440-22-4		0.6253	mg	
			Supplier	Formaldehyde Polymer	9003-36-5		0.0555	mg	
Lead Frame	37.17	mg	Supplier	Silver (Ag)	7440-22-4		0.4832	mg	
			Supplier	Zinc (Zn)	7440-66-6		0.0372	mg	
			Supplier	Iron (Fe)	7439-89-6		0.8921	mg	
			Supplier	Copper (Cu)	7440-50-8		35.7575	mg	
Mold Compound-Black	62.4	mg		Epoxy resin	proprietary data		3.12	mg	
			Supplier	Phenolic Resin	Proprietary Data		3.12	mg	
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		1.248	mg	
			Supplier	Carbon Black (C)	1333-86-4		0.312	mg	
			Supplier	Fused Silica (SiO2)	60676-86-0		54.6	mg	
Plating	7.44	mg	Supplier	Tin (Sn)	7440-31-5		7.44	mg	
Wire Bond - Cu	0.01	mg	Supplier	Copper (Cu)	7440-50-8		0.01	mg	

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).