IPC  ASSOCIATION CONN ELECTRONICS INDU	© Copyright 2005. IPC	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.			This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.										
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				*	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					ials and Mfc Information			
upplier Info	Cormation						·								
Company name*			Company unique ID			τ	Unique ID Authority				Response Date*				
nsemi											2024-05-15				
Contact Name			Title - Contact			1	Phone - Contact*				Email - Contact*				
Product-Env-S	Stewards		Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
uthorized Rep	presentative*		Title - Representative			1	Phone - Representative*			Email - Representative*					
Product-Env-S	Stewards		Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
Req	Requester Item Number Mfr Ite		em Number Mfr Item Name				Effective Date	Version	N	Manufacturing Site	V	Veight*	UOM	Unit Type	
		NCV8177AMTW090T Linear Vreg 500 mA CG-A642		A with Enable	e	2024-05-15	TH6		9	.04	mg	Each			
Ianufacturi	ing Proccess Information	on													
Terminal Plating / Grid Array Material Term			erminal Base Alloy J-STD-020 MSL			L Rating	Peak Process Body Temperature   Max Time at Peak				Temperatu	ıre Num	ber of Reflow Cyc	eles	
Matte Tin (Sn) - annealed		C	CU Alloy				260		С	30	second	ls 3			
omments															
vel 1 - maxim	um time at peak temperature	e during sol	dering is 10-3	0 seconds											
or more infor	mation regarding material co	omposition 1	olease refer to	page 3											

RoHS Material Composition Declaration			Declaration Type *	Detail	led						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU  RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledges and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its paragraph. If the Company and the Supplier have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier have provided as part of that agreement, will be the sole and exclusivesource of the Supplier's liability and the Company's remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty rights and/or remedies of Supplier's Standard											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substa	ances per the definition above	Supplier Ac	ceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructional Complete all of the required	fields on all neggs of this form. Calcut th		a duan dawn. This will display the signature on	a Digitally sign	the declaration (if recruired by the						
Instructions: Complete all of the required Requester) and click on Submit Form to			e drop-down. This will display the signature ar	ea. Digitally sign	the declaration (if required by the						

## **Homogeneous Material Composition Declaration for Electronic Products**

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.55	mg	Supplier	Silicon (Si)	7440-21-3		0.55	mg
Die Attach	0.09	mg	Supplier	Isobornyl Methacrylate	7534-94-3		0.0054	mg
			Supplier	Silver (Ag)	7440-22-4		0.0734	mg
			Supplier	Isobornyl Acrylate	5888-33-5		0.0054	mg
			Supplier	Misc.	Proprietary Data		0.0005	mg
			Supplier	Tricyclo[5.2.1.02,6]decanedimethanol Diacrylate (C18H24O4)	42594-17-2		0.0054	mg
Lead Frame	2.16	mg	Supplier	Silver (Ag)	7440-22-4		0.0432	mg
			Supplier	Tin (Sn)	7440-31-5		0.0054	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0048	mg
			Supplier	Chromium (Cr)	7440-47-3		0.0054	mg
			Supplier	Copper (Cu)	7440-50-8		2.1012	mg
Mold Compound-Black	5.77			Epoxy resin	proprietary data		0.2885	mg
			Supplier	Phenolic Resin	Proprietary Data		0.1327	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		0.2885	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0231	mg
			Supplier	Aluminum Hydroxide (Al(OH)3)	21645-51-2		0.1327	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		4.9045	mg
Plating	0.39	mg	Supplier	Tin (Sn)	7440-31-5		0.39	mg
Wire Bond - Au	0.08	mg	Supplier	Gold (Au)	7440-57-5		0.08	mg