© Copyright 2005. IPC.	© Convright 2005 IPC Bannockhurn Illinois All rights reserved under both				This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.									
	P.1.1 IPC Web Site for Information on IPC-1752 Standard Form http://www.ipc.org/IPC-175x Distri				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials and					Afg Informati	on			
Supplier Information														
Company name* Compa			ompany unique ID			Unique ID Authority					Response Date*			
onsemi										2024-0	2024-05-17			
Contact Name Title - Contact					Phone - Contact*				Email	Email - Contact*				
Product-Env-Stewards Product Enviro			iro Compliance			NA				Produ	Product-Env-Stewards@onsemi.com			
Authorized Representative* Title - Representative			entative		Phone - Representative*			Email	Email - Representative*					
Product-Env-Stewards Product En			Enviro Compliance			NA				Produ	Product-Env-Stewards@onsemi.com			
Requester Item Number	umber Mfr Item Number		umber Mfr Item Name			Effective Date	Version		Manufacturing Site		Weight*	UOM	Unit Type	
	NVMFS4	NVMFS4C01NT1G NFET SO8FL 30		V 305A 0.9MO	,	2024-05-17			MY1		100.83	mg	Each	
Manufacturing Proccess Informatio	n													
Terminal Plating / Grid Array Mater	Plating / Grid Array Material Terminal Base Alloy		Alloy	J-STD-020 MSI	L Rating	Peak Proc	ess Body T	emperatu	re Max Time at Peal	K Tempera	ature Numb	er of Reflow Cy	cles	
Matte Tin (Sn) - annealed CU Alloy				1		260		С	30	seco	nds 3			
Comments														
level 1 - maximum time at peak temperature	during sol	dering is 10-3	0 seconds											
for more information regarding material co	nposition j	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed					
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		mium (Cr6+), Polybrominated Biphenyls (Pl		dmium and quantity limit of 0.1% by mass (10 minated Diphenyl Ethers (PBDE), and Bis(2-et						
cadmium, hexavalentchromium, polybromina contains a RoHS restricted substance inexces encompass all such components. Supplier cer as of the date that Supplier completes this for Company acknowledges that Supplier may h independently verified information provided certification in this paragraph. If the Company	ated biphenyls and/or polybrominated dip s of an applicable quantity limit, please in iffies that it gathered the information it pr m.Supplier acknowledges that Company ave relied on informationprovided by oth by others, Supplier agrees that, at a minir and the Supplier enter into a written agr esource of the Supplier's liability and the	henyl ethers (each a "RoHS restricted substa ndicate below which, if any, RoHS exemption ovides in this form using appropriate methoo will rely on this certification in determining ers in completing this form, and that Supplie num, itssuppliers have provided certification eement with respect to the identified part, the Company's remedies for issues that arise reg	nce") in exco n you believe ls to ensure i the compliar r may not ha s regarding t terms and co	e may apply. If the part is an assembly with low s accuracy and that such information is true an ce of its products with European Union member de independently verified such information. Ho neir contributions to the part, and those certifica	ove. If a homogeneous material within the part er level components, the declaration shall d correct to the best of its knowledge and belief, er state laws that implement the RoHS Directive. wever, in situations where Supplier has not ations are at least as comprehensive as the anty rights and/or remedies provided as part of					
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted subst	ances per the definition above except for sele	ected exempt	ions Supplier Acceptance	* Accepted					
Exemption: 7a: Lead in high melting temperature type solders (i.e. lead based solder alloys containing 85% by weight or more lead).										
Exemption List Version	EL-2011/534/EU									
Declaration Signature										
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.										
Supplier Digital Signature	astislav Drska	Le								

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Clip	4.8	mg	Supplier	Iron (Fe)	7439-89-6		0.0048	mg	
			Supplier	Copper (Cu)	7440-50-8		4.7938	mg	
			Supplier	Phosphorus (P)	7723-14-0		0.0014	mg	
Die	0.73	mg	Supplier	Silicon (Si)	7440-21-3		0.73	mg	
Die Attach Solder	2.41	mg	Supplier	Silver (Ag)	7440-22-4		0.0603	mg	
			А	Lead (Pb)	7439-92-1	7a	2.2293	mg	
			Supplier	Tin (Sn)	7440-31-5		0.1205	mg	
Lead Frame	47.6	mg	Supplier	Silver (Ag)	7440-22-4		0.0286	mg	
			Supplier	Iron (Fe)	7439-89-6		0.0476	mg	
			Supplier	Copper (Cu)	7440-50-8		47.5096	mg	
			Supplier	Phosphorus (P)	7723-14-0		0.0143	mg	
Mold Compound-Black	43.54	mg		Epoxy resin	proprietary data		3.2655	mg	
			Supplier	Phenolic Resin	Proprietary Data		1.0885	mg	
			Supplier	Silica Amorphous (SiO2)	7631-86-9		3.2655	mg	
			Supplier	Carbon Black (C)	1333-86-4		0.2177	mg	
			Supplier	Fused Silica (SiO2)	60676-86-0		35.7028	mg	
Plating	1.7	mg	Supplier	Tin (Sn)	7440-31-5		1.7	mg	
Wire Bond - Cu	0.05	mg	Supplier	Copper (Cu)	7440-50-8		0.05	mg	

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).