NCS2004, NCS2004A

Operational Amplifier, Rail-to-Rail, 3.5 MHz, Wide Supply

The NCS2004 operational amplifier provides rail−to−rail output operation. The output can swing within 70 mV to the positive rail and 30 mV to the negative rail. This rail−to−rail operation enables the user to make optimal use of the entire supply voltage range while taking advantage of 3.5 MHz bandwidth. The NCS2004 can operate on supply voltage as low as 2.5 V over the temperature range of −40°C to 125°C. The high bandwidth provides a slew rate of 2.4 V/µs while only consuming a typical 390 µA of quiescent current. Likewise the NCS2004 can run on a supply voltage as high as 16 V making it ideal for a broad range of battery operated applications. Since this is a CMOS device it has high input impedance and low bias currents making it ideal for interfacing to a wide variety of signal sensors. In addition it comes in either a small SC−88A or UDFN package allowing for use in high density PCB's.

Features

- Rail−To−Rail Output
- Wide Bandwidth: 3.5 MHz
- High Slew Rate: 2.4 V/µs
- Wide Power Supply Range: 2.5 V to 16 V
- Low Supply Current: 390 µA
- Low Input Bias Current: 45 pA
- Wide Temperature Range: −40°C to 125°C
- Small Packages: 5−Pin SC−88A and UDFN6 1.6x1.6
- These Devices are Pb−Free, Halogen Free/BFR Free and are RoHS Compliant

Applications

- Notebook Computers
- Portable Instruments

ON Semiconductor®

www.onsemi.com

MARKING DIAGRAMS

SC−88A (SC−70−5) SN SUFFIX CASE 419A



ADK = Specific Device Code
M = Date Code
▪ = Pb−Free Package
(Note: Microdot may be in either location)



UDFN6 CASE 517AP



xx = Specific Device Code
AA for NCS2004
AC for NCS2004A
M = Date Code
▪ = Pb−Free Package
(Note: Microdot may be in either location)

PIN CONNECTIONS



SC−88A (Top View)



UDFN (Top View)

ORDERING INFORMATION

Device	Package	Shipping†
NCS2004SQ3T2G	SC−88A (Pb−Free)	3000 / Tape & Reel
NCS2004MUTAG, NCS2004AMUTAG	UDFN6 (Pb−Free)	3000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

© Semiconductor Components Industries, LLC, 2015

October, 2015 − Rev. 9

Publication Order Number:
NCS2004/D

MAXIMUM RATINGS

Symbol	Rating	Value	Unit
V_{DD}	Supply Voltage	16.5	V
V_{ID}	Input Differential Voltage	±Supply Voltage	V
V_I	Input Common Mode Voltage Range	−0.2 V to (V_{DD} + 0.2 V)	V
I_I	Maximum Input Current	±10	mA
I_O	Output Current Range	±100	mA
	Continuous Total Power Dissipation (Note 1)	200	mW
T_J	Maximum Junction Temperature	150	°C
θ_{JA}	Thermal Resistance	333	°C/W
T_{stg}	Operating Temperature Range (free−air)	−40 to 125	°C
T_{stg}	Storage Temperature	−65 to 150	°C
	Mounting Temperature (Infrared or Convection − 20 sec)	260	°C
V_{ESD}	Machine Model Human Body Model	300 2000	V

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Continuous short circuit operation to ground at elevated ambient temperature can result in exceeding the maximum allowed junction temperature of 150°C. Output currents in excess of 45 mA over long term may adversely affect reliability. Shorting output to either V+ or V− will adversely affect reliability.

DC ELECTRICAL CHARACTERISTICS (V_{DD} = 2.5 V, 3.3 V, 5 V and ±5 V, T_A = 25°C, R_L ≥ 10 kΩ unless otherwise noted)

Parameter	Symbol	Conditions		Min	Typ	Max	Unit
Input Offset Voltage (NCS2004)	V_{IO}	VIC = V_{DD}/2, V_O = V_{DD}/2, R_L = 10 kΩ, R_S = 50 Ω			0.5	5.0	mV
		T_A = −40°C to +125°C				7.0	
Input Offset Voltage (NCS2004A)	V_{IO}	VIC = V_{DD}/2, V_O = V_{DD}/2, R_L = 10 kΩ, R_S = 50 Ω				3.0	mV
		T_A = −40°C to +125°C				5.0	
Offset Voltage Drift	ICV_{OS}	VIC = V_{DD}/2, V_O = V_{DD}/2, R_L = 10 kΩ, R_S = 50 Ω			2.0		μV/°C
Common Mode Rejection Ratio	CMRR	0 V ≤ VIC ≤ V_{DD} − 1.35 V, R_S = 50 Ω	V_{DD} = 2.5 V	55	94		dB
		T_A = −40°C to +125°C		52			
		0 V ≤ VIC ≤ V_{DD} − 1.35 V, R_S = 50 Ω	V_{DD} = 5 V	65	130		
		T_A = −40°C to +125°C		62			
		0 V ≤ VIC ≤ V_{DD} − 1.35 V, R_S = 50 Ω	V_{DD} = ±5 V	69	140		
		T_A = −40°C to +125°C		66			
Power Supply Rejection Ratio	PSRR	V_{DD} = 2.5 V to 16 V, VIC = V_{DD}/2, No Load		70	135		dB
		T_A = −40°C to +125°C		65			
Large Signal Voltage Gain	A_{VD}	$V_{O(pp)}$ = V_{DD}/2, R_L = 10 kΩ	V_{DD} = 2.5 V	90	130		dB
		T_A = −40°C to +125°C		76			
		$V_{O(pp)}$ = V_{DD}/2, R_L = 10 kΩ	V_{DD} = 3.3 V	92	123		
		T_A = −40°C to +125°C		76			
		$V_{O(pp)}$ = V_{DD}/2, R_L = 10 kΩ	V_{DD} = 5 V	95	127		
		T_A = −40°C to +125°C		86			
		$V_{O(pp)}$ = V_{DD}/2, R_L = 10 kΩ	V_{DD} = ±5 V	95	130		
		T_A = −40°C to +125°C		90			

DC ELECTRICAL CHARACTERISTICS (V_{DD} = 2.5 V, 3.3 V, 5 V and ±5 V, T_A = 25°C, R_L ≥ 10 kΩ unless otherwise noted)

Parameter	Symbol	Conditions		Min	Typ	Max	Unit
Input Bias Current	I_B	V_{DD} = 5 V, VIC = V_{DD}/2, V_O = V_{DD}/2, R_S = 50 Ω	T_A = 25°C		45	150	pA
			T_A = 125°C			1000	
Input Offset Current	I_{IO}	V_{DD} = 5 V, VIC = V_{DD}/2, V_O = V_{DD}/2, R_S = 50 Ω	T_A = 25°C		45	150	pA
			T_A = 125°C			1000	
Differential Input Resistance	$r_{i(d)}$				1000		GΩ
Common−mode Input Capacitance	C_{IC}	f = 21 kHz			8.0		pF
Output Swing (High−level)	V_{OH}	VIC = V_{DD}/2, I_{OH} = −1 mA	V_{DD} = 2.5 V	2.35	2.43		V
		T_A = −40°C to +125°C		2.28			
		VIC = V_{DD}/2, I_{OH} = −1 mA	V_{DD} = 3.3 V	3.15	3.21		
		T_A = −40°C to +125°C		3.00			
		VIC = V_{DD}/2, I_{OH} = −1 mA	V_{DD} = 5 V	4.8	4.93		
		T_A = −40°C to +125°C		4.75			
		VIC = V_{DD}/2, I_{OH} = −1 mA	V_{DD} = ±5 V	4.92	4.96		
		T_A = −40°C to +125°C		4.9			
		VIC = V_{DD}/2, I_{OH} = −5 mA	V_{DD} = 2.5 V	1.7	2.14		V
		T_A = −40°C to +125°C		1.5			
		VIC = V_{DD}/2, I_{OH} = −5 mA	V_{DD} = 3.3 V	2.5	2.89		
		T_A = −40°C to +125°C		2.1			
		VIC = V_{DD}/2, I_{OH} = −5 mA	V_{DD} = 5 V	4.5	4.68		
		T_A = −40°C to +125°C		4.35			
		VIC = V_{DD}/2, I_{OH} = −5 mA	V_{DD} = ±5 V	4.7	4.78		
		T_A = −40°C to +125°C		4.65			
Output Swing (Low−level)	V_{OL}	VIC = V_{DD}/2, I_{OL} = −1 mA	V_{DD} = 2.5 V		0.03	0.15	V
		T_A = −40°C to +125°C				0.22	
		VIC = V_{DD}/2, I_{OL} = −1 mA	V_{DD} = 3.3 V		0.03	0.15	
		T_A = −40°C to +125°C				0.22	
		VIC = V_{DD}/2, I_{OL} = −1 mA	V_{DD} = 5 V		0.03	0.1	
		T_A = −40°C to +125°C				0.15	
		VIC = V_{DD}/2, I_{OL} = −1 mA	V_{DD} = ±5 V		0.05	0.08	
		T_A = −40°C to +125°C				0.1	
		VIC = V_{DD}/2, I_{OL} = −5 mA	V_{DD} = 2.5 V		0.15	0.7	V
		T_A = −40°C to +125°C				1.1	
		VIC = V_{DD}/2, I_{OL} = −5 mA	V_{DD} = 3.3 V		0.13	0.7	
		T_A = −40°C to +125°C				1.1	
		VIC = V_{DD}/2, I_{OL} = −5 mA	V_{DD} = 5 V		0.13	0.4	
		T_A = −40°C to +125°C				0.5	
		VIC = V_{DD}/2, I_{OL} = −5 mA	V_{DD} = ±5 V		0.16	0.3	
		T_A = −40°C to +125°C				0.35	

DC ELECTRICAL CHARACTERISTICS (V_{DD} = 2.5 V, 3.3 V, 5 V and ±5 V, T_A = 25°C, R_L ≥ 10 kΩ unless otherwise noted)

Parameter	Symbol	Conditions		Min	Typ	Max	Unit
Output Current	I_O	V_O = 0.5 V from rail, V_{DD} = 2.5 V	Positive rail		4.0		mA
			Negative rail		5.0		
		V_O = 0.5 V from rail, V_{DD} = 5 V	Positive rail		7.0		
			Negative rail		8.0		
		V_O = 0.5 V from rail, V_{DD} = 10 V	Positive rail		13		
			Negative rail		12		
Power Supply Quiescent Current	I_{DD}	V_O = V_{DD}/2	V_{DD} = 2.5 V		380	560	μA
			V_{DD} = 3.3 V		385	620	
			V_{DD} = 5 V		390	660	
			V_{DD} = 10 V		400	800	
		T_A = −40°C to +125°C				1000	

AC ELECTRICAL CHARACTERISTICS (V_{DD} = 2.5 V, 5 V, & ±5 V, T_A = 25°C, and R_L ≥ 10 kΩ unless otherwise noted)

Parameter	Symbol	Conditions		Min	Typ	Max	Unit
Unity Gain Bandwidth	UGBW	R_L = 2 kΩ, C_L = 10 pF	V_{DD} = 2.5 V		3.2		MHz
			V_{DD} = 5 V to 10 V		3.5		
Slew Rate at Unity Gain	SR	$V_{O(pp)}$ = V_{DD}/2, R_L = 10 kΩ, C_L = 50 pF	V_{DD} = 2.5 V	1.35	2.0		V/μS
		T_A = −40°C to +125°C		1			
		$V_{O(pp)}$ = V_{DD}/2, R_L = 10 kΩ, C_L = 50 pF	V_{DD} = 5 V	1.45	2.3		
		T_A = −40°C to +125°C		1.2			
		$V_{O(pp)}$ = V_{DD}/2, R_L = 10 kΩ, C_L = 50 pF	V_{DD} = ±5 V	1.8	2.6		
		T_A = −40°C to +125°C		1.3			
Phase Margin	θ_m	R_L = 2 kΩ, C_L = 10 pF			45		°
Gain Margin		R_L = 2 kΩ, C_L = 10 pF			14		dB
Settling Time to 0.1%	t_S	V−step(pp) = 1 V, AV = −1, R_L = 2 kΩ, C_L = 10 pF	V_{DD} = 2.5 V		2.9		μS
		V−step(pp) = 1 V, AV = −1, R_L = 2 kΩ, C_L = 68 pF	V_{DD} = 5 V, ±5 V		2.0		
Total Harmonic Distortion plus Noise	THD+N	V_{DD} = 2.5 V, $V_{O(pp)}$ = V_{DD}/2, R_L = 2 kΩ, f = 10 kHz	AV = 1		0.004		%
			AV = 10		0.04		
			AV = 100		0.3		
		V_{DD} = 5 V, ± 5 V, $V_{O(pp)}$ = V_{DD}/2, R_L = 2 kΩ, f = 10 kHz	AV = 1		0.004		
			AV = 10		0.04		
			AV = 100		0.03		
Input−Referred Voltage Noise	e_n	f = 1 kHz			30		nV/$\sqrt{Hz}$
		f = 10 kHz			20		
Input−Referred Current Noise	i_n	f = 1 kHz			0.6		fA/$\sqrt{Hz}$



Figure 1. CMRR vs. Frequency



Figure 2. Input Bias and Offset Current vs. Temperature



Figure 3. 2.5 V V_{OL} vs. I_{out}



Figure 4. 2.5 V V_{OH} vs. I_{out}



Figure 5. 3.3 V V_{OL} vs. I_{out}



Figure 6. 3.3 V V_{OH} vs. I_{out}



Figure 7. V_{OL} vs. I_{out}



Figure 8. V_{OH} vs. I_{out}



Figure 9. 10 V V_{OL} vs. I_{out}



Figure 10. 10 V V_{OH} vs. I_{out}



Figure 11. Peak−to−Peak Output vs. Supply vs. Frequency



Figure 12. Supply Current vs. Supply Voltage



Figure 13. PSRR vs. Frequency



Figure 14. Open Loop Gain and Phase vs. Frequency



Figure 15. Gain Bandwidth Product vs. Temperature



Figure 16. Slew Rate vs. Supply Voltage



Figure 17. Slew Rate vs. Temperature



Figure 18. Voltage Noise vs. Frequency



Figure 19. 2.5 V Inverting Large Signal Pulse Response



Figure 20. 2.5 V Non−Inverting Large Signal Pulse Response



Figure 21. 2.5 V Inverting Small Signal Pulse Response



Figure 22. 2.5 V Non−Inverting Small Signal Pulse Response



Figure 23. 3 V Inverting Large Signal Pulse Response



Figure 24. 3 V Non−Inverting Large Signal Pulse Response



Figure 25. 3 V Inverting Small Signal Pulse Response



Figure 26. 3 V Non−Inverting Small Signal Pulse Response



Figure 27. 6 V Inverting Large Signal Pulse Response



Figure 28. 6 V Non−Inverting Large Signal Pulse Response



Figure 29. 6 V Inverting Small Signal Pulse Response



Figure 30. 6 V Non−Inverting Small Signal Pulse Response

APPLICATIONS



Figure 31. Voltage Reference



Figure 32. Wien Bridge Oscillator



$$V_{in}L = \frac{R1}{R1 + R2}\ (V_{OL} - V_{ref}) + V_{ref}$$

$$V_{in}H = \frac{R1}{R1 + R2}\ (V_{OH} - V_{ref}) + V_{ref}$$

$$H = \frac{R1}{R1 + R2}\ (V_{OH} - V_{OL})$$

Figure 33. Comparator with Hysteresis



Given: f_o = center frequency
$A(f_o)$ = gain at center frequency

Choose value f_o, C

Then : $R3 = \frac{Q}{\pi f_O C}$

$$R1 = \frac{R3}{2\,A(f_O)}$$

$$R2 = \frac{R1\,R3}{4Q^2\,R1 - R3}$$

For less than 10% error from operational amplifier, $((Q_O\,f_O)/BW) < 0.1$ where f_o and BW are expressed in Hz. If source impedance varies, filter may be preceded with voltage follower buffer to stabilize filter parameters.

Figure 34. Multiple Feedback Bandpass Filter

SC−88A (SC−70−5/SOT−353)
CASE 419A−02
ISSUE M

SCALE 2:1

DATE 11 APR 2023



NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETERS
3. 419A−01 OBSOLETE. NEW STANDARD 419A−02
4. DIMENSIONS D AND E1 DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.1016MM PER SIDE.

DIM	MILLIMETERS		
	MIN.	NOM.	MAX.
A	0.80	0.95	1.10
A1	---	---	0.10
A3	0.20 REF		
b	0.10	0.20	0.30
c	0.10	---	0.25
D	1.80	2.00	2.20
E	2.00	2.10	2.20
E1	1.15	1.25	1.35
e	0.65 BSC		
L	0.10	0.15	0.30



RECOMMENDED
MOUNTING FOOTPRINT

* For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

GENERIC MARKING DIAGRAM*



*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

XXX = Specific Device Code
M = Date Code
▪ = Pb−Free Package
(Note: Microdot may be in either location)

STYLE 1:
PIN 1. BASE
2. EMITTER
3. BASE
4. COLLECTOR
5. COLLECTOR

STYLE 2:
PIN 1. ANODE
2. EMITTER
3. BASE
4. COLLECTOR
5. CATHODE

STYLE 3:
PIN 1. ANODE 1
2. N/C
3. ANODE 2
4. CATHODE 2
5. CATHODE 1

STYLE 4:
PIN 1. SOURCE 1
2. DRAIN 1/2
3. SOURCE 1
4. GATE 1
5. GATE 2

STYLE 5:
PIN 1. CATHODE
2. COMMON ANODE
3. CATHODE 2
4. CATHODE 3
5. CATHODE 4

STYLE 6:
PIN 1. EMITTER 2
2. BASE 2
3. EMITTER 1
4. COLLECTOR
5. COLLECTOR 2/BASE 1

STYLE 7:
PIN 1. BASE
2. EMITTER
3. BASE
4. COLLECTOR
5. COLLECTOR

STYLE 8:
PIN 1. CATHODE
2. COLLECTOR
3. N/C
4. BASE
5. EMITTER

STYLE 9:
PIN 1. ANODE
2. CATHODE
3. ANODE
4. ANODE
5. ANODE

Note: Please refer to datasheet for style callout. If style type is not called out in the datasheet refer to the device datasheet pinout or pin assignment.

DOCUMENT NUMBER:	98ASB42984B	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	SC−88A (SC−70−5/SOT−353)	PAGE 1 OF 1

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

UDFN6 1.6x1.6, 0.5P
CASE 517AP
ISSUE O

DATE 26 OCT 2007



SCALE 4:1



TOP VIEW



SIDE VIEW



DETAIL A
OPTIONAL CONSTRUCTION



DETAIL B
OPTIONAL CONSTRUCTION

NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.30 mm FROM TERMINAL.
4. COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.

	MILLIMETERS	
DIM	MIN	MAX
A	0.45	0.55
A1	0.00	0.05
A3	0.13 REF	
b	0.20	0.30
D	1.60 BSC	
E	1.60 BSC	
e	0.50 BSC	
D2	1.10	1.30
E2	0.45	0.65
K	0.20	---
L	0.20	0.40
L1	0.00	0.15



BOTTOM VIEW

SOLDERMASK DEFINED MOUNTING FOOTPRINT*



DIMENSIONS: MILLIMETERS

*For additional information on our Pb−Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

GENERIC MARKING DIAGRAM*



XX = Specific Device Code
M = Date Code
▪ = Pb−Free Package

(Note: Microdot may be in either location)

*This information is generic. Please refer to device data sheet for actual part marking.
Pb−Free indicator, “G” or microdot “ ▪”, may or may not be present.

DOCUMENT NUMBER:	98AON25711D	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	6 PIN UDFN, 1.6X1.6, 0.5P	PAGE 1 OF 1

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, onsemi, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales