Low $V_{CE(sat)}$ PNP Transistors
60 V, 1 A

NSS60100DMT

onsemi's e²PowerEdge family of low $V_{CE(sat)}$ transistors are miniature surface mount devices featuring ultra low saturation voltage ($V_{CE(sat)}$) and high current gain capability. These are designed for use in low voltage, high speed switching applications where affordable efficient energy control is important.

Typical applications are DC−DC converters and LED lightning, power management…etc. In the automotive industry they can be used in air bag deployment and in the instrument cluster. The high current gain allows e²PowerEdge devices to be driven directly from PMU's control outputs, and the Linear Gain (Beta) makes them ideal components in analog amplifiers.

Features

- NSV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC−Q101 Qualified and PPAP Capable
- NSV60100DMTWTBG − Wettable Flanks Device
- These Devices are Pb−Free, Halogen Free/BFR Free and are RoHS Compliant

60 Volt, 1 Amp
PNP Low $V_{CE(sat)}$ Transistors



1

WDFN6
CASE 506AN

MARKING DIAGRAM

AP = Specific Device Code
M = Date Code
▪ = Pb−Free Package

(Note: Microdot may be in either location)

PIN CONNECTIONS





MAXIMUM RATINGS (T_A = 25°C)

Rating	Symbol	Max	Unit
Collector−Emitter Voltage	V_{CEO}	60	Vdc
Collector−Base Voltage	V_{CBO}	60	Vdc
Emitter−Base Voltage	V_{EBO}	6	Vdc
Collector Current − Continuous	I_C	1	A
Collector Current − Peak	I_{CM}	2	A

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance Junction−to−Ambient (Notes 1 and 2)	$R_{\theta JA}$	55	°C/W
Total Power Dissipation per Package @ T_A = 25°C (Note 2)	P_D	2.27	W
Thermal Resistance Junction−to−Ambient (Note 3)	$R_{\theta JA}$	69	°C/W
Power Dissipation per Transistor @ T_A = 25°C (Note 3)	P_D	1.8	W
Junction and Storage Temperature Range	T_J, T_{stg}	−55 to +150	°C

1. Per JESD51−7 with 100 mm² pad area and 2 oz. Cu (Dual Operation).
2. P_D per Transistor when both are turned on is one half of Total P_D or 1.13 Watts.
3. Per JESD51−7 with 100 mm² pad area and 2 oz. Cu (Single−Operation).

ORDERING INFORMATION

Device	Package	Shipping†
NSS60100DMTTBG	WDFN6 (Pb−Free)	3000/Tape & Reel
NSV60100DMTWTBG	WDFN6 (Pb−Free)	3000/Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

© Semiconductor Components Industries, LLC, 2016

Table 1. ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS					
Collector−Emitter Breakdown Voltage (I_C = −10 mA, I_B = 0)	$V_{(BR)CEO}$	−60			V
Collector−Base Breakdown Voltage (Ic = −0.1 mA, I_E = 0)	$V_{(BR)CBO}$	−80			V
Emitter−Base Breakdown Voltage (I_E = −0.1 mA, I_C = 0)	$V_{(BR)EBO}$	−6			V
Collector Cutoff Current (V_{CB} = −60 V, I_E = 0)	I_{CBO}			−100	nA
Emitter Cutoff Current (V_{BE} = −5.0 V)	I_{EBO}			−100	nA
ON CHARACTERISTICS					
DC Current Gain (Note 4) (I_C = −100 mA, V_{CE} = −2.0 V) (I_C = −500 mA, V_{CE} = −2.0 V) (I_C = −1 A, V_{CE} = −2.0 V) (I_C = −2 A, V_{CE} = −2.0 V	h_{FE}	 150 120 90 40	 230 180 140 80		
Collector−Emitter Saturation Voltage (Note 4) (I_C = −500 mA, I_B = −50 mA) (I_C = −1 A, I_B = −50 mA) (I_C = −1 A, I_B = −100 mA)	$V_{CE(sat)}$		 −0.115 −0.250 −0.200	 −0.160 −0.350 −0.300	V
Base − Emitter Saturation Voltage (Note 4) (I_C = −500 mA, I_B = −50 mA) (I_C = −1 A, I_B = −50 mA) (I_C = −1 A, I_B = −100 mA)	$V_{BE(sat)}$			 −1.0 −1.0 −1.1	V
Base−Emitter Turn−on Voltage (Note 4) (I_C = 500 mA, I_B = 50 mA)	$V_{BE(on)}$			−0.9	V
DYNAMIC CHARACTERISTICS					
Output Capacitance (V_{CB} = 10 V, f = 1.0 MHz)	C_{obo}		18		pF
Cutoff Frequency (I_C = 50 mA, V_{CE} = 2.0 V, f = 100 MHz)	f_T		155		MHz
SWITCHING TIMES					
Delay Time (V_{CC} = −10 V, I_C = −0.5 A, I_{B1} = −25 mA, I_{B2} = 25 mA)	t_d		15		ns
Rise Time (V_{CC} = −10 V, I_C = −0.5 A, I_{B1} = −25 mA, I_{B2} = 25 mA)	t_r		13		ns
Storage Time (V_{CC} = −10 V, I_C = −0.5 A, I_{B1} = −25 mA, I_{B2} = 25 mA)	t_s		360		ns
Fall Time (V_{CC} = −10 V, I_C = −0.5 A, I_{B1} = −25 mA, I_{B2} = 25 mA)	t_f		22		ns

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

4. Pulse Condition: Pulse Width = 300 μsec, Duty Cycle ≤ 2%

TYPICAL CHARACTERISTICS



Figure 1. DC Current Gain



Figure 2. DC Current Gain



Figure 3. Collector Current as a Function of Collector Emitter Voltage



Figure 4. Collector−Emitter Saturation Voltage



Figure 5. Collector−Emitter Saturation Voltage



Figure 6. Collector−Emitter Saturation Voltage

TYPICAL CHARACTERISTICS



Figure 7. Base−Emitter Saturation Voltage



Figure 8. Base−Emitter "ON" Voltage



Figure 9. Collector Saturation Region



Figure 10. Input Capacitance



Figure 11. Output Capacitance



Figure 12. f_T, Current Gain Bandwidth Product

TYPICAL CHARACTERISTICS



Figure 13. Power Derating



Figure 14. Thermal Resistance by Transistor



Figure 15. Thermal Resistance for Both Transistors



WDFN6 2x2, 0.65P
CASE 506AN
ISSUE H

DATE 25 JAN 2022



TOP VIEW

DETAIL A
OPTIONAL CONSTRUCTIONS

NOTES:

1. DIMENSIONING AND TOLERANCING PER. ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS
3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.30 MM FROM THE TERMINAL TIP.
4. COPLANARITY APPLIES TO THE EXPOSED PADS AS WELL AS THE TERMINALS.



SIDE VIEW



DETAIL B
OPTIONAL CONSTRUCTIONS

DIM	MILLIMETERS MIN.	MAX.
A	0.70	0.80
A1	0.00	0.05
A3	0.20 REF	
b	0.25	0.35
D	2.00 BSC	
D2	0.57	0.77
E	2.00 BSC	
E2	0.90	1.10
e	0.65 BSC	
F	0.95 BSC	
k	0.25 REF	
L	0.20	0.30
L1	---	0.10



BOTTOM VIEW



RECOMMENDED
MOUNTING FOOTPRINT
SOLDERMASK DEFINED

GENERIC MARKING DIAGRAM*

XX = Specific Device Code
M = Date Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	98AON20861D	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	WDFN6 2x2, 0.65P	PAGE 1 OF 1

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, onsemi, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales