NTND31225CZ

MOSFET – Small Signal, Complementary, XLLGAS6, 0.65mm x 0.90mm x 0.4mm

20 V

ON Semiconductor®

www.onsemi.com

Features

- Advanced Trench Complementary MOSFET
- Offers a Low $R_{DS(ON)}$ Solution in the Ultra Small 0.65 mm × 0.90 mm Package
- These Devices are Pb−Free, Halogen Free/BFR Free and are RoHS Compliant

Applications

- Small Signal Load Switch with Level Shift
- Analog Switch
- High Speed Interfacing
- Optimized for Power Management in Ultra Portable Products

$V_{(BR)DSS}$	$R_{DS(ON)}$ MAX	I_D Max
N−Channel 20 V	1.5 Ω @ 4.5 V	220 mA
	2.0 Ω @ 2.5 V	
	3.0 Ω @ 1.8 V	
	4.5 Ω @ 1.5 V	
P−Channel −20 V	5.0 Ω @ −4.5 V	−127 mA
	6.0 Ω @ −2.5 V	
	7.0 Ω @ −1.8 V	
	10.0 Ω @ −1.5 V	

MAXIMUM RATINGS (T_J = 25°C unless otherwise specified)

Parameter			Symbol	Value	Unit
Drain-to-Source Voltage		NMOS	V_{DSS}	20	V
		PMOS		−20	
Gate-to-Source Voltage		NMOS	V_{GSS}	±8	V
		PMOS		±8	
N−Channel Continuous Drain Current (Note 1)	Steady State	T_A = 25°C	I_D	220	mA
		T_A = 85°C		158	
	t ≤ 5 s	T_A = 25°C		253	
P−Channel Continuous Drain Current (Note 1)	Steady State	T_A = 25°C	I_D	−127	mA
		T_A = 85°C		−91	
	t ≤ 5 s	T_A = 25°C		−146	
Power Dissipation (Note 1)	Steady State	T_A = 25°C	P_D	125	mW
	t ≤ 5 s			166	
Pulsed Drain Current	NMOS	t_p = 10 μs	I_{DM}	846	mA
	PMOS			−488	
Source Current (Body Diode)			I_S	200	mA
				−200	
Operating Junction and Storage Temperature			T_J, T_{STG}	−55 to 150	°C
Lead Temperature for Soldering Purposes (1/8″ from case for 10 s)			T_L	260	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

DEVICE SYMBOL



XLLGA6
Case 713AC

MARKING DIAGRAM



L = Specific Device Code
M = Date Code

PINOUT DIAGRAM



(Bottom View)

ORDERING INFORMATION

See detailed ordering and shipping information on page 4 of this data sheet.

© Semiconductor Components Industries, LLC, 2015

1. Surface-mounted on FR4 board using the minimum recommended pad size, 1 oz Cu.

THERMAL RESISTANCE RATINGS

Parameter	Symbol	Max	Unit
Junction-to-Ambient (Note 2) Steady State t ≤ 5 s	$R_{\theta JA}$	 998 751	°C/W

2. Surface−mounted on FR4 board using 1 in sq pad size (Cu area = 1.127 in sq), 1 oz copper

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise specified)

Parameter	Symbol	FET	Test Condition		Min	Typ	Max	Unit
OFF CHARACTERISTICS								
Drain-to-Source Breakdown Voltage	$V_{(BR)DSS}$	N	V_{GS} = 0 V, I_D = 250 μA		20			V
		P	V_{GS} = 0 V, I_D = −250 μA		−20			
Zero Gate Voltage Drain Current	I_{DSS}	N	V_{GS} = 0 V, V_{DS} = 5 V	T_J = 25°C			50	nA
				T_J = 85°C			200	
			V_{GS} = 0 V, V_{DS} = 16 V	T_J = 25°C			100	
		P	V_{GS} = 0 V, V_{DS} = −5 V	T_J = 25°C			−50	
				T_J = 85°C			−200	
			V_{GS} = 0 V, V_{DS} = −16 V	T_J = 25°C			−100	
Gate-to-Source Leakage Current	I_{GSS}	N	V_{GS} = 0 V, V_{DS} = ±5 V				±100	nA
		P	V_{GS} = 0 V, V_{DS} = ±5 V				±100	
ON CHARACTERISTICS								
Gate Threshold Voltage	$V_{GS(TH)}$	N	V_{GS} = V_{DS}, I_D = 250 μA		0.4		1.0	V
		P	V_{GS} = V_{DS}, I_D = −250 μA		−0.4		−1.0	
Drain-to-Source On Resistance	$R_{DS(ON)}$	N	V_{GS} = 4.5 V, I_D = 100 mA			0.8	1.5	Ω
			V_{GS} = 2.5 V, I_D = 50 mA			1.1	2.0	
			V_{GS} = 1.8 V, I_D = 20 mA			1.4	3.0	
			V_{GS} = 1.5 V, I_D = 10 mA			1.8	4.5	
		P	V_{GS} = −4.5 V, I_D = −100 mA			2.1	5.0	
			V_{GS} = −2.5 V, I_D = −50 mA			2.7	6.0	
			V_{GS} = −1.8 V, I_D = −20 mA			3.6	7.0	
			V_{GS} = −1.5 V, I_D = −10 mA			4.2	10.0	
Forward Transconductance	g_{FS}	N	V_{DS} = 5 V, I_D = 125 mA			0.48		S
		P	V_{DS} = −5 V, I_D = −125 mA			0.35		
Forward Diode Voltage	V_{SD}	N	V_{GS} = 0 V, I_S = 10 mA			0.6	1.0	V
		P	V_{GS} = 0 V, I_S = −10 mA			−0.6	−1.0	

3. Switching characteristics are independent of operating junction temperatures.
Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise specified)

Parameter	Symbol	FET	Test Condition	Min	Typ	Max	Unit
CAPACITANCES							
Input Capacitance	C_{ISS}	N	V_{GS} = 0 V, f = 1 MHz, V_{DS} = 15 V		12.3		pF
Output Capacitance	C_{OSS}				3.4		
Reverse Capacitance	C_{RSS}				2.5		
Input Capacitance	C_{ISS}	P	V_{GS} = 0 V, f = 1 MHz, V_{DS} = −15 V		12.8		
Output Capacitance	C_{OSS}				2.8		
Reverse Capacitance	C_{RSS}				2.0		
SWITCHING CHARACTERISTICS, V_{GS} = 4.5 V							
Turn-On Delay Time	$t_{d(ON)}$	N	V_{GS} = 4.5 V, V_{DS} = 15 V, I_D = 200 mA, R_G = 2 Ω		16.5		ns
Rise Time	t_r				25.5		
Turn-Off Delay Time	$t_{d(OFF)}$				142		
Fall Time	t_f				80		
Turn-On Delay Time	$t_{d(ON)}$	P	V_{GS} = −4.5 V, V_{DS} = −15 V, I_D = −200 mA, R_G = 2 Ω		37		
Rise Time	t_r				71		
Turn-Off Delay Time	$t_{d(OFF)}$				280		
Fall Time	t_f				171		

3. Switching characteristics are independent of operating junction temperatures.

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

ORDERING INFORMATION

Device	Package	Shipping†
NTND31225CZTAG	XLLGA6 (Pb−Free)	8000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

TYPICAL CHARACTERISTICS – P–CHANNEL



Figure 1. On–Region Characteristics



Figure 2. Transfer Characteristics



Figure 3. On–Resistance vs. Gate–to–Source Voltage



Figure 4. On–Resistance vs. Drain Current and Gate Voltage



Figure 5. On–Resistance Variation with Temperature



Figure 6. Drain–to–Source Leakage Current vs. Voltage

TYPICAL CHARACTERISTICS – P–CHANNEL



Figure 7. Capacitance Variation



Figure 8. Resistive Switching Time Variation vs. Gate Resistance



Figure 9. Diode Forward Voltage vs. Current



Figure 10. Maximum Rated Forward Biased Safe Operating Area



Figure 11. Thermal Response

TYPICAL CHARACTERISTICS – N–CHANNEL



Figure 12. On–Region Characteristics



Figure 13. Transfer Characteristics



Figure 14. On–Resistance vs. Gate–to–Source Voltage



Figure 15. On–Resistance vs. Drain Current and Gate Voltage



Figure 16. On–Resistance Variation with Temperature



Figure 17. Drain–to–Source Leakage Current vs. Voltage

TYPICAL CHARACTERISTICS – N–CHANNEL



Figure 18. Capacitance Variation



Figure 19. Resistive Switching Time Variation vs. Gate Resistance



Figure 20. Diode Forward Voltage vs. Current



Figure 21. Maximum Rated Forward Biased Safe Operating Area



Figure 22. Thermal Response

XLLGA6 0.90x0.65
CASE 713AC
ISSUE O

SCALE 8:1

DATE 19 JUN 2014



NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994 .
2. CONTROLLING DIMENSION: MILLIMETERS.
3. POSITIONAL TOERANCE APPLIES TO ALL SIX LEADS.

DIM	MILLIMETERS MIN	MAX
A	0.340	0.440
A1	0.000	0.050
b	0.200	0.300
b2	0.080	0.180
D	0.900 BSC	
E	0.650 BSC	
e	0.295 BSC	
e1	0.340 BSC	
e2	0.300 BSC	
e3	0.208 BSC	
e4	0.158 BSC	
L	0.215	0.315
L2	0.115	0.215

GENERIC MARKING DIAGRAM*

X = Specific Device Code
M = Date Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “ ▪”, may or may not be present.

RECOMMENDED SOLDERING FOOTPRINT*



DIMENSIONS: MILLIMETERS

*For additional information on our Pb−Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

DOCUMENT NUMBER:	98AON86873F	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	XLLGA6 0.90X0.65	PAGE 1 OF 1

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, onsemi, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales