



DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	14.22	14.99	0.560	0.590
B	9.78	10.54	0.385	0.415
C	4.06	4.83	0.160	0.190
D	0.69	0.94	0.027	0.037
E	1.14	1.40	0.045	0.055
F	13.46	13.84	0.530	0.545
G	1.70	BSC	0.067	BSC
J	0.36	0.56	0.014	0.022
K	19.94	20.32	0.785	0.800
L	8.15	8.56	0.321	0.337
M	1.60	1.98	0.063	0.078
Q	3.71	3.96	0.146	0.156
R	6.88	8.15	0.271	0.321
S	3.71	4.98	0.146	0.196
U	11.68	12.07	0.460	0.475
W		5°		5°

NOTES:

- DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
- CONTROLLING DIMENSION: INCH.
- DIMENSION D DOES NOT INCLUDE INTERCONNECT BAR (DAM BAR) PROTRUSION. DIMENSION D INCLUDING PROTRUSION SHALL NOT EXCEED 10.92(0.043) MAXIMUM.

CASE NO.	314K-01
STATUS	ON SEMICONDUCTOR STANDARD
NEW STD	
USED ON	SERIES 10103



DOCUMENT NUMBER	98AON02822D
SHEET 2 OF 2	

ISSUE	REVISION	COORD/ DATE
0	INITIAL RELEASE REQ BY T. GRINTER	FB 01 AUG 00