ASSOCIATION ELECTRONICS	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.				This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.										
1752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Typhtp://www.ipc.org/IPC-175x Distribute				Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					erials and l	ials and Mfg Information				
Supplier	Information														
Company name* Company uniq				que ID U:			Unique ID Authority				Respo	Response Date*			
onsemi											2024-0	2024-04-25			
Contact Na	me	Title - Contact				Phone - Contact*				Email	Email - Contact*				
Product-E	nv-Stewards	Product Enviro Compliance				NA				Produ	Product-Env-Stewards@onsemi.com				
Authorized	Representative*	Title - Representative			1	Phone - Representative*				Email	Email - Representative*				
Product-E	nv-Stewards	Product Enviro Compliance				NA				Produ	Product-Env-Stewards@onsemi.com				
	Requester Item Number Mfr Item		n Number Mfr Item Name				Effective Da	ate Ver	sion	on Manufacturing Site		Weight*	UOM	Unit Type	
		74VHC157MX QUAD 2-INP		QUAD 2-INPUT N	T MULTIPLEXER		2024-04-25			PH1		147.797	mg	Each	
Manufac	turing Proccess Informa	ntion											,		
,	Terminal Plating / Grid Array Material To			Terminal Base Alloy J-STD-020 MSI		SL Rating	Peak Process Body Temperature		re Max Time at Pe	ak Temper	ature Nun	nber of Reflow Cyc	eles		
Matte Tin (Sn) - annealed			CU Alloy 1			260	260 C 30		30	seco	nds 3				
Comments															
evel 1 - ma	ximum time at peak temperat	ure during sol	dering is 10-3	30 seconds											
or more i	nformation regarding material	composition	please refer to	page 3											

RoHS Material Composition Declaration			Declaration Type *	Detail	ed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusivesource of the Supplier's Iability and the Company's remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty rights and/or remedies of Supplier's Sta											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the						

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	4.35	mg	Supplier	Silicon (Si)	7440-21-3		4.35	mg
Die Attach	0.44	mg		Epoxy resin	proprietary data		0.044	mg
			Supplier	Silver (Ag)	7440-22-4		0.352	mg
			Supplier	Formaldehyde Polymer	9003-36-5		0.044	mg
Lead Frame	46.4		Supplier	Silver (Ag)	7440-22-4		0.2042	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0603	mg
			Supplier	Iron (Fe)	7439-89-6		1.1136	mg
			Supplier	Copper (Cu)	7440-50-8		45.0034	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0186	mg
Mold Compound-Black	93.9			Epoxy resin	proprietary data		4.695	mg
			Supplier	Phenolic Resin	Proprietary Data		1.878	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		2.3475	mg
			Supplier	Carbon Black (C)	1333-86-4		0.4695	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		84.51	mg
Plating	2.31	mg	Supplier	Tin (Sn)	7440-31-5		2.31	mg
Wire Bond - Au	0.397	mg	Supplier	Gold (Au)	7440-57-5		0.397	mg