Authorized Representative* Product-Env-Stewards Requester Item Number Mfr Item Number Mfr Item Name Effective Date Version Manufacturing Site Weight* UOM ATP202-TL-H NCH 4.5V DRIVE SERIES Description Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Phone - Representative* NA Product-Env-Stewards@ons Weight* UOM 262.59 mg Peak Process Body Temperature Max Time at Peak Temperature Number of Reflo	ne substances within the manufacturer listed item. Nasses all lower level materials for which the manufacturer listed item.	Dosition Declaration IPC, Bannockburn, Illinois. All rights reserved under both un-American copyright conventions. This document is a declaration of level parts, the declaration enconventions.	
Company name* Company unique ID			us Materials and Mfg Information
nsemi ontact Name Title - Contact Title - Contact Phone - Contact* Product-Env-Stewards Title - Representative Title - Representative Title - Representative Product-Env-Stewards Title - Representative Title - Representative Phone - Representative* Product-Env-Stewards Ons Requester Item Number Mfr Item Number Mfr Item Name Effective Date Version Manufacturing Site Weight* UOM ATP202-TL-H NCH 4.5V DRIVE SERIES 2024-05-04 CNG 262.59 mg Iteminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Peak Process Body Temperature Max Time at Peak Temperature Number of Reflo			
Title - Contact Name Product-Env-Stewards Product-E	Response Da	Company unique ID Unique ID Authority	Response Date*
Product-Env-Stewards Authorized Representative* Title - Representative Product-Env-Stewards P	2024-05-04		2024-05-04
Authorized Representative* Product-Env-Stewards Product Enviro Compliance Requester Item Number Mfr Item Number Mfr Item Name Effective Date Version Manufacturing Site Weight* UOM ATP202-TL-H NCH 4.5V DRIVE SERIES Death of the series of th	Email - Cont	Title - Contact Phone - Contact*	Email - Contact*
Product-Env-Stewards Requester Item Number Mfr Item Number Mfr Item Name Effective Date Version Manufacturing Site Weight* UOM ATP202-TL-H NCH 4.5V DRIVE SERIES 2024-05-04 CNG 262.59 mg Manufacturing Proccess Information Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Peak Process Body Temperature Max Time at Peak Temperature Number of Reflo	Product-Env	Product Enviro Compliance NA	Product-Env-Stewards@onsemi.com
Requester Item Number Mfr Item Number Mfr Item Name Effective Date Version Manufacturing Site Weight* UOM ATP202-TL-H NCH 4.5V DRIVE SERIES 2024-05-04 CNG 262.59 mg Manufacturing Proccess Information Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Peak Process Body Temperature Max Time at Peak Temperature Number of Reflo	e* Email - Repr	Title - Representative Phone - Representa	Email - Representative*
ATP202-TL-H NCH 4.5V DRIVE SERIES 2024-05-04 CNG 262.59 mg Internal Plating Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Peak Process Body Temperature Max Time at Peak Temperature Number of Reflo	Product-Env	Product Enviro Compliance NA	Product-Env-Stewards@onsemi.com
Manufacturing Proccess Information Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Peak Process Body Temperature Max Time at Peak Temperature Number of Reflo	ion Manufacturing Site Weigl	Mfr Item Number Mfr Item Name Effective Date Ve	g Site Weight* UOM Unit Type
Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Peak Process Body Temperature Max Time at Peak Temperature Number of Reflo	CNG 262.5	ATP202-TL-H NCH 4.5V DRIVE SERIES 2024-05-04	262.59 mg Each
	W Tomposeture May Time at Peak Tomposeture		a at Back Tamparatura Number of Boflow Cycles
looptoing Di CH Alloy 1		CU Alloy 1 260	
Contains Di Co Anoy I 200 C 50 Seconds 5	Seconds Seconds	CU Anoy 1 200	seconds
omments		nune duning coldening is 10-20 seconds	
vel 1 - maximum time at peak temperature during soldering is 10-30 seconds or more information regarding material composition please refer to page 3		8 8	

RoHS Material Composition Declaration			Declaration Type *	Detailed					
Directive 2015/863/EU amending RoHS Directive 2011/65/EU									
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its provided certification is regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies of Supplier's Standard Terms and/conditions of Sale applicable to such part shall apply.									
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted substance	s per the definition above except for selected exemp	tions Supplier Acceptance	* Accepted					
Exemption: 7a: Lead in high melting temperature type solders (i.e. lead based solder alloys containing 85% by weight or more lead).									
Exemption List Version	EL-2011/534/EU								
Declaration Signature									
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.									
Supplier Digital Signature Ra	astislav Drska	-En							

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	1.66	mg	Supplier	Silicon (Si)	7440-21-3		1.66	mg
Die Attach	2.85	mg	Supplier	Silver (Ag)	7440-22-4		0.057	mg
			A	Lead (Pb)	7439-92-1	7a	2.6505	mg
			Supplier	Tin (Sn)	7440-31-5		0.1425	mg
Lead Frame	Lead Frame 148.06	mg	Supplier	Tin (Sn)	7440-31-5		0.2221	mg
			Supplier	Copper (Cu)	7440-50-8		147.8379	mg
Mold Compound-Black	106.72	mg		Epoxy Phenol Resin	proprietary data		0.8538	mg
			Supplier	Carbon Black (C)	1333-86-4		1.0672	mg
			Supplier	Aluminum Hydroxide (Al(OH)3)	21645-51-2		6.4032	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		85.376	mg
			Supplier	Ortho-Cresol Novolac Resin	29690-82-2		12.8064	mg
			Supplier	Silica Crystalline (SiO2)	14808-60-7		0.2134	mg
Plating	3.3	mg	В	Bismuth (Bi)	7440-69-9		0.0198	mg
			Supplier	Tin (Sn)	7440-31-5		3.2802	mg