IPC ASSOCIATION ELECTRONIC	© Copyright 2005.	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reser international and Pan-American copyright conventions.			der both	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with le level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.							sembly with lower responsibility.		
1752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Typhttp://www.ipc.org/IPC-175x Distribute									rials and M	ials and Mfg Information				
Supplie	r Information														
Company name*				npany unique ID			Unique ID Authority					Response Date*			
nsemi											2024-05	2024-05-02			
Contact N	ame		Title - Contact			1	Phone - Contact*				Email -	Email - Contact*			
Product-l	Env-Stewards		Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
uthorize	d Representative*	Title - Representative			I	Phone - Representative*				Email - Representative*					
Product-l	Env-Stewards	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com					
			Item Number Mfr Item Name			Effectiv		te Versi	on I	Manufacturing Site		Weight*	UOM	Unit Type	
			PSR PWM	PWM		2024-05-02 TAD		TAD	17.874		mg	Each			
<b>Aanufa</b>	cturing Process Informa	ation						·							
Terminal Plating / Grid Array Material Terminal Base All			Alloy J-	STD-020 MS	L Rating	Peak Pro	ocess Body	Temperatu	re Max Time at Peal	k Tempera	ure Num	ber of Reflow Cyc	eles		
Matte Tin (Sn) - annealed CU Alloy 1							260		C	30	secon	ds 3			
Comments															
vel 1 - m	aximum time at peak temperat	ture during sol	dering is 10-3	0 seconds											
or more	information regarding materia	l composition	please refer to	page 3											

RoHS Material Composition Declaration			Declaration Type *	Detail	ed				
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		ium (Cr6+), Polybrominated Biphenyls (PB)	erial for Cadmium and quantity limit of 0.1% b B), Polybrominated Diphenyl Ethers (PBDE), a						
cadmium, hexavalentchromium, polybromin contains a RoHS restricted substance inexce encompass all such components. Supplier cet as of the date that Supplier completes this Company acknowledges that Supplier may hindependently verified information provided certification in this paragraph. If the Compan	nated biphenyls and/or polybrominated diphess of an applicable quantity limit, please indriffes that it gathered the information it provom. Supplier acknowledges that Company wave relied on informationprovided by others of the supplier agrees that, at a minimusy and the Supplier enter into a written agree yesource of the Supplier's liability and the C	enyl ethers (each a "RoHS restricted substan licate below which, if any, RoHS exemption vides in this form using appropriate methods vill rely on this certification in determining the s in completing this form, and that Supplier um, itssuppliers have provided certifications ement with respect to the identified part, the tompany's remedies for issues that arise rega	s of the European Union member states) of the ce") in excess of the applicable quantity limit is you believe may apply. If the part is an assemb to ensure its accuracy and that such informatio e compliance of its products with European Ur may not have independently verified such infor regarding their contributions to the part, and the erms and conditions of that agreement, including information the Supplier provides in this	dentified above. If a ally with lower level in is true and correct tion member state la mation. However, in ose certifications are ag any warranty righ	homogeneous material within the part components, the declaration shall to the best of its knowledge and belief, was that implement the RoHS Directive. In situations where Supplier has not the at least as comprehensive as the lats and/or remedies provided as part of				
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted				
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.									
Exemption List Version	EL-2011/534/EU								
Declaration Signature									
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the				

## **Homogeneous Material Composition Declaration for Electronic Products**

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

<b>Homogeneous Material</b>	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.779	mg	Supplier	Silicon (Si)	7440-21-3		0.779	mg
Die Attach	0.099	mg	Supplier	Silver (Ag)	7440-22-4		0.0792	mg
			Supplier	Phenolic Resin-2	54208-63-8		0.0198	mg
Lead Frame	8.252	mg	Supplier	Silver (Ag)	7440-22-4		0.022	mg
			Supplier	Zinc (Zn)	7440-66-6		0.01	mg
			Supplier	Iron (Fe)	7439-89-6		0.198	mg
			Supplier	Copper (Cu)	7440-50-8		8.0201	mg
			Supplier	Phosphorus (P)	7723-14-0		0.002	mg
Mold Compound-Black	7.588	mg	Supplier	Ortho Cresol Novolac Resin	29690-82-2		1.9	mg
			Supplier	Carbon Black (C)	1333-86-4		0.038	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		5.65	mg
Plating	1.13	mg	Supplier	Tin (Sn)	7440-31-5		1.13	mg
Wire Bond - Au	0.026	mg	Supplier	Gold (Au)	7440-57-5		0.026	mg