IPC ASSOCIATION CONNE	Material Comp © Copyright 2005. international and Pa	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.				This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lowe level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.									
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					rials and M	ials and Mfc Information			
upplier Info	ormation								·						
Company name	**	Company unique ID			τ	Unique ID Authority				Respon	Response Date*				
nsemi											2024-05	2024-05-21			
Contact Name			Title - Contact			1	Phone - Contact*				Email - Contact*				
Product-Env-Stewards			Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
uthorized Rep	oresentative*	Title - Representative			1	Phone - Representative*				Email - Representative*					
Product-Env-St	tewards	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com					
Requ	Requester Item Number Mfr I		Item Number Mfr Item Name				Effective Dat	e Version	n I	Manufacturing Site		Weight*	UOM	Unit Type	
		FAN48630UC315X 3MHZ DC/DC B		3MHZ DC/DC Bo	ost 1.5A		2024-05-21 PBB		PBB		3.38704	mg	Each		
Ianufacturi	ing Proccess Informa	ation													
Terminal Plating / Grid Array Material			Terminal Base Alloy J-STD-020 MSI		SL Rating	Peak Process Body Temperatur		re Max Time at Peal	k Tempera	ture Numb	er of Reflow Cyc	eles			
SnAgCu			CU Alloy 1			260 C 30		30	secor	nds 3					
omments															
vel 1 - maximu	um time at peak temperat	ure during sol	ldering is 10	30 seconds											
or more inforn	nation regarding material	l composition	please refer t	o page 3											

RoHS Material Composition Declaration			Declaration Type *	Detail	ed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier have not with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusivesource of the Supplier's Itaalian and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the						

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	2.40717	mg	Supplier	Silicon (Si)	7440-21-3		2.3978	mg
			Supplier	Aluminum (Al)	7429-90-5		0.0094	mg
Solder Ball	0.973411	mg	Supplier	Silver (Ag)	7440-22-4		0.0389	mg
			Supplier	Tin (Sn)	7440-31-5		0.9296	mg
			Supplier	Copper (Cu)	7440-50-8		0.0049	mg
Under Bump Metal	0.006459	mg	Supplier	Titanium (Ti)	7440-32-6		0.0052	mg
			Supplier	Copper (Cu)	7440-50-8		0.0012	mg