© Cop	erial Composition byright 2005. IPC, B ational and Pan-Ame	annockbu	urn, Illinois. A	Il rights reserved untions.	under both	This docum level parts, t	ent is a declara the declaration	tion of the s encompasse	ubstances v s all lower	within the manufact level materials for	urer listed which the r	tem. Note: i nanufacturer	f the item is an as has engineering	ssembly with low responsibility.	
	IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				e *	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					ifg Informati	on			
upplier Information															
Company name*			Company unique ID			Unique ID Authority				Respon	Response Date*				
onsemi											2025-05	2025-05-13			
Contact Name Title			Title - Contac	Title - Contact			Phone - Contact*				Email -	Email - Contact*			
Product-Env-Stewards P			Product Enviro Compliance				NA				Produc	Product-Env-Stewards@onsemi.com			
Authorized Representative* Tit			Title - Representative			Phone - Representative*				Email -	Email - Representative*				
Product-Env-Stewards			Product Enviro Compliance				NA				Produc	Product-Env-Stewards@onsemi.com			
Requester Item Nu	Requester Item Number Mfr Item		n Number Mfr Item Name				Effective Date Version Manufacturing Si		Ianufacturing Site		Weight*	UOM	Unit Type		
	I	FDB0690N1507L FET 15		FET 150V 6.9 m	FET 150V 6.9 mOhm D2PAK		2025-05-13		С	СРА		1572.945	mg	Each	
Aanufacturing Procces	ss Information			-											
Terminal Plating /	Terminal Plating / Grid Array Material Terminal Base		Alloy	J-STD-020 MS	Peak Process Body Temperature Max Time at Peak			ık Tempera	Temperature Number of Reflow Cycles						
Matte Tin (Sn) - annealed CU A		U Alloy	1			245 C		С	30 seco		seconds 3				
omments															
vel 1 - maximum time at pe	eak temperature du	ring solo	dering is 10-3	0 seconds											
or more information regard	ding material comp	osition p	blease refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		mium (Cr6+), Polybrominated Biphenyls (Pl		dmium and quantity limit of 0.1% by mass (10 minated Diphenyl Ethers (PBDE), and Bis(2-et	
cadmium, hexavalentchromium, polybromina contains a RoHS restricted substance inexces encompass all such components. Supplier cer as of the date that Supplier completes this for Company acknowledges that Supplier may h independently verified information provided certification in this paragraph. If the Company	ated biphenyls and/or polybrominated dip s of an applicable quantity limit, please in iffies that it gathered the information it pr m.Supplier acknowledges that Company ave relied on informationprovided by oth by others, Supplier agrees that, at a minir and the Supplier enter into a written agr esource of the Supplier's liability and the	henyl ethers (each a "RoHS restricted substa ndicate below which, if any, RoHS exemption ovides in this form using appropriate methoo will rely on this certification in determining ers in completing this form, and that Supplie num, itssuppliers have provided certification eement with respect to the identified part, the Company's remedies for issues that arise reg	nce") in exco n you believe ls to ensure i the compliar r may not ha s regarding t terms and co	e may apply. If the part is an assembly with low s accuracy and that such information is true an ce of its products with European Union member de independently verified such information. Ho neir contributions to the part, and those certifica	ove. If a homogeneous material within the part er level components, the declaration shall d correct to the best of its knowledge and belief, er state laws that implement the RoHS Directive. wever, in situations where Supplier has not ations are at least as comprehensive as the anty rights and/or remedies provided as part of
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted subst	ances per the definition above except for sele	ected exempt	ions Supplier Acceptance	* Accepted
Exemption: 7a: Lead in high melting temp	erature type solders (i.e. lead based sol	der alloys containing 85% by weight or m	ore lead).		
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
Instructions: Complete all of the required Requester) and click on Submit Form to h			e drop-dowi	a. This will display the signature area. Digita	lly sign the declaration (if required by the
Supplier Digital Signature	astislav Drska	Le			

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless	otherwise noted).							
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	6.75	mg	Supplier	Silicon (Si)	7440-21-3		6.75	mg
Die Attach	2.271	mg	Supplier	Silver (Ag)	7440-22-4		0.057	mg
			А	Lead (Pb)	7439-92-1	7a	2.1	mg
			Supplier	Tin (Sn)	7440-31-5		0.114	mg
Lead Frame	921.0	mg	В	Nickel (Ni)	7440-02-0		0.092	mg
			Supplier	Iron (Fe)	7439-89-6		0.921	mg
			Supplier	Copper (Cu)	7440-50-8		919.7106	mg
			Supplier	Phosphorus (P)	7723-14-0		0.276	mg
Mold Compound-Black	626.0	mg	Supplier	Phenol, polymer with 1,4- bis(methoxymethyl)benzene	26834-02-6		31.3	mg
			Supplier	Proprietary	Proprietary Data		28.17	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		31.3	mg
			Supplier	Carbon Black (C)	1333-86-4		3.13	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		532.1	mg
Plating	0.224	mg	Supplier	Tin (Sn)	7440-31-5		0.224	mg
Wire Bond - Al	16.7	mg	Supplier	Aluminum (Al)	7429-90-5		16.7	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted).