| IPC ASSOCIATION ELECTRONIC | © Copyright 2005 | Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under bot international and Pan-American copyright conventions. | | | nder both | This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility. | | | | | | | | | |
|----------------------------|--|--|----------------------------|---------------|---------------------------|---|--------------------------------------|---------|-------------------|-----------------------------|---------------------------------|----------------|-----------------|------|--|
| 752-21.1 | IPC Web Site for Information on IPC-1752 Standard Form Typhttp://www.ipc.org/IPC-175x Distribute | | | | Form Type * Distribute | * Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater | | | | aterials and | ials and Mfg Information | | | | |
| Supplie | r Information | | | | | | · | | | | | | | | |
| Company name* Company | | | | any unique ID | | | Unique ID Authority | | | | Respo | Response Date* | | | |
| nsemi | | | | | | | | | | | 2024- | 2024-05-01 | | | |
| Contact N | Name | Title - Contact | | | I | Phone - Contact* | | | | Emai | Email - Contact* | | | | |
| Product-l | Env-Stewards | Product Enviro Compliance | | | | NA | | | | Prod | Product-Env-Stewards@onsemi.com | | | | |
| uthorize | ed Representative* | Title - Representative | | | I | Phone - Representative* | | | | Emai | Email - Representative* | | | | |
| Product-l | Env-Stewards | Product Enviro Compliance | | | | NA | | | | Prod | Product-Env-Stewards@onsemi.com | | | | |
| | Requester Item Number Mfr Item | | n Number Mfr Item Name | | | | Effective Date Version Manufacturing | | Ianufacturing Sit | e | Weight* | UOM | Unit Type | | |
| | | FOD816 | FOD8160V SSO5 3.3V 10MB | | VDE | | 2024-05-01 | -01 PBI | | В | | 197.151 | mg | Each | |
| Ianufa | ncturing Proccess Inform | nation | | | | | | | | | | | · | | |
| | 3 · · · · · · · · · · · · · · · · · · · | | Terminal Base Alloy J-STD- | | -STD-020 MSL | Rating | | | Temperatur | perature Max Time at Peak T | | rature Numb | er of Reflow Cy | eles | |
| Matte Tin (Sn) - annealed | | | U Alloy 1 | | | 260 | C | | 30 se | | seconds 3 | | | | |
| omments | • | | | | | | | | | | | | | | |
| <u>vel 1 - m</u> | naximum time at peak temper | ature during so | ldering is 10-3 | 30 seconds | | | | | | | | | | | |
| or more | information regarding mater | al composition | please refer to | o page 3 | | | | | | | | | | | |

| RoHS Material Composition Declaration | | | Declaration Type * | Detail | ed | | | | | | |
|---|---|---|---|---|---|--|--|--|--|--|--|
| Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP). | | | | | | | | | | | |
| cadmium, hexavalentchromium, polybromin contains a RoHS restricted substance inexce encompass all such components. Supplier cet as of the date that Supplier completes this Company acknowledges that Supplier may hindependently verified information provided certification in this paragraph. If the Compan | nated biphenyls and/or polybrominated diphess of an applicable quantity limit, please indriffes that it gathered the information it provom. Supplier acknowledges that Company wave relied on informationprovided by others of the supplier agrees that, at a minimusy and the Supplier enter into a written agree yesource of the Supplier's liability and the C | enyl ethers (each a "RoHS restricted substan licate below which, if any, RoHS exemption vides in this form using appropriate methods vill rely on this certification in determining the s in completing this form, and that Supplier um, itssuppliers have provided certifications ement with respect to the identified part, the tompany's remedies for issues that arise rega | s of the European Union member states) of the ce") in excess of the applicable quantity limit is you believe may apply. If the part is an assemb to ensure its accuracy and that such informatio e compliance of its products with European Ur may not have independently verified such infor regarding their contributions to the part, and the erms and conditions of that agreement, including information the Supplier provides in this | dentified above. If a ally with lower level in is true and correct tion member state la mation. However, in ose certifications are ag any warranty righ | homogeneous material within the part components, the declaration shall to the best of its knowledge and belief, was that implement the RoHS Directive. In situations where Supplier has not the at least as comprehensive as the lats and/or remedies provided as part of | | | | | | |
| RoHS Declaration * 1 - Item | (s) does not contain RoHS restricted substar | nces per the definition above | Supplier A | cceptance * | Accepted | | | | | | |
| Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions. | | | | | | | | | | | |
| Exemption List Version | EL-2011/534/EU | | | | | | | | | | |
| Declaration Signature | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | e "Accepted" on the Supplier Acceptance | drop-down. This will display the signature a | rea. Digitally sign t | the declaration (if required by the | | | | | | |

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

| Homogeneous Material | nogeneous Material Weight Unit of Measure Level Substance | | Substance | CAS | Exempt | Weight | Unit of Measure | |
|----------------------|---|----|-------------------|---|------------|--------|-----------------|----|
| Coupling Gel | 3.5 mg Supplier Dimethyl Siloxane | | Dimethyl Siloxane | 68083-19-2 | | 3.5 | mg | |
| Die | 1.131 | mg | В | Gallium Arsenide (AsGa) | 1303-00-0 | | 0.071 | mg |
| | | | Supplier | Silicon (Si) | 7440-21-3 | | 1.06 | mg |
| Die Attach | 0.223 | mg | Supplier | Silver (Ag) | 7440-22-4 | | 0.1784 | mg |
| | | | Supplier | Phenolic Resin-2 | 54208-63-8 | | 0.0446 | mg |
| Lead Frame | 36.392 | mg | Supplier | Silver (Ag) | 7440-22-4 | | 0.2 | mg |
| | | | Supplier | Zinc (Zn) | 7440-66-6 | | 0.044 | mg |
| | | | Supplier | Iron (Fe) | 7439-89-6 | | 0.837 | mg |
| | | | Supplier | Copper (Cu) | 7440-50-8 | | 35.3 | mg |
| | | | Supplier | Phosphorus (P) | 7723-14-0 | | 0.011 | mg |
| Mold Compound-Black | 153.98 | mg | Supplier | Titanium Dioxide (TiO2) | 13463-67-7 | | 30.8 | mg |
| | | | Supplier | 2,6-dibromo-4-[1-(3-bromo-4-hydroxyphenyl)-1-methylethyl]phenol | 6386-73-8 | | 6.16 | mg |
| | | | Supplier | Ortho Cresol Novolac Resin | 29690-82-2 | | 35.4 | mg |
| | | | В | Antimony Trioxide (Sb2O3) | 1309-64-4 | | 4.62 | mg |
| | | | Supplier | Fused Silica (SiO2) | 60676-86-0 | | 77 | mg |
| Plating | 1.69 | mg | Supplier | Tin (Sn) | 7440-31-5 | | 1.69 | mg |
| Wire Bond - Au | 0.235 | mg | Supplier | Gold (Au) | 7440-57-5 | | 0.235 | mg |