IPC - ASSOCIATION CONNECT ELECTRONICS INDUSTR	© Copyright 2005. II	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.			ler both	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.								
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Typhttp://www.ipc.org/IPC-175x Distribute				Declaration Class * Class 6 - RoHS Yes/No. Homogeneous Materi					ials and Mfc Information			
upplier Infor	mation								,					
Company name*		Company unique ID			τ	Unique ID Authority				Response Date*				
nsemi											2024-04-25			
Contact Name		Title - Contact			P	Phone - Contact*				Email - Contact*				
Product-Env-Stev	wards		Product Enviro Compliance			1	NA				Product-Env-Stewards@onsemi.com			
uthorized Repre	sentative*	Title - Representative			P	Phone - Representative*				Email - Representative*				
Product-Env-Stev	wards	Product Enviro Compliance			1	NA				Product-Env-Stewards@onsemi.com				
Reques	ster Item Number	Mfr Item Number		Mfr Item Name			Effective Date	Version	M	Manufacturing Site		Veight*	UOM	Unit Type
	FUSB302BUCX USB-C Port Con		USB-C Port Contro	l w/ PD		2024-04-25 MY1		IY1	1	.902276	mg	Each		
	g Proccess Informa								·					·
				ninal Base Alloy J-STD-020 MSL Rating			Peak Process Body Temperature Max Time at Peak Tem				Temperati	are Numbe	er of Reflow Cyc	cles
SnAgC	u	C	CU Alloy	1			260		С	30	second	ds 3		
omments														
vel 1 - maximum	time at peak temperatu	ire during sol	dering is 10	30 seconds										
or more informa	tion regarding material	composition <sub>j</sub>	please refer t	o page 3										

RoHS Material Composition Declaration			Declaration Type *	Detail	ed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU  RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
cadmium, hexavalentchromium, polybromin contains a RoHS restricted substance inexce encompass all such components. Supplier cet as of the date that Supplier completes this Company acknowledges that Supplier may hindependently verified information provided certification in this paragraph. If the Compan	nated biphenyls and/or polybrominated diphess of an applicable quantity limit, please indriffes that it gathered the information it provom. Supplier acknowledges that Company wave relied on informationprovided by others of the supplier agrees that, at a minimusy and the Supplier enter into a written agree yesource of the Supplier's liability and the C	enyl ethers (each a "RoHS restricted substan licate below which, if any, RoHS exemption vides in this form using appropriate methods vill rely on this certification in determining the s in completing this form, and that Supplier um, itssuppliers have provided certifications ement with respect to the identified part, the tompany's remedies for issues that arise rega	s of the European Union member states) of the ce") in excess of the applicable quantity limit is you believe may apply. If the part is an assemb to ensure its accuracy and that such informatio e compliance of its products with European Ur may not have independently verified such infor regarding their contributions to the part, and the erms and conditions of that agreement, including information the Supplier provides in this	dentified above. If a ally with lower level in is true and correct tion member state la mation. However, in ose certifications are ag any warranty righ	homogeneous material within the part components, the declaration shall to the best of its knowledge and belief, was that implement the RoHS Directive. In situations where Supplier has not the at least as comprehensive as the lats and/or remedies provided as part of						
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the						

## **Homogeneous Material Composition Declaration for Electronic Products**

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Backside Protection Film	0.057028	mg		Epoxy resin	proprietary data		0.0119	mg
			Supplier	Carbon Black (C)	1333-86-4		0.001	mg
			Supplier	Acrylic resins	Proprietary Data		0.0119	mg
			Supplier	Silica (SiO2)	14464-46-1		0.0321	mg
Die	1.27178	mg	Supplier	Silicon (Si)	7440-21-3		1.2648	mg
			Supplier	Aluminum (Al)	7429-90-5		0.007	mg
Solder Ball	0.547544	mg	Supplier	Silver (Ag)	7440-22-4		0.0214	mg
			Supplier	Tin (Sn)	7440-31-5		0.5229	mg
			Supplier	Copper (Cu)	7440-50-8		0.0033	mg
Under Bump Metal	0.025924	924 mg	Supplier	Titanium (Ti)	7440-32-6		0.0002	mg
			Supplier	Copper (Cu)	7440-50-8		0.0258	mg