ABSOLATION CONNECTING LECTRODUCS INDUSTRIES® INCOMPETING OF INCOMP	Bannockt	ourn, Illinois. A	ll rights reserved untions.	under both	This docume level parts, t	ent is a declar the declaratio	ation of the n encompass	substances ses all lowe	within the er level mate	manufacture erials for wh	er listed ite ich the ma	m. Note: i nufacturer	f the item is an as has engineering	sembly with lower responsibility.
	IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				e *	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					als and Mfg Information			
Supplier Information														
Company name* Cor			Company unique ID			Unique ID Authority					Response Date*			
onsemi											2025-06-06			
Contact Name Title - Contact			et	Phone - Contact*				Email			il - Contact*			
Product-Env-Stewards Product Er			duct Enviro Compliance			NA					Product-Env-Stewards@onsemi.com			
Authorized Representative* Title - Re			- Representative			Phone - Representative*				Email - Representative*				
Product-Env-Stewards	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com					
Requester Item Number	Mfr Item Number		Mfr Item Name			Effective Da	Pate Version Manufacturing Site		ing Site	W	eight*	UOM	Unit Type	
	M74LCX G			G CMOS TRNSCIEVR 16BIT		2025-06-06]	PH1		19	2.45	mg	Each
Manufacturing Proccess Informatio	n													
Terminal Plating / Grid Array Mater	ial T	Terminal Base Alloy		J-STD-020 MS	MSL Rating P		Peak Process Body Temperature Ma		re Max Ti	Max Time at Peak Temperate		re Number of Reflow Cycles		
Precious metal (e.g. Ag,Au, NiPdAu) (no C Sn)		CU Alloy 1		1		260		C	30 sec		second	seconds 3		
Comments									•					
evel 1 - maximum time at peak temperature	during so	dering is 10-3	0 seconds											
For more information regarding material co	nposition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed							
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	(Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Disobutyl phthalate (DIBP).											
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of							
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	on above	Supplier Acceptance	* Accepted								
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.												
Exemption List Version	EL-2011/534/EU											
Declaration Signature												
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the							
Supplier Digital Signature Ra	stislav Drska	Le										

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	2.3	mg	Supplier	Silicon (Si)	7440-21-3		2.3	mg	
Die Attach	3.83	mg	Supplier	Silver (Ag)	7440-22-4		2.8725	mg	
			Supplier	Epoxy resins	129915-35-1		0.9575	mg	
Lead Frame	60.05	mg	Supplier	Iron (Fe)	7439-89-6		1.1409	mg	
			Supplier	Copper (Cu)	7440-50-8		58.909	mg	
Mold Compound-Black	117.21	mg		Epoxy resin	proprietary data		5.8605	mg	
			Supplier	Phenolic Resin	Proprietary Data		5.8605	mg	
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		2.3442	mg	
			Supplier	Carbon Black (C)	1333-86-4		0.586	mg	
			Supplier	Fused Silica (SiO2)	60676-86-0		102.5587	mg	
Plating	7.91	mg	Supplier	Palladium (Pd)	7440-05-3		0.6012	mg	
			В	Nickel (Ni)	7440-02-0		7.1981	mg	
			Supplier	Gold (Au)	7440-57-5		0.1107	mg	
Wire Bond - Au	1.15	mg	Supplier	Gold (Au)	7440-57-5		1.15	mg	

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signar range of distribution unless otherwise noted)