BC SECIATION CONNECTING ECTRONICS INDUSTRIES® AND ADDRESS INDUSTRIES® INDUSTRIES®					This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.								
	IPC Web Site for Information on IPC-1752 Standard Form				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materia				als and Mfg Information				
Supplier Information													
Company name* Co			Company unique ID			Unique ID Authority				Response Date*			
onsemi								2025-06-05					
ontact Name Title - Contact			ct		Phone - Contact*			Email - Contact*					
Product-Env-Stewards Product Envi			nviro Compliance			NA				Product-Env-Stewards@onsemi.com			
Authorized Representative* Title - Representative			presentative			Phone - Representative*			Email - Representative*				
Product-Env-Stewards Produ			Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com			
Requester Item Number	Mfr Item Number		Mfr Item Name			Effective Date	Version	M	Manufacturing Site		Weight*	UOM	Unit Type
	MC3336	MC33363ADWR2G ANA HI VOL		OFFLN SW REG		2025-06-05		PF	PH1		142.68	mg	Each
Manufacturing Proccess Informati	on												
Terminal Plating / Grid Array Mat	Terminal Plating / Grid Array Material Terminal Base Allo		Alloy J	-STD-020 MSL	Rating	Peak Proc	ess Body Ten	nperature	Max Time at Peak	Tempera	ture Numb	er of Reflow Cyc	eles
Matte Tin (Sn) - annealed CU Alloy			3	3		260	0	2	30	secor	nds 3		
Comments													
ATTENTION: MSL 3 Rated item requires	Bake and D	ry Pack (after	electrical test)										
for more information regarding material c	omposition	please refer to	page 3										

RoHS Material Composition Declaration				Declaration Type *	Detailed							
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Dibutyl phthalate (DBP), Dibutyl phthalate (DBP).											
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of							
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	on above	Supplier Acceptance	* Accepted								
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all							
Exemption List Version	EL-2011/534/EU											
Declaration Signature												
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the							
Supplier Digital Signature Ra	stislav Drska	Le										

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

signs range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	2.73	mg	Supplier	Silicon (Si)	7440-21-3		2.73	mg	
Die Attach	4.85	mg	Supplier	Silver (Ag)	7440-22-4		3.6375	mg	
			Supplier	Epoxy resins	129915-35-1		1.2125	mg	
Lead Frame	75.92	mg	Supplier	Silver (Ag)	7440-22-4		0.7592	mg	
			Supplier	Zinc (Zn)	7440-66-6		0.1518	mg	
			Supplier	Iron (Fe)	7439-89-6		1.9739	mg	
			Supplier	Copper (Cu)	7440-50-8		73.035	mg	
Mold Compound-Black	55.11	mg		Epoxy Phenol Resin	proprietary data		5.7866	mg	
			Supplier	Fused Silica (SiO2)	60676-86-0		49.3234	mg	
Plating	3.73	mg	Supplier	Tin (Sn)	7440-31-5		3.73	mg	
Wire Bond - Cu	0.34	mg	Supplier	Copper (Cu)	7440-50-8		0.34	mg	

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signar range of distribution unless otherwise noted)