ABSOCIATION CONNECTING ELECTRONICE INDUSTRIES® INCLUSTRIES®	ckburn, Illinois, A	Ill rights reserved untions.	under both	This docume level parts, t	ent is a declaration	ion of the s encompasse	ubstances es all lowe	within the materi	anufacture als for whi	r listed item. I ich the manuf	Note: if th acturer ha	e item is an as s engineering	sembly with lowe responsibility.	
52-21.1 IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distributed				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					us Material	als and Mfg Information				
Supplier Information														
Company name* Company unique ID				Unique ID Authority					]	Response Date*				
onsemi										2025-09-11				
Contact Name	e Title - Contact			]	Phone - Contact*				]	Email - Contact*				
Product-Env-Stewards Product Enviro Compliance				NA						Product-Env-Stewards@onsemi.com				
Authorized Representative* Title - Representative				Phone - Representative*					1	Email - Representative*				
Product-Env-Stewards Product Enviro Compl			Compliance		NA					Product-Env-Stewards@onsemi.com				
Requester Item Number Mfr 1	tem Number	Mfr Item Name		·	Effective Date	Version		Manufacturing Site		Weig	nt*	UOM	Unit Type	
MC7	4AC74DG LOG CMOS D FLI		LIP FLOP DUAI	L	2025-09-11 PH1		PH1		122.0	5	mg	Each		
Manufacturing Proccess Information												·	· · ·	
Terminal Plating / Grid Array Material	Terminal Base Alloy J-STD-020			Rating	Peak Process Body Temperature Max Time at Pea			e at Peak T	Temperature Number of Reflow Cycles					
Matte Tin (Sn) - annealed CU Alloy 1			1		260		С	30		seconds	3			
Comments														
evel 1 - maximum time at peak temperature during	soldering is 10-3	0 seconds												
or more information regarding material composit	on please refer to	page 3												

RoHS Material Composition Declaration				Declaration Type *	Detailed							
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a that agreement, will be the sole and exclusives	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ess of the applicable quantity limit identified above may apply. If the part is an assembly with low is accuracy and that such information is true and ce of its products with European Union membe we independently verified such information. How heir contributions to the part, and those certificat anditions of that agreement, including any warra	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of							
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	on above	Supplier Acceptance	* Accepted								
Exemption: If the declared item does not con applicable exemptions.	U  (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl    phthalate (BBP), Dibutyl phthalate (DBP), Dibiobutyl phthalate (DBP).  Disobutyl phthalate (DBP).    her any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified above. If a homogeneous material within the part icide uses of an applicable quantity limit identified above. If a homogeneous material within the part icide uses of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall onpresente increases of an applicable guantity limit ideate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration in determining the compliance of its products with European Union member state laws that implement the RoHS Directive, ges that Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive, argraph. If the Company and the Supplier refer into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of be the sole and exclusivesource of the Supplier's Standard Terms andConditions of Sale applicable to such part shall apply.    *  1 - Item(s) does not contain RoHS restricted substances per the definition above  Supplier Acceptance *  Accepted    ion  EL-2011/534/EU											
Exemption List Version	EL-2011/534/EU											
Declaration Signature												
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	h. This will display the signature area. Digital	lly sign the declaration (if required by the							
Supplier Digital Signature Ra	stislav Drska	Le										

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).										
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure		
Die	0.98	mg	Supplier	Silicon (Si)	7440-21-3		0.98	mg		
Die Attach	4.44	mg	Supplier	Silver (Ag)	7440-22-4		3.33	mg		
			Supplier	Epoxy resins	129915-35-1		1.11	mg		
Lead Frame 69.6	69.62	mg	Supplier	Silver (Ag)	7440-22-4		0.7658	mg		
			Supplier	Zinc (Zn)	7440-66-6		0.1392	mg		
			Supplier	Iron (Fe)	7439-89-6		1.8101	mg		
			Supplier	Copper (Cu)	7440-50-8		66.9048	mg		
Mold Compound-Black	43.43	mg		Epoxy Phenol Resin	proprietary data		4.5601	mg		
			Supplier	Fused Silica (SiO2)	60676-86-0		38.8699	mg		
Plating	3.27	mg	Supplier	Tin (Sn)	7440-31-5		3.27	mg		
Wire Bond - Au	0.31	mg	Supplier	Gold (Au)	7440-57-5		0.31	mg		

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted)