ASSOCIATION CONNECTING ELECTRONICS INDUSTRIES® INFORMATION CONNECTING INDUSTRIES® INFORMATION CONNECTING	burn, Illinois. All rights reserved u	Inder both This docur level parts,	nent is a decla the declaratio	ration of the sul on encompasses	bstances v all lower	vithin the manufactur level materials for wh	er listed ite	m. Note: if t nufacturer h	he item is an as as engineering	sembly with lower responsibility.	
IPC Web Site for Information or http://www.ipc.org/IPC-175x	IPC Web Site for Information on IPC-1752 Standard Form Type ³ http://www.ipc.org/IPC-175x Distribute			Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials and Mfg Info					n		
Supplier Information											
Company name*		Unique ID Authority				Response Date*					
onsemi	mi			2024-05-14							
Contact Name	Name Title - Contact			Phone - Contact*				Email - Contact*			
Product-Env-Stewards		NA				Product-Env-Stewards@onsemi.com					
Authorized Representative*	zed Representative* Title - Representative			Phone - Representative*				Email - Representative*			
oduct-Env-Stewards Product Enviro Compliance		NA				Product-Env-Stewards@onsemi.com					
Requester Item Number Mfr Ite	m Number Mfr Item Name	Mfr Item Name		ate Version	М	Manufacturing Site		'eight*	UOM	Unit Type	
NB3H0 2G	0113GH4MTR 3.3 V Programma with Single Ender	able OmniClock Generator d LVCMOS Output	2024-05-14	2024-05-14 MY1		IY1	8.51		mg	Each	
Manufacturing Proccess Information											
Terminal Plating / Grid Array Material	Terminal Base Alloy	J-STD-020 MSL Rating	Peak P	Peak Process Body Temperature		e Max Time at Peak Temperat		erature Number of Reflow Cycles		les	
Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)	CU Alloy	1	260		C 30		seconds 3				
Comments											
evel 1 - maximum time at peak temperature during s	oldering is 10-30 seconds										
or more information regarding material compositio	please refer to page 3										

RoHS Material Composition Declaration				Declaration Type *	Detailed
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth	
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the
Supplier Digital Signature Ra	stislav Drska	Le			

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.85	mg	Supplier	Silicon (Si)	7440-21-3		0.85	mg
Die Attach Epoxy	0.09	mg		Epoxy resin	proprietary data		0.0585	mg
			Supplier	Aluminum Trioxide (Al2O3)	1344-28-1		0.0315	mg
Lead Frame	2.86	mg	Supplier	Tin (Sn)	7440-31-5		0.0071	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0063	mg
			Supplier	Chromium (Cr)	7440-47-3		0.0071	mg
			Supplier	Copper (Cu)	7440-50-8		2.8394	mg
Mold Compound-Black	4.52	mg		Epoxy resin	proprietary data		0.2124	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		0.452	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0045	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		3.6386	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.2124	mg
Plating	0.1	mg	Supplier	Palladium (Pd)	7440-05-3		0.0024	mg
			В	Nickel (Ni)	7440-02-0		0.088	mg
			Supplier	Gold (Au)	7440-57-5		0.0096	mg
Vire Bond - Au	0.09	mg	Supplier	Gold (Au)	7440-57-5		0.09	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).