ASSOCIATION CONNEC	© Copyright 2005, IPC, H	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.				This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with low level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.										
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater						als and Mf	g Infori	mation		
Supplier Infor	rmation															
Company name*			Company unique ID			Ţ	Unique ID Authority					Response Date*				
nsemi												2024-05-03				
Contact Name			Title - Contact			I	Phone - Contact*					Email - Contact*				
Product-Env-Ste	wards		Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com					
uthorized Repre	esentative*	Title - Representative			I	Phone - Representative*				Email - Representative*						
Product-Env-Ste	wards	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com						
Reque	ester Item Number	Mfr Item	Item Number Mfr Item Name				Effective Da	te Versio	Version Manufa		ing Site	V	/eight*	* UOM	I U	Jnit Type
		NC7WZ240K8X		DUAL UHS INVERTING BUFFER		FER	2024-05-03 THB		11.4		1.479	mg	F	Each		
<b>Ianufacturin</b>	g Proccess Information			,												
Termin	al Plating / Grid Array Material		Terminal Base Alloy		J-STD-020 MS	SL Rating	Peak Pro	Peak Process Body Temperature		re Max Time at Peak Temper		Temperatu	ure Number of Reflow Cycles			
Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)			CU Alloy 1		1		260		С	30 seco		second	ls <b>3</b>			
Comments																
vel 1 - maximun	n time at peak temperature d	uring sol	dering is 10-3	0 seconds												
or more informa	ation regarding material com	position p	please refer to	page 3												

RoHS Material Composition Declaration			Declaration Type *	Detail	led						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU  RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledges and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substa	ances per the definition above	Supplier Ac	ceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructional Complete all of the required	fields on all neggs of this form. Calcut th		a duan dawn. This will display the signature on	a Digitally sign	the declaration (if recruired by the						
Instructions: Complete all of the required Requester) and click on Submit Form to			e drop-down. This will display the signature ar	ea. Digitally sign	the declaration (if required by the						

## **Homogeneous Material Composition Declaration for Electronic Products**

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.15	mg	Supplier	Silicon (Si)	7440-21-3		0.15	mg
Die Attach Tape	0.019	mg	Supplier	Oxirane, (chloromethyl)-, homopolymer	24969-06-0		0.0029	mg
			Supplier	2-Propenoic acid, 2-methyl-, polymer with butyl 2-propenoate and methyl 2-methyl-2-propenoate	25035-69-2		0.0029	mg
			Supplier	Proprietary	Proprietary Data		0.0019	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		0.0085	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.0029	mg
Lead Frame	4.7	mg	Supplier	Zinc (Zn)	7440-66-6		0.0056	mg
			Supplier	Iron (Fe)	7439-89-6		0.1104	mg
			Supplier	Copper (Cu)	7440-50-8		4.5825	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0014	mg
Mold Compound-Black	6.5	mg		Epoxy resin	proprietary data		0.325	mg
			Supplier	Phenolic Resin	Proprietary Data		0.13	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.1625	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0325	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		5.85	mg
Plating	0.09	mg	Supplier	Palladium (Pd)	7440-05-3		0.0022	mg
			В	Nickel (Ni)	7440-02-0		0.0792	mg
			Supplier	Gold (Au)	7440-57-5		0.0086	mg
Wire Bond - Cu	0.02	mg	Supplier	Palladium (Pd)	7440-05-3		0.0004	mg
			Supplier	Gold (Au)	7440-57-5		0	mg
			Supplier	Copper (Cu)	7440-50-8		0.0196	mg