IPC ASSOCIATION ELECTRONICS	© Copyright 2005.	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under bo international and Pan-American copyright conventions.			der both This d	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lowe level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.									
1752-21.1					Form Type * Distribute	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					ials and Mfg Information				
Supplier	Information														
Company name*				ompany unique ID			Unique ID Authority					Response Date*			
nsemi											2025-05-13				
Contact Na	ame		Title - Contact			Phor	Phone - Contact*				Email - Contact*				
Product-E	Env-Stewards		Product Enviro Compliance			NA	NA				Product-Env-Stewards@onsemi.com				
uthorized	l Representative*		Title - Representative			Phor	Phone - Representative*				Email - Representative*				
Product-E	Cnv-Stewards		Product Enviro Compliance			NA	NA				Product-Env-Stewards@onsemi.com				
	Requester Item Number Mfr Item		n Number Mfr Item Name			Effe	fective Date	ate Version Manufacturing Site			Weight*	UOM	Unit Type		
		NCP1612	NCP1612A1DR2G Enhanced, High-Ef Controller in SOIC		ficiency Power Facto 10, Vcc 10.5V, VBU	or 202	25-05-13	3 PH1		7	74.7	mg	Each		
Manufac	cturing Proccess Informa	ntion													
	Terminal Plating / Grid Array Material Terminal Base Alloy			Alloy J-S	STD-020 MSL Ratin	SL Rating Peak Process Body Temperature Max Time at Peak					Temperat	ure Nu	ımber of Reflow C	ycles	
Matte Tin (Sn) - annealed CU Alloy			1			260		C	30	secon	ds 3				
Comments															
evel 1 - ma	aximum time at peak temperat	ure during sol	dering is 10-3	30 seconds											
or more i	nformation regarding material	composition	please refer to	page 3											

RoHS Material Composition Declaration			Declaration Type *	Detail	led						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on informationprovided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substa	ances per the definition above	Supplier Ac	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructional Complete all of the required	fields on all neggs of this form. Calcut th		a duan dawn. This will display the signature on	a Digitally sign	the declaration (if recurined by the						
Instructions: Complete all of the required Requester) and click on Submit Form to			e drop-down. This will display the signature ar	ea. Digitally sign	the declaration (if required by the						

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure Level		Substance	CAS	Exempt	Weight	Unit of Measure
Die	1.24 mg		Supplier	Silicon (Si)	7440-21-3		1.24	mg
Die Attach	0.1	mg	Supplier	Silver (Ag)	7440-22-4		0.075	mg
			Supplier	Epoxy resins	129915-35-1		0.025	mg
Lead Frame	15.95		Supplier	Silver (Ag)	7440-22-4		0.335	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0319	mg
			Supplier	Iron (Fe)	7439-89-6		0.3988	mg
			Supplier	Copper (Cu)	7440-50-8		15.1844	mg
Mold Compound-Black	55.41			Epoxy resin	proprietary data		2.7705	mg
			Supplier	Phenolic Resin	Proprietary Data		2.7705	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		1.1082	mg
			Supplier	Carbon Black (C)	1333-86-4		0.277	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		48.4837	mg
Plating	1.89	mg	Supplier	Tin (Sn)	7440-31-5		1.89	mg
Wire Bond - Au	0.11	mg	Supplier	Gold (Au)	7440-57-5		0.11	mg