©	<b>faterial Composit</b> Copyright 2005. IPC, I ternational and Pan-An	Bannockb	urn, Illinois. A	ll rights reserved untions.	under both	This docume level parts, ti	ent is a decla he declaratio	aration of the second s	of the substa ompasses all	ances w lower l	ithin the m evel mater	nanufactur ials for wh	er listed it hich the m	em. No anufac	ote: if the	e item is an as s engineering	sembly with lower responsibility.
					Form Type <sup>3</sup> Distribute	*	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					us Materia	ials and Mfg Information				
Supplier Informatio	on																
Company name*			Company unique ID			Unique ID Authority					Response Date*						
onsemi										2025-07-03							
Contact Name	Title - Contact			]	Phone - Contact*						Email - Contact*						
Product-Env-Stewards			Product Enviro Compliance			NA					Product-Env-Stewards@onsemi.com						
Authorized Representative*			Title - Representative			Phone - Representative*					Email - Representative*						
Product-Env-Stewards			Product Enviro Compliance			NA					Product-Env-Stewards@onsemi.com						
Requester Iter	Requester Item Number Mfr Item Nu   NCV4333D1		Number Mfr Item Name				Effective D	Date \	Version	Ma	Manufacturing Site		Weight*		t*	UOM	Unit Type
				2G QUAD, LOW OFFSET, LOW VOLTAGE OP-AMP			2025-07-03	3	PH1		44.36			mg	Each		
Manufacturing Pro	ccess Information	L															
Terminal Plati	Terminal Plating / Grid Array Material		erminal Base A	al Base Alloy J-STD-020 M		Rating	Peak Proc		ess Body Temperature Max Time at Pe		e at Peak	Temperature Numb		Number o	of Reflow Cyc	les	
Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)		i) (no C	U Alloy 1		1		260		С		30		seconds 3		3		
Comments																	
evel 1 - maximum time a	at peak temperature d	uring sol	dering is 10-3	0 seconds													
or more information re	garding material com	position <b>j</b>	please refer to	page 3													

RoHS Material Composition Declaration				Declaration Type *	Detailed
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth	
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the
Supplier Digital Signature Ra	stislav Drska	Le			

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.77	mg	Supplier	Silicon (Si)	7440-21-3		0.77	mg
Die Attach Epoxy	0.28	mg	Supplier	Silver (Ag)	7440-22-4		0.238	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.042	mg
Lead Frame	22.54	mg	Supplier	Zinc (Zn)	7440-66-6		0.027	mg
			Supplier	Iron (Fe)	7439-89-6		0.5297	mg
			Supplier	Copper (Cu)	7440-50-8		21.9765	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0068	mg
Mold Compound-Black	20.51	mg		Epoxy resin	proprietary data		1.5383	mg
			Supplier	Phenolic Resin	Proprietary Data		0.5128	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		1.5383	mg
			Supplier	Carbon Black (C)	1333-86-4		0.1025	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		16.8182	mg
Plating	0.04	mg	Supplier	Palladium (Pd)	7440-05-3		0.003	mg
			В	Nickel (Ni)	7440-02-0		0.0364	mg
			Supplier	Gold (Au)	7440-57-5		0.0006	mg
Vire Bond - Au	0.22	mg	Supplier	Gold (Au)	7440-57-5		0.22	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).