IPC ASSOCIATION OF ELECTRONICS	© Copyright 2005.	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.			der both lev	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.								
752-21.1		IPC Web Site for Information on IPC-1752 Standard  Form Typ  http://www.ipc.org/IPC-175x  Distribute				* Declaration Class * Class 6 - RoHS Yes/No. Homogeneous Materi					ials and Mfg Information			
upplier 1	Information						,		,					
Company name*				Company unique ID			Unique ID Authority				Response Date*			
nsemi											2025-05-12			
Contact Nai	me		Title - Contact			P	Phone - Contact*				Email - Contact*			
Product-En	nv-Stewards		Product Enviro Compliance			N	NA				Product-Env-Stewards@onsemi.com			
uthorized	Representative*	Title - Representative			P	Phone - Representative*				Email - Representative*				
Product-En	ıv-Stewards		Product Enviro Compliance			N	NA				Product-Env-Stewards@onsemi.com			
]	Requester Item Number	Mfr Item	Number	Mfr Item Name		]	Effective Date	Version	M	Manufacturing Site		eight*	UOM	Unit Type
		NCV6324CMTAAWT DCDC BUCK CO BG WETTABLE FL		DCDC BUCK CON WETTABLE FLAN		SLP 2	2025-05-12		MY1		9.0	)4	mg	Each
Ianufact	turing Proccess Informa	ation												
Т	Terminal Plating / Grid Array Material			Terminal Base Alloy J-STD-020 MSL		Rating	Peak Process Body Temperature   Max Time at Pe			Max Time at Peak	ak Temperature Number of Reflow Cycles			
Matte Tin (Sn) - annealed		CU Alloy 1				260	(	2	30	seconds	3			
omments														
vel 1 - max	ximum time at peak temperat	ture during sol	ldering is 10-3	0 seconds								_		
or more in	formation regarding materia	l composition	nlease refer to	nage 3										

RoHS Material Composition Declaration			Declaration Type *	Detail	ed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU  RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on informationprovided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusivesource of the Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the						

## **Homogeneous Material Composition Declaration for Electronic Products**

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.55	mg	Supplier	Silicon (Si)	7440-21-3		0.55	mg
Die Attach Tape	0.09	mg		Epoxy resin	proprietary data		0.0176	mg
			Supplier	Silver (Ag)	7440-22-4		0.0725	mg
Lead Frame	2.16		Supplier	Silver (Ag)	7440-22-4		0.0432	mg
			Supplier	Tin (Sn)	7440-31-5		0.0054	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0048	mg
			Supplier	Chromium (Cr)	7440-47-3		0.0054	mg
			Supplier	Copper (Cu)	7440-50-8		2.1012	mg
Mold Compound-Black	5.77			Epoxy resin	proprietary data		0.2885	mg
			Supplier	Phenolic Resin	Proprietary Data		0.1327	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		0.2885	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0231	mg
			Supplier	Aluminum Hydroxide (Al(OH)3)	21645-51-2		0.1327	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		4.9045	mg
Plating	0.39	mg	Supplier	Tin (Sn)	7440-31-5		0.39	mg
Wire Bond - Au	0.08	mg	Supplier	Gold (Au)	7440-57-5		0.08	mg