ASSOCIATION CONNECTING LECTRONICS INDUSTRIES® Material Comp © Copyright 2005. Il international and Par	PC. Bannock	burn. Illinois. A	ll rights reserved untions.	under both	This docum level parts, t	ent is a declar the declaration	ation of the encompass	substances ses all low	s within the er level ma	e manufacture terials for wh	er listed ite	em. Note anufactu	e: if the item rer has engin	is an assem neering resp	bly with lowe onsibility.
				Form Type Distribute	*	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					als and Mfg Information				
Supplier Information															
Company name* C			Company unique ID			Unique ID Authority					Response Date*				
onsemi											2025-07-13				
Contact Name Title - Contact					Phone - Contact*					Email - Contact*					
Product-Env-Stewards Pro			Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com					
Authorized Representative*			Title - Representative			Phone - Representative*				Email - Representative*					
Product-Env-Stewards	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com						
Requester Item Number	uester Item Number Mfr Item		n Number Mfr Item Name			Effective Da	te Version	n	Manufacturing Site		V	/eight*	UOM	Л	Unit Type
	NCV81: CG	NCV8152MX180280T Dual 150 mA, Low CG Voltage Regulator		ow IQ, Low Dro or	pout	2025-07-13	07-13 MY1			1.87		mg		Each	
Manufacturing Proccess Information	tion														
Terminal Plating / Grid Array Material Terminal Base Alloy J.			J-STD-020 MSI	L Rating	Peak Process Body Temperature Max Time at Peak Temper					Temperatu	re Nui	mber of Refl	ow Cycles		
Matte Tin (Sn) - annealed CU Alloy			1		260		С	30		second	s 3				
Comments															
evel 1 - maximum time at peak temperatu	re during so	ldering is 10-3	0 seconds												
for more information regarding material	composition	please refer to	page 3												

RoHS Material Composition Declaration				Declaration Type *	Detailed
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth	
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the
Supplier Digital Signature Ra	stislav Drska	Le			

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	0.09	mg	Supplier	Silicon (Si)	7440-21-3		0.09	mg	
Die Attach	0.03	mg	Supplier	Silver (Ag)	7440-22-4		0.0225	mg	
			Supplier	Epoxy resins	129915-35-1		0.0075	mg	
Lead Frame 0.82	0.82	mg	Supplier	Silver (Ag)	7440-22-4		0.0328	mg	
			Supplier	Tin (Sn)	7440-31-5		0.0021	mg	
			Supplier	Zinc (Zn)	7440-66-6		0.0018	mg	
			Supplier	Chromium (Cr)	7440-47-3		0.0021	mg	
			Supplier	Copper (Cu)	7440-50-8		0.7813	mg	
Mold Compound-Black (	0.88	mg		Epoxy resin	proprietary data		0.0616	mg	
			Supplier	Phenolic Resin	Proprietary Data		0.0616	mg	
			Supplier	Silica Amorphous (SiO2)	7631-86-9		0.132	mg	
			Supplier	Carbon Black (C)	1333-86-4		0.0044	mg	
			Supplier	Fused Silica (SiO2)	60676-86-0		0.6204	mg	
Plating	0.02	mg	Supplier	Tin (Sn)	7440-31-5		0.02	mg	
Wire Bond - Au	0.03	mg	Supplier	Gold (Au)	7440-57-5		0.03	mg	

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).