ASSOCIATION CONNE	© Copyright 2005. I	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.				This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with low level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.									
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				e * Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater						ials and Mfg Information			
Supplier Info	ormation														
Company name*			Company un	Company unique ID			Unique ID Authority					Response Date*			
nsemi												2025-09-07			
Contact Name		Title - Conta	Title - Contact			Phone - Contact*					Email - Contact*				
Product-Env-St	tewards	Product Enviro Compliance				NA					Product-Env-Stewards@onsemi.com				
Authorized Repi	resentative*	Title - Repre	Title - Representative			Phone - Representative*				Email - Representative*					
Product-Env-St	tewards	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com					
Requ	uester Item Number			Mfr Item Name			Effective Dat	e Version	Version Ma		Manufacturing Site		Weight* UOM	UOM	Unit Type
				DUAL BUFFER			2025-09-07 MY		MY1		20	20.0 mg		Each	
Ianufacturi	ng Proccess Informa	tion		,										1	
Termi	inal Plating / Grid Array M	l Plating / Grid Array Material		Terminal Base Alloy		SL Rating	Peak Pro	Peak Process Body Temperature Max Tir		ne at Peak	at Peak Temperature N		Number of Reflow Cycles		
Precio Sn)			CU Alloy 1		1		260		С		30 seco		s 3		
Comments								<u> </u>			<u> </u>				
vel 1 - maximu	ım time at peak temperatı	ure during so	oldering is 10-3	0 seconds											
or more inform	nation regarding material	composition	please refer to	page 3											

RoHS Material Composition Declaration			Declaration Type *	Detail	ed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusivesource of the Supplier's liability and the Company's remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the						

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.2	mg	Supplier	Silicon (Si)	7440-21-3		0.2	mg
Die Attach	0.45	mg	Supplier	Epoxized Condensate Of Para- Hydrobenzaldehyde And Alkyl Phenol	129915-35-1		0.144	mg
			Supplier	Aluminum Trioxide (Al2O3)	1344-28-1		0.306	mg
Lead Frame	6.97	mg	Supplier	Tin (Sn)	7440-31-5		0.0174	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0153	mg
			Supplier	Chromium (Cr)	7440-47-3		0.0174	mg
			Supplier	Copper (Cu)	7440-50-8		6.9198	mg
Mold Compound-Black	10.0	mg		Epoxy resin	proprietary data		0.7	mg
			Supplier	Phenolic Resin	Proprietary Data		0.7	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		1.5	mg
			Supplier	Carbon Black (C)	1333-86-4		0.05	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		7.05	mg
Plating	0.71	mg	Supplier	Palladium (Pd)	7440-05-3		0.0227	mg
			В	Nickel (Ni)	7440-02-0		0.6795	mg
			Supplier	Gold (Au)	7440-57-5		0.0078	mg
Wire Bond - Au	1.67	mg	Supplier	Gold (Au)	7440-57-5		1.67	mg