©	Iaterial Composit Copyright 2005. IPC, 1 ternational and Pan-An	Bannockb	urn, Illinois. A	ll rights reserved untions.	under both	This docume level parts, th	ent is a declar he declaratio	ration of n encom	the substance the substance passes all low	s within the er level ma	e manufactur terials for wi	er listed it hich the m	em. Not anufacti	te: if the it urer has e	tem is an ass ngineering r	embly with low esponsibility.
	IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				e *	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					als and Mi	g Inforr	mation			
Supplier Informatio	n															
Company name*			Company unique ID			Unique ID Authority					Response Date*					
onsemi												2025-06-08				
Contact Name			Title - Contact]	Phone - Contact*					Email - Contact*				
Product-Env-Stewards			Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com					
Authorized Representative*			Title - Representative			Phone - Representative*				Email - Representative*						
Product-Env-Stewards			Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com						
Requester Iter	Requester Item Number Mfr Item		n Number Mfr Item Name				Effective Date Version Manufacturing		ring Site	Weight*		τ	JOM	Unit Type		
	NLV14071BDTR2G		QUAD 2-INPUT OR GATE		2025-06-08			PH1		4	5.24	n	ng	Each		
Manufacturing Pro	ccess Information	l					1					I		I		1
Terminal Platin	Terminal Plating / Grid Array Material		Cerminal Base Alloy J-ST		J-STD-020 MS	L Rating	Peak Pr	Peak Process Body Temperature		ure Max T	e Max Time at Peak Tempera		ire Nu	umber of I	Reflow Cycl	es
Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)			CU Alloy 1		1		260		С	30		second	is 3			
Comments																
evel 1 - maximum time a	at peak temperature d	luring sol	dering is 10-3	0 seconds												
or more information re	garding material com	position 1	please refer to	page 3												

RoHS Material Composition Declaration				Declaration Type *	Detailed
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth	
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the
Supplier Digital Signature Ra	stislav Drska	Le			

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	2.0	mg	Supplier	Silicon (Si)	7440-21-3		2	mg	
Die Attach	1.44	mg		Epoxy resin	proprietary data		0.144	mg	
			Supplier	Silver (Ag)	7440-22-4		1.152	mg	
			Supplier	Formaldehyde Polymer	9003-36-5		0.144	mg	
Lead Frame	22.54	mg	Supplier	Iron (Fe)	7439-89-6		0.4283	mg	
			Supplier	Copper (Cu)	7440-50-8		22.1117	mg	
Mold Compound-Black	19.0	mg		Epoxy resin	proprietary data		1.425	mg	
			Supplier	Phenolic Resin	Proprietary Data		0.475	mg	
			Supplier	Silica Amorphous (SiO2)	7631-86-9		1.425	mg	
			Supplier	Carbon Black (C)	1333-86-4		0.095	mg	
			Supplier	Fused Silica (SiO2)	60676-86-0		15.58	mg	
Plating	0.04	mg	Supplier	Palladium (Pd)	7440-05-3		0.003	mg	
			В	Nickel (Ni)	7440-02-0		0.0364	mg	
			Supplier	Gold (Au)	7440-57-5		0.0006	mg	
Wire Bond - Cu	0.22	mg	Supplier	Copper (Cu)	7440-50-8		0.22	mg	

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).