C C	Iaterial Composit Copyright 2005. IPC, ternational and Pan-An	Bannockb	urn, Illinois. A	ll rights reserved nations.	under both	This docume level parts, t	ent is a declarat he declaration	ion of the su encompasse	ibstances v s all lower	vithin the manufactule level materials for v	urer listed which the i	tem. Note: nanufacture	if the item is an as er has engineering	ssembly with low responsibility.	
	IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				e *	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					als and Mfg Information				
upplier Informatio	on														
Company name*			Company unique ID				Unique ID Authority				Respon	Response Date*			
onsemi											2024-05	2024-05-03			
Contact Name			Title - Contact				Phone - Contact*				Email -	Email - Contact*			
Product-Env-Stewards			Product Enviro Compliance				NA				Produ	Product-Env-Stewards@onsemi.com			
Authorized Representative*			Title - Representative				Phone - Representative*				Email -	Email - Representative*			
Product-Env-Stewards			Product Enviro Compliance				NA				Produ	Product-Env-Stewards@onsemi.com			
Requester Item Number Mfr Iten		Mfr Item	n Number Mfr Item Name				Effective Date	Version	М	Manufacturing Site		Weight*	UOM	Unit Type	
		NRVBS260T3G SBN		SBN BE SCHOTTKY		2024-05-03		V	VN5		114.91	mg	Each		
Anufacturing Pro	ccess Information	1		-											
Terminal Plating / Grid Array Material Terminal Bas			erminal Base A	Alloy	Peak Process Body Temperature Max Time at Peak Temperature Number of Reflow Cycle						cles				
Matte Tin (Sn) - annealed CU Alloy			U Alloy		1		260		С	30	seco	nds 3			
omments															
vel 1 - maximum time a	at peak temperature d	luring sol	dering is 10-3	0 seconds											
or more information re	garding material com	position	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		mium (Cr6+), Polybrominated Biphenyls (Pl		dmium and quantity limit of 0.1% by mass (10 minated Diphenyl Ethers (PBDE), and Bis(2-et	
cadmium, hexavalentchromium, polybromina contains a RoHS restricted substance inexces encompass all such components. Supplier cer as of the date that Supplier completes this for Company acknowledges that Supplier may h independently verified information provided certification in this paragraph. If the Company	ated biphenyls and/or polybrominated dip s of an applicable quantity limit, please in iffies that it gathered the information it pr m.Supplier acknowledges that Company ave relied on informationprovided by oth by others, Supplier agrees that, at a minir and the Supplier enter into a written agr esource of the Supplier's liability and the	henyl ethers (each a "RoHS restricted substa ndicate below which, if any, RoHS exemption ovides in this form using appropriate methoo will rely on this certification in determining ers in completing this form, and that Supplie num, itssuppliers have provided certification eement with respect to the identified part, the Company's remedies for issues that arise reg	nce") in exco n you believe ls to ensure i the compliar r may not ha s regarding t terms and co	e may apply. If the part is an assembly with low s accuracy and that such information is true an ce of its products with European Union member de independently verified such information. Ho neir contributions to the part, and those certifica	ove. If a homogeneous material within the part er level components, the declaration shall d correct to the best of its knowledge and belief, er state laws that implement the RoHS Directive. wever, in situations where Supplier has not ations are at least as comprehensive as the anty rights and/or remedies provided as part of
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted subst	ances per the definition above except for sele	ected exempt	ions Supplier Acceptance	* Accepted
Exemption: 7a: Lead in high melting temp	erature type solders (i.e. lead based sol	der alloys containing 85% by weight or m	ore lead).		
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
Instructions: Complete all of the required Requester) and click on Submit Form to h			e drop-dowi	a. This will display the signature area. Digita	lly sign the declaration (if required by the
Supplier Digital Signature	astislav Drska	Le			

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Clip	16.81	mg	Supplier	Zinc (Zn)	7440-66-6		0.0202	mg	
			Supplier	Iron (Fe)	7439-89-6		0.395	mg	
			Supplier	Copper (Cu)	7440-50-8		16.3897	mg	
			Supplier	Phosphorus (P)	7723-14-0		0.005	mg	
Die	0.7	mg	Supplier	Silicon (Si)	7440-21-3		0.7	mg	
Die Attach Solder	0.52	mg	Supplier	Silver (Ag)	7440-22-4		0.013	mg	
			А	Lead (Pb)	7439-92-1	7a	0.481	mg	
			Supplier	Tin (Sn)	7440-31-5		0.026	mg	
Lead Frame	46.99	mg	Supplier	Zinc (Zn)	7440-66-6		0.047	mg	
			Supplier	Iron (Fe)	7439-89-6		1.1278	mg	
			Supplier	Copper (Cu)	7440-50-8		45.8153	mg	
Mold Compound-Black	48.07	mg	Supplier	Ortho Cresol Novolac Resin	29690-82-2		4.807	mg	
			Supplier	Carbon Black (C)	1333-86-4		0.2403	mg	
			Supplier	Aluminum Hydroxide (Al(OH)3)	21645-51-2		6.9701	mg	
			Supplier	Fused Silica (SiO2)	60676-86-0		31.2455	mg	
			Supplier	Phenolic Resin (Novolac)	9003-35-4		4.807	mg	
Plating	1.82	mg	Supplier	Tin (Sn)	7440-31-5		1.82	mg	

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).