IPC ASSOCIATION ELECTRONIC	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved un international and Pan-American copyright conventions.			der both	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.										
1752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi				erials and N	Лfg Informat	ion			
Supplie	r Information														
Company name*			Company unique ID			τ	Unique ID Authority				Respon	Response Date*			
onsemi											2025-0	2025-06-02			
Contact N	lame	Title - Contact			1	Phone - Contact*				Email	Email - Contact*				
Product-l	Env-Stewards		Product Enviro Compliance				NA				Produ	Product-Env-Stewards@onsemi.com			
uthorize	ed Representative*		Title - Representative			I	Phone - Representative*				Email	Email - Representative*			
Product-l	Env-Stewards		Product Enviro Compliance				NA				Produ	Product-Env-Stewards@onsemi.com			
	Requester Item Number Mfr Item		Number Mfr Item Name				Effective Da	Date Version Manufacturing Site			Weight*	UOM	Unit Type		
		NRVHPRS1AFA SR SOI		SR SOD123FA PN	R SOD123FA PN 0.8A 50V		2025-06-02			TSCBE		18.79156	mg	Each	
Manufa	acturing Process Information	ation						·					·		
	Terminal Plating / Grid Array Material Terminal Base Alloy			Alloy J-	-STD-020 MSL Rating Peak Process Body Temperat			re Max Time at Pea	ak Tempera	ature Numl	ber of Reflow Cyc	eles			
Matte Tin (Sn) - annealed CU Alloy					260		C	30	seco	nds 3					
Comments	S														
evel 1 - m	naximum time at peak tempera	ture during sol	dering is 10-3	30 seconds											
or more	information regarding materia	l composition	please refer t	page 3											

<b>RoHS Material Composition Declaration</b>			Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU  RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).										
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its uppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier have provided as part of that agreement, will be the sole and exclusivesource of the Supplier's liability and the Company's remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale appli										
RoHS Declaration * 4 - Item(s	s) does not contain RoHS restricted substance	ces per the definition above except for selected exer	nptions Supplier Acceptance	* Accepted						
Exemption: 7a: Lead in high melting temperature type solders (i.e. lead based solder alloys containing 85% by weight or more lead).  Exemption: 7c-I Electrical and electronic components containing lead in a glass or ceramic other than dielectric ceramic in capacitors, e.g. piezoelectronic devices, or in a glass or ceramic matrix compound.										
Exemption List Version	EL-2011/534/EU									
Declaration Signature										
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.										
Supplier Digital Signature R		,								

## **Homogeneous Material Composition Declaration for Electronic Products**

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.72998		Supplier	Silicon (Si)	7440-21-3		0.657	mg
			В	Nickel (Ni)	7440-02-0		0.0047	mg
			Supplier	Gold (Au)	7440-57-5		0.0011	mg
			Supplier	Lead Bisilicate	65997-18-4	7c	0.0672	mg
Die Attach Solder	4.11996	mg	Supplier	Silver (Ag)	7440-22-4		0.103	mg
			A	Lead (Pb)	7439-92-1	7a	3.811	mg
			Supplier	Tin (Sn)	7440-31-5		0.206	mg
Lead Frame	6.79991	mg	Supplier	Iron (Fe)	7439-89-6		0.0068	mg
			Supplier	Copper (Cu)	7440-50-8		6.7911	mg
			Supplier	Phosphorus (P)	7723-14-0		0.002	mg
Mold Compound-Black	6.94164		Supplier	Ortho Cresol Novolac Resin	29690-82-2		1.0725	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0715	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.715	mg
			Supplier	Silica Crystalline (SiO2)	14808-60-7		5.0826	mg
Plating	0.20007	mg	Supplier	Tin (Sn)	7440-31-5		0.2001	mg