ABSOCIATION CONNECTING ELECTRONICS INDUSTRIES INDUSTRIES International and Pan-Am	Bannockburn, Illino	is. All rights reserved u	under both	This docume level parts, t	ent is a declarat he declaration e	ion of the su	bstances v all lower	within the manufactur level materials for w	er listed it hich the m	em. Note: if anufacturer	f the item is an as has engineering	sembly with lower responsibility.
	IPC Web Site for Information on IPC-1752 Standard Form http://www.ipc.org/IPC-175x Distri							ials and Mfg Information				
Supplier Information												
Company name* Company unique I			ue ID Unique			ique ID Authority			Response Date*			
onsemi									2025-06-04			
Contact Name	act Name Title - Contact]	Phone - Contact*				Email - Contact*			
Product-Env-Stewards Product Enviro Cor			o Compliance		NA			Product-Env-Stewards@onsemi.com				
Authorized Representative* Title - Representative			tative Pho		Phone - Repres	one - Representative*			Email - Representative*			
Product-Env-Stewards	Enviro Compliance			NA				Product-Env-Stewards@onsemi.com				
Requester Item Number	Mfr Item Number	Mfr Item Name	Mfr Item Name		Effective Date	Version	М	Manufacturing Site		Weight*	UOM	Unit Type
	NSS30100LT1G	S30100LT1G SSP LOW VCES 3			2025-06-04 CN1		N1	8	3.125	mg	Each	
Manufacturing Proccess Information					·		<u></u>					·
Terminal Plating / Grid Array Materia	ial Terminal Base Alloy		J-STD-020 MSL	Rating	Peak Proc	Process Body Temperature Max Time at Peak		Temperat	ure Numb	er of Reflow Cyd	eles	
Matte Tin (Sn) - annealed CU Alloy		1		260		С	30	secon	ds 3			
Comments												
level 1 - maximum time at peak temperature d	uring soldering is	10-30 seconds										
For more information regarding material com	position please ref	er to page 3										

RoHS Material Composition Declaration				Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Disobutyl phthalate (DIBP).										
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of						
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	on above	Supplier Acceptance	* Accepted							
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all						
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the						
Supplier Digital Signature Ra	stislav Drska	Le									

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3

sigma range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	0.16	mg	Supplier	Silicon (Si)	7440-21-3		0.16	mg	
Lead Frame	2.92	mg	Supplier	Silver (Ag)	7440-22-4		0.5198	mg	
			В	Nickel (Ni)	7440-02-0		0.9023	mg	
			Supplier	Iron (Fe)	7439-89-6		1.2468	mg	
			Supplier	Copper (Cu)	7440-50-8		0.2511	mg	
Mold Compound-Black	4.9	mg	Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.49	mg	
			Supplier	Carbon Black (C)	1333-86-4		0.0245	mg	
			Supplier	Aluminum Hydroxide (Al(OH)3)	21645-51-2		0.7105	mg	
			Supplier	Fused Silica (SiO2)	60676-86-0		3.185	mg	
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.49	mg	
Plating	0.14	mg	Supplier	Tin (Sn)	7440-31-5		0.14	mg	
Wire Bond - Cu	0.005	mg	Supplier	Copper (Cu)	7440-50-8		0.005	mg	