IPC ASSOCIATION OF	© Copyright 2005.	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.			der both	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.								
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi				ials and Mfg Information				
upplier l	Information				·		·							
Company name*				Company unique ID			Unique ID Authority				Response Date*			
onsemi											2024-05-05			
Contact Nai	me	Title - Contact			1	Phone - Contact*				Email - Contact*				
Product-En	nv-Stewards		Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com			
uthorized	Representative*	Title - Representative			I	Phone - Representative*			Email - Representative*					
roduct-En	nv-Stewards	Product Envi	Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com				
]	Requester Item Number	Mfr Item	Number	Mfr Item Name			Effective Date	Version	N	Manufacturing Site	W	eight*	UOM	Unit Type
		NVATS5A304PLZT4 PCH 4.5V DRIVI		PCH 4.5V DRIVE	SERIES		2024-05-05 CNG		CNG	27	1.02	mg	Each	
Ianufact	turing Proccess Inform	ation												
Т	Terminal Plating / Grid Array Material Terminal Base Alloy			Alloy J-S	STD-020 MSI	20 MSL Rating Peak Process Body Temperature Max Time at Pea					Temperatu	e Numb	per of Reflow Cyc	les
contains Bi		CU Alloy 1				260 C		C	30	second	3			
omments														
vel 1 - max	ximum time at peak tempera	ture during sol	dering is 10-3	0 seconds										
ar more in	formation regarding materia	al composition	nlease refer to	nage 3										

RoHS Material Composition Declaration			Declaration Type *	Detailed						
Priective 2015/863/EU amending RoHS directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).										
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its keloardin shall encompass all such components. Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, itssuppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies of Supplier's Standard Terms and/Conditions of Sale applicable to such part shall apply.										
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted substance	s per the definition above except for selected exemp	tions Supplier Acceptance	* Accepted						
Exemption: 7a: Lead in high melting temperature type solders (i.e. lead based solder alloys containing 85% by weight or more lead).										
Exemption List Version	EL-2011/534/EU									
Declaration Signature										
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.										
Supplier Digital Signature Ra	astislav Drska	-En								

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	10.29	mg	Supplier	Silicon (Si)	7440-21-3		10.29	mg
Die Attach	8.6		Supplier	Silver (Ag)	7440-22-4		0.1892	mg
			A	Lead (Pb)	7439-92-1	7a	7.9808	mg
			Supplier	Tin (Sn)	7440-31-5		0.43	mg
Lead Frame	151.27	_	Supplier	Tin (Sn)	7440-31-5		0.2269	mg
			Supplier	Copper (Cu)	7440-50-8		151.0431	mg
Mold Compound-Black	97.56			Phenolic Resin	proprietary data		2.439	mg
			Supplier	Epoxy Phenol Resin	Proprietary Data		8.0487	mg
			Supplier	Carbon Black (C)	1333-86-4		0.4878	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		86.0967	mg
			Supplier	Silica Crystalline (SiO2)	14808-60-7		0.4878	mg
Plating	3.3	mg	В	Bismuth (Bi)	7440-69-9		0.0198	mg
			Supplier	Tin (Sn)	7440-31-5		3.2802	mg