ASSOCIATION CONNECTING ELECTRONICS INDUSTRIES INDUSTRIES INDUSTRIES	C. Bannockb	ourn. Illinois. A	Il rights reserved untions.	under both	This docume level parts, t	ent is a declara he declaration	tion of the s encompasse	ubstances es all lowe	within the n er level mate	nanufacture rials for wh	er listed item ich the man	. Note: if ufacturer	the item is an as has engineering	sembly with lowe responsibility.
	P-21.1 IPC Web Site for Information on IPC-1752 Standard Form Distr				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					ous Materia	ials and Mfg Information			
Supplier Information														
Company name* Company			any unique ID			Unique ID Authority					Response Date*			
onsemi											2025-06-08			
Contact Name	tact Name Title - Contact					Phone - Contact*					Email - Contact*			
Product-Env-Stewards Product Envir			iro Compliance			NA				Product-Env-Stewards@onsemi.com				
Authorized Representative* Title - Repres			sentative			Phone - Representative*				Email - Representative*				
Product-Env-Stewards Product En			Enviro Compliance			NA				Product-Env-Stewards@onsemi.com				
Requester Item Number	er Item Number Mfr Item Number		umber Mfr Item Name			Effective Dat	e Version		Manufacturing Site		We	ight*	UOM	Unit Type
	SBC8471	SBC847BPDW1T1G SS SC88 GP 2		XSTR DUAL 45V		2025-06-08			CN1		6.2		mg	Each
Manufacturing Proccess Informati	on					·							·	
Terminal Plating / Grid Array Mate	rray Material Terminal Base Alloy		Alloy	J-STD-020 MSI	020 MSL Rating		Peak Process Body Temperature Max Time at Pea		ne at Peak T	Temperature Number of Reflow Cycles				
Matte Tin (Sn) - annealed CU Alloy			1		260		С	30		seconds	3			
Comments														
evel 1 - maximum time at peak temperatur	e during sol	dering is 10-3	0 seconds											
or more information regarding material c	mposition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed					
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth						
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of					
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	on above	Supplier Acceptance	* Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.										
Exemption List Version	EL-2011/534/EU									
Declaration Signature										
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.										
Supplier Digital Signature Ra	stislav Drska	Le								

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).									
Homogeneous Material Weight Unit of Measur		Unit of Measure	Level Substance		CAS	Exempt	Weight	Unit of Measure	
Die	0.19	mg	Supplier	Silicon (Si)	7440-21-3		0.19	mg	
Lead Frame	2.04	mg	В	Nickel (Ni)	7440-02-0		0.7813	mg	
			Supplier	Iron (Fe)	7439-89-6		1.0792	mg	
			Supplier	Copper (Cu)	7440-50-8		0.1795	mg	
Mold Compound-Black	3.9	mg	Supplier	Boron zinc hydroxide oxide	138265-88-0		0.117	mg	
			Supplier	Zinc Monoxide (ZnO)	1314-13-2		0.0195	mg	
			Supplier	2,4,6-triamino-s-triazincompd.withs- triazine-triol	37640-57-6		0.117	mg	
			Supplier	Silica Amorphous (SiO2)	7631-86-9		3.12	mg	
			Supplier	Carbon Black (C)	1333-86-4		0.039	mg	
			Supplier	Ortho-Cresol Novolac Resin	29690-82-2		0.312	mg	
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.1755	mg	
Plating	0.05	mg	Supplier	Tin (Sn)	7440-31-5		0.05	mg	
Wire Bond	0.02	mg	Supplier	Palladium (Pd)	7440-05-3		0.0002	mg	
			Supplier	Copper (Cu)	7440-50-8		0.0198	mg	

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).