

製品概要

LM385B: MicroPower Voltage Reference Diodes

技術情報は、データシートをご参照ください。

The LM285/LM385 series are micropower two-terminal bandgap voltage regulator diodes. Designed to operate over a wide current range of 10 μ A to 20 mA, these devices feature exceptionally low dynamic impedance, low noise and stable operation over time and temperature. Tight voltage tolerances are achieved by on-chip trimming. The large dynamic operating range enables these devices to be used in applications with widely varying supplies with excellent regulation. Extremely low operating current make these devices ideal for micropower circuitry like portable instrumentation, regulators and other analog circuitry where extended battery life is required. The LM285/LM385 series are packaged in a low cost TO-226AA plastic case and are available in two voltage versions of 1.235 and 2.500 V as denoted by the device suffix (see Ordering Information table). The LM285 is specified over a -40 C to +85 C temperature range while the LM385 is rated from 0 C to +70 C. The LM385 is also available in a surface mount plastic package in voltages of 1.235 and 2.500 V.

特長

- Operating Current from 10 μ A to 20 mA
- 1.0%, 1.5%, 2.0% and 3.0% Initial Tolerance Grades
- Low Temperature Coefficient
- 1.0 W Dynamic Impedance
- Surface Mount Package Available
- Pb-Free Packages are Available

電気的仕様

製品	Compliance	Status	Type	$V_{(BR)}$ Typ (V)	Tolerance (%)	I_O Typ (mA)	I_R Min (mA)	V_F Max (V)	T_A Min ($^{\circ}$ C)	T_A Max ($^{\circ}$ C)	Package Type
LM385BD-1.2G	Pb-free	Active	Fixed	1.25	1		0.015		0	70	SOIC-8
	Halide free										
LM385BD-1.2R2G	Pb-free	Active	Fixed	1.25	1		0.015		0	70	SOIC-8
	Halide free										
LM385BD-2.5G	Pb-free	Active	Fixed	2.5	1.5		0.015		0	70	SOIC-8
	Halide free										
LM385BD-2.5R2G	Pb-free	Active	Fixed	2.5	1.5		0.015		0	70	SOIC-8
	Halide free										
LM385BZ-1.2G	Pb-free	Active	Fixed	1.25	1		0.015		0	70	TO-92
	Halide free										
LM385BZ-1.2RAG	Pb-free	Active	Fixed	1.25	1		0.015		0	70	TO-92
	Halide free										
LM385BZ-2.5G	Pb-free	Active	Fixed	2.5	1.5		0.015		0	70	TO-92
	Halide free										

詳細は、弊社 www.onsemi.jp の営業または販売代理店にお問い合わせください。

7/16/2019 作成