Medium-Power Plastic NPN Silicon Transistors

2N4921G, 2N4922G, 2N4923G

These high−performance plastic devices are designed for driver circuits, switching, and amplifier applications.

Features

- Low Saturation Voltage
- Excellent Power Dissipation
- Excellent Safe Operating Area
- Complement to PNP 2N4920G
- These Devices are Pb−Free and are RoHS Compliant**

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector−Emitter Voltage 2N4921G 2N4922G 2N4923G	V_{CEO}	 40 60 80	Vdc
Collector−Emitter Voltage 2N4921G 2N4922G 2N4923G	V_{CB}	 40 60 80	Vdc
Emitter Base Voltage	V_{EB}	5.0	Vdc
Collector Current − Continuous (Note 2)	I_C	1.0	Adc
Collector Current − Peak (Note 2)	I_{CM}	3.0	Adc
Base Current − Continuous	I_B	1.0	Adc
Total Power Dissipation @ T_C = 25°C Derate above 25°C	P_D	 30 0.24	 W mW/°C
Operating and Storage Junction Temperature Range	T_J, T_{stg}	−65 to +150	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

2. The 1.0 A maximum I_C value is based upon JEDEC current gain requirements. The 3.0 A maximum value is based upon actual current handling capability of the device (see Figures 5 and 6).

THERMAL CHARACTERISTICS (Note 3)

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction−to−Case	$R_{\theta JC}$	4.16	°C/W

3. Recommend use of thermal compound for lowest thermal resistance.

*Indicates JEDEC Registered Data.

*For additional information on our Pb−Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

1.0 AMPERE GENERAL PURPOSE POWER TRANSISTORS 40−80 VOLTS, 30 WATTS





TO−225
CASE 77−09
STYLE 1

MARKING DIAGRAM



Y = Year
WW = Work Week
2N492x = Device Code
x = 1, 2, or 3
G = Pb−Free Package

ORDERING INFORMATION

Device	Package	Shipping
2N4922G	TO−225 (Pb−Free)	500 Units / Box
2N4923G	TO−225 (Pb−Free)	500 Units / Box

DISCONTINUED (Note 1)

2N4921G	TO−225 (Pb−Free)	500 Units / Box

1. **DISCONTINUED:** This device is not recommended for new design. Please contact your **onsemi** representative for information. The most current information on this device may be available on www.onsemi.com.

© Semiconductor Components Industries, LLC, 2013

ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
OFF CHARACTERISTICS				
Collector−Emitter Sustaining Voltage (Note 4) (I_C = 0.1 Adc, I_B = 0) 2N4921G 2N4922G 2N4923G	$V_{CEO(sus)}$	 40 60 80	 – – –	Vdc
Collector Cutoff Current (V_{CE} = 20 Vdc, I_B = 0) 2N4921G (V_{CE} = 30 Vdc, I_B = 0) 2N4922G (V_{CE} = 40 Vdc, I_B = 0) 2N4923G	I_{CEO}	 – – –	 0.5 0.5 0.5	mAdc
Collector Cutoff Current (V_{CE} = Rated V_{CEO}, $V_{EB(off)}$ = 1.5 Vdc) (V_{CE} = Rated V_{CEO}, $V_{EB(off)}$ = 1.5 Vdc, T_C = 125°C	I_{CEX}	 – –	 0.1 0.5	mAdc
Collector Cutoff Current (V_{CB} = Rated V_{CB}, I_E = 0)	I_{CBO}	 –	 0.1	mAdc
Emitter Cutoff Current (V_{EB} = 5.0 Vdc, I_C = 0)	I_{EBO}	 –	 1.0	mAdc
ON CHARACTERISTICS				
DC Current Gain (Note 4) (I_C = 50 mAdc, V_{CE} = 1.0 Vdc) (I_C = 500 mAdc, V_{CE} = 1.0 Vdc) (I_C = 1.0 Adc, V_{CE} = 1.0 Vdc)	h_{FE}	 40 30 10	 – 150 –	–
Collector−Emitter Saturation Voltage (Note 4) (I_C = 1.0 Adc, I_B = 0.1 Adc)	$V_{CE(sat)}$	 –	 0.6	Vdc
Base−Emitter Saturation Voltage (Note 4) (I_C = 1.0 Adc, I_B = 0.1 Adc)	$V_{BE(sat)}$	 –	 1.3	Vdc
Base−Emitter On Voltage (Note 4) (I_C = 1.0 Adc, V_{CE} = 1.0 Vdc)	$V_{BE(on)}$	 –	 1.3	Vdc
SMALL−SIGNAL CHARACTERISTICS				
Current−Gain − Bandwidth Product (I_C = 250 mAdc, V_{CE} = 10 Vdc, f = 1.0 MHz)	f_T	 3.0	 –	MHz
Output Capacitance (V_{CB} = 10 Vdc, I_E = 0, f = 100 kHz)	C_{ob}	 –	 100	pF
Small−Signal Current Gain (I_C = 250 mAdc, V_{CE} = 10 Vdc, f = 1.0 kHz)	h_{fe}	 25	 –	–

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

4. Pulse Test: PW ≈ 300 μs, Duty Cycle ≈ 2.0%.

Share Feedback
Your Opinion Matters



Figure 1. Power Derating

Safe Area Curves are indicated by Figure 5. All limits are applicable and must be observed.



Figure 2. Switching Time Equivalent Circuit



Figure 3. Turn−On Time

Share Feedback
Your Opinion Matters



Figure 4. Thermal Response



Figure 5. Active−Region Safe Operating Area

There are two limitations on the power handling ability of a transistor: average junction temperature and second breakdown. Safe operating area curves indicate $I_C - V_{CE}$ operation i.e., the transistor must not be subjected to greater dissipation than the curves indicate.

The data of Figure 5 is based on $T_{J(pk)} = 150°C$; T_C is variable depending on conditions. Second breakdown pulse limits are valid for duty cycles to 10% provided $T_{J(pk)} \leq 150°C$. At high case temperatures, thermal limitations will reduce the power that can be handled to values less than the limitations imposed by second breakdown.



Figure 6. Storage Time



Figure 7. Fall Time

Share Feedback
Your Opinion Matters



Figure 8. Current Gain



Figure 9. Collector Saturation Region



Figure 10. Effects of Base−Emitter Resistance



Figure 11. “On” Voltage



Figure 12. Collector Cut−Off Region



Figure 13. Temperature Coefficients

Share Feedback
Your Opinion Matters

TO−225
CASE 77−09
ISSUE AD

DATE 25 MAR 2015



FRONT VIEW **BACK VIEW**

SCALE 1:1



FRONT VIEW



SIDE VIEW

NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. NUMBER AND SHAPE OF LUGS OPTIONAL.

	MILLIMETERS	
DIM	MIN	MAX
A	2.40	3.00
A1	1.00	1.50
b	0.60	0.90
b2	0.51	0.88
c	0.39	0.63
D	10.60	11.10
E	7.40	7.80
e	2.04	2.54
L	14.50	16.63
L1	1.27	2.54
P	2.90	3.30
Q	3.80	4.20

GENERIC MARKING DIAGRAM*



Y = Year
WW = Work Week
XXXXX = Device Code
G = Pb−Free Package

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

STYLE 1:
PIN 1. EMITTER
2., 4. COLLECTOR
3. BASE

STYLE 2:
PIN 1. CATHODE
2., 4. ANODE
3. GATE

STYLE 3:
PIN 1. BASE
2., 4. COLLECTOR
3. EMITTER

STYLE 4:
PIN 1. ANODE 1
2., 4. ANODE 2
3. GATE

STYLE 5:
PIN 1. MT 1
2., 4. MT 2
3. GATE

STYLE 6:
PIN 1. CATHODE
2., 4. GATE
3. ANODE

STYLE 7:
PIN 1. MT 1
2., 4. GATE
3. MT 2

STYLE 8:
PIN 1. SOURCE
2., 4. GATE
3. DRAIN

STYLE 9:
PIN 1. GATE
2., 4. DRAIN
3. SOURCE

STYLE 10:
PIN 1. SOURCE
2., 4. DRAIN
3. GATE

DOCUMENT NUMBER:	**98ASB42049B**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	**TO−225**	**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, ONSEMI , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales