

MOSFET – P-Channel, POWERTRENCH®

-40 V, -50 A, 12.3 mΩ

FDD4141-F085

General Description

This P-Channel MOSFET has been produced using onsemi's proprietary POWERTRENCH technology to deliver low $R_{DS(on)}$ and optimized BV_{DSS} capability to offer superior performance benefit in the applications. and optimized switching performance capability reducing power dissipation losses in converter/inverter applications.

Features

- Typ $R_{DS(on)}$ = 12.3 mΩ at $V_{GS} = -10$ V, $I_D = -12.7$ A
- Typ $R_{DS(on)}$ = 18.0 mΩ at $V_{GS} = -4.5$ V, $I_D = -10.4$ A
- High Performance Trench Technology for Extremely Low $R_{DS(on)}$
- AEC-Q101 Qualified and PPAP Capable
- This Device is Pb-Free and is RoHS Compliant

Applications

- Inverter
- Power Supplies



MOSFET MAXIMUM RATINGS ($T_C = 25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Ratings	Unit
V_{DS}	Drain to Source Voltage	-40	V
V_{GS}	Gate to Source Voltage	±20	V
I_D	Drain Current -Continuous (Package limited) $T_C = 25^\circ\text{C}$ -Continuous (Silicon limited) $T_C = 25^\circ\text{C}$ -Continuous $T_A = 25^\circ\text{C}$ (Note 1a) -Pulsed	-50 -58 -10.8 -100	A
E_{AS}	Single Pulse Avalanche Energy (Note 3)	337	mJ
P_D	Power Dissipation - $T_C = 25^\circ\text{C}$ - $T_A = 25^\circ\text{C}$ (Note 1a)	69 2.4	W
T_J, T_{STG}	Operating and Storage Junction Temperature Range	-55 to +175	$^\circ\text{C}$

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.


THERMAL CHARACTERISTICS

Symbol	Parameter	Ratings	Unit
$R_{\theta JC}$	Maximum Thermal Resistance, Junction to Case	1.8	$^\circ\text{C}/\text{W}$
$R_{\theta JA}$	Maximum Thermal Resistance, Junction to Ambient	52	



P-Channel MOSFET

MARKING DIAGRAM



&Z = Assembly Plant Code
 &3 = Date Code (Year & Week)
 &T = Traceability Code
 FDD4141 = Specific Device Code

ORDERING INFORMATION

See detailed ordering and shipping information on page 3 of this data sheet.

FDD4141–F085

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)


Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
BV _{DSS}	Drain to Source Breakdown Voltage	I _D = –250 μA, V _{GS} = 0 V	–40	–	–	V
$\frac{\Delta BV_{DSS}}{\Delta T_J}$	Breakdown Voltage Temperature Coefficient	I _D = –250 μA, referenced to 25°C	–	–29	–	mV/°C
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} = –32 V, V _{GS} = 0 V	–	–	–1	μA
I _{GSS}	Gate to Source Leakage Current	V _{GS} = ±20 V, V _{DS} = 0 V	–	–	±100	nA
ON CHARACTERISTICS						
V _{GS(th)}	Gate to Source Threshold Voltage	V _{GS} = V _{DS} , I _D = –250 μA	–1	–1.8	–3	V
$\frac{\Delta V_{GS(th)}}{\Delta T_J}$	Gate to Source Threshold Voltage Temperature Coefficient	I _D = –250 μA, referenced to 25°C	–	5.8	–	mV/°C
R _{DS(on)}	Static Drain to Source On Resistance	V _{GS} = –10 V, I _D = –12.7 A	–	10.1	12.3	mΩ
		V _{GS} = –4.5 V, I _D = –10.4 A	–	14.5	18.0	
		V _{GS} = –10 V, I _D = –12.7 A, T _J = 175°C	–	17.3	19.4	
g _{FS}	Forward Transconductance	V _{DS} = –5 V, I _D = –12.7 A	–	38	–	S
DYNAMIC CHARACTERISTICS						
C _{iss}	Input Capacitance	V _{DS} = –20 V, V _{GS} = 0 V, f = 1 MHz	–	2085	2775	pF
C _{oss}	Output Capacitance		–	360	480	pF
C _{rss}	Reverse Transfer Capacitance		–	210	310	pF
R _g	Gate Resistance	f = 1 MHz	–	4.6	–	Ω
SWITCHING CHARACTERISTICS						
t _{d(on)}	Turn-On Delay Time	V _{DD} = –20 V, I _D = –12.7 A, V _{GS} = –10 V, R _{GEN} = 6 Ω	–	10	19	ns
t _r	Rise Time		–	7	13	ns
t _{d(off)}	Turn-Off Delay Time		–	38	60	ns
t _f	Fall Time		–	15	27	ns
Q _g	Total Gate Charge	V _{GS} = 0 V to –10 V V _{DD} = –20 V, I _D = –12.7 A	–	36	50	nC
		V _{GS} = 0 V to –5 V V _{DD} = –20 V, I _D = –12.7 A	–	19	27	nC
Q _{gs}	Gate to Source Charge	V _{DD} = –20 V, I _D = –12.7 A	–	7	–	nC
Q _{gd}	Gate to Drain “Miller” Charge	V _{DD} = –20 V, I _D = –12.7 A	–	8	–	nC
DRAIN–SOURCE DIODE CHARACTERISTICS						
V _{SD}	Source to Drain Diode Forward Voltage	V _{GS} = 0 V, I _S = –12.7 A (Note 2)	–	–0.8	–1.2	V
t _{rr}	Reverse Recovery Time	I _F = –12.7 A, di/dt = 100 A/μs	–	29	44	ns
Q _{rr}	Reverse Recovery Charge		–	26	40	nC

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

FDD4141–F085

NOTES:

1. $R_{\theta JA}$ is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins. $R_{\theta JC}$ is guaranteed by design while $R_{\theta JA}$ is determined by the user's board design.



- a) 52°C/W when mounted on a 1 in² pad of 2 oz copper.



- b) 100°C/W when mounted on a minimum pad.

2. Pulse Test: Pulse Width < 300 μ s, Duty cycle < 2.0%.
3. Starting T_J = 25°C, L = 3 mH, I_{AS} = 15 A, V_{DD} = 40 V, V_{GS} = 10 V.

PACKAGE MARKING AND ORDERING INFORMATION

Device Marking	Device	Package	Reel Size [†]	Tape Width	Quantity
FDD4141	FDD4141–F085	DPAK3	13"	16 mm	2500 Units

[†]For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

TYPICAL CHARACTERISTICS

($T_J = 25^\circ\text{C}$ unless otherwise noted)




Figure 1. On-Region Characteristics




Figure 2. Normalized On-Resistance vs Drain Current and Gate Voltage




Figure 3. Normalized On-Resistance vs Junction Temperature




Figure 4. On-Resistance vs Gate to Source Voltage




Figure 5. Transfer Characteristics




Figure 6. Source to Drain Diode Forward Voltage vs Source Current

TYPICAL CHARACTERISTICS (continued)


(T_J = 25°C unless otherwise noted)

Figure 7. Gate Charge Characteristics




Figure 8. Capacitance vs Drain to Source Voltage




Figure 9. Unclamped Inductive Switching Capability




Figure 10. Maximum Continuous Drain Current vs Case Temperature




Figure 11. Forward Bias Safe Operating Area




Figure 12. Single Pulse Maximum Power Dissipation

TYPICAL CHARACTERISTICS

($T_J = 25^\circ\text{C}$ unless otherwise noted)




Figure 13. Transient Thermal Response Curve

onsemi, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:

Technical Library: www.onsemi.com/design/resources/technical-documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support

For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales