SMPS Series N-Channel IGBT with Anti-Parallel Hyperfast Diode

600 V

HGTG30N60A4D

ON Semiconductor®

www.onsemi.com

The HGTG30N60A4D is a MOS gated high voltage switching devices combining the best features of MOSFETs and bipolar transistors. This device has the high input impedance of a MOSFET and the low on−state conduction loss of a bipolar transistor. The much lower on−state voltage drop varies only moderately between 25°C and 150°C. The IGBT used is the development type TA49343. The diode used in anti−parallel is the development type TA49373.

This IGBT is ideal for many high voltage switching applications operating at high frequencies where low conduction losses are essential. This device has been optimized for high frequency switch mode power supplies.

Formerly Developmental Type TA49345.





TO−247−3LD SHORT LEAD
CASE 340CK
JEDEC STYLE

Features

- >100 kHz Operation 390 V, 30 A
- 200 kHz Operation 390 V, 18 A
- 600 V Switching SOA Capability
- Typical Fall Time 60 ns at T_J = 125°C
- Low Conduction Loss
- *Temperature Compensating* Saber™ Model
- This is a Pb−Free Device

DISCONTINUED
THIS DEVICE IS NOT RECOMMENDED FOR NEW DESIGN
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION

MARKING DIAGRAM



$Y	= ON Semiconductor Logo
&Z	= Assembly Plant Code
&3	= Numeric Date Code
&K	= Lot Code
30N60A4D	= Specific Device Code

ORDERING INFORMATION

See detailed ordering and shipping information on page 8 of this data sheet.

© Semiconductor Components Industries, LLC, 2004

May, 2024 − Rev. 3

Publication Order Number:
HGTG30N60A4D/D

ABSOLUTE MAXIMUM RATINGS (T_C = 25°C unless otherwise specified)

Parameter	Symbol	HGTG30N60A4D	Unit
Collector to Emitter Voltage	BV_{CES}	600	V
Collector Current Continuous At T_C = 25°C At T_C = 110°C	 I_{C25} I_{C110}	 70 60	 A A
Collector Current Pulsed (Note 1)	I_{CM}	240	A
Gate to Emitter Voltage Continuous	V_{GES}	±20	V
Gate to Emitter Voltage Pulsed	V_{GEM}	±30	V
Switching Safe Operating Area at T_J = 150°C, (Figure 2)	SSOA	150 A at 600 V	
Power Dissipation Total at T_C = 25°C	P_D	463	W
Power Dissipation Derating T_C > 25°C		3.7	W/°C
Operating and Storage Junction Temperature Range	T_J, T_{STG}	−55 to 150	°C
Maximum Temperature for Soldering	T_L	260	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Pulse width limited by maximum junction temperature.

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise specified)

Parameter	Symbol	Test Condition		Min	Typ	Max	Unit
Collector to Emitter Breakdown Voltage	BV_{CES}	I_C = 250 μA, V_{GE} = 0 V		600	–	–	V
Collector to Emitter Leakage Current	I_{CES}	V_{CE} = 600 V	T_J = 25°C	–	–	250	μA
			T_J = 125°C	–	–	2.8	mA
Collector to Emitter Saturation Voltage	$V_{CE(SAT)}$	I_C = 30 A, V_{GE} = 15 V	T_J = 25°C	–	1.8	2.6	V
			T_J = 125°C	–	1.6	2.0	V
Gate to Emitter Threshold Voltage	$V_{GE(TH)}$	I_C = 250 μA, V_{CE} = V_{GE}		4.5	5.2	7.0	V
Gate to Emitter Leakage Current	I_{GES}	V_{GE} = ±20 V		–	–	±250	nA
Switching SOA	SSOA	T_J = 150°C, R_G = 3 Ω, V_{GE} = 15 V, L = 100 μH, V_{CE} = 600 V		150	–	–	A
Gate to Emitter Plateau Voltage	V_{GEP}	I_C = 30 A, V_{CE} = 300 V		–	8.5	–	V
On−State Gate Charge	$Q_{g(ON)}$	I_C = 30 A, V_{CE} = 300 V	V_{GE} = 15 V	–	225	270	nC
			V_{GE} = 20 V	–	300	360	nC
Current Turn−On Delay Time	$t_{d(ON)I}$	IGBT and Diode at T_J = 25°C, I_{CE} = 30 A, V_{CE} = 390 V, V_{GE} = 15 V, R_G = 3 Ω, L = 200 μH, Test Circuit (Figure 24)		–	25	–	ns
Current Rise Time	t_{rI}			–	12	–	ns
Current Turn−Off Delay Time	$t_{d(OFF)I}$			–	150	–	ns
Current Fall Time	t_{fI}			–	38	–	ns
Turn−On Energy (Note 2)	E_{ON1}			–	280	–	μJ
Turn−On Energy (Note 2)	E_{ON2}			–	600	–	μJ
Turn−Off Energy (Note 3)	E_{OFF}			–	240	350	μJ
Current Turn−On Delay Time	$t_{d(ON)I}$	IGBT and Diode at T_J = 125°C, I_{CE} = 30 A, V_{CE} = 390 V, V_{GE} = 15 V, R_G = 3 Ω, L = 200 μH, Test Circuit (Figure 24)		–	24	–	ns
Current Rise Time	t_{rI}			–	11	–	ns
Current Turn−Off Delay Time	$t_{d(OFF)I}$			–	180	200	ns
Current Fall Time	t_{fI}			–	58	70	ns
Turn−On Energy (Note 2)	E_{ON1}			–	280	–	μJ
Turn−On Energy (Note 2)	E_{ON2}			–	1000	1200	μJ
Turn−Off Energy (Note 3)	E_{OFF}			–	450	750	μJ
Diode Forward Voltage	V_{EC}	I_{EC} = 30 A		–	2.2	2.5	V
Diode Reverse Recovery Time	t_{rr}	I_{EC} = 30 A, dI_{EC}/dt = 200 A/μs		–	40	55	ns
		I_{EC} = 1 A, dI_{EC}/dt = 200 A/μs		–	30	42	ns

DISCONTINUED
THIS DEVICE IS NOT RECOMMENDED FOR NEW DESIGN
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise specified) (continued)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Thermal Resistance Junction To Case	$R_{\theta JC}$	IGBT	−	−	0.27	°C/W
		Diode	−	−	0.65	°C/W

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

2. Values for two Turn−On loss conditions are shown for the convenience of the circuit designer. E_{ON1} is the turn−on loss of the IGBT only. E_{ON2} is the turn−on loss when a typical diode is used in the test circuit and the diode is at the same T_J as the IGBT. The diode type is specified in Figure 24.
3. Turn−Off Energy Loss (E_{OFF}) is defined as the integral of the instantaneous power loss starting at the trailing edge of the input pulse and ending at the point where the collector current equals zero (I_{CE} = 0 A). All devices were tested per JEDEC Standard No. 24−1 Method for Measurement of Power Device Turn−Off Switching Loss. This test method produces the true total Turn−Off Energy Loss.

TYPICAL PERFORMANCE CURVES (unless otherwise specified)



Figure 1. DC COLLECTOR CURRENT vs. CASE TEMPERATURE



Figure 2. MINIMUM SWITCHING SAFE OPERATING AREA



Figure 3. OPERATING FREQUENCY vs. COLLECTOR TO EMITTER CURRENT



Figure 4. SHORT CIRCUIT WITHSTAND TIME

DISCONTINUED
THIS DEVICE IS NOT RECOMMENDED FOR NEW DESIGN
PLEASE CONTACT YOUR onsemi REPRESENTATIVE FOR INFORMATION

TYPICAL PERFORMANCE CURVES (unless otherwise specified) (continued)



Figure 5. COLLECTOR TO EMITTER ON−STATE VOLTAGE



Figure 6. COLLECTOR TO EMITTER ON−STATE VOLTAGE



Figure 7. TURN−ON ENERGY LOSS vs. COLLECTOR TO EMITTER CURRENT



Figure 8. TURN−OFF ENERGY LOSS vs. COLLECTOR TO EMITTER CURRENT



Figure 9. TURN−ON DELAY TIME vs. COLLECTOR TO EMITTER CURRENT



Figure 10. TURN−ON RISE TIME vs. COLLECTOR TO EMITTER CURRENT

DISCONTINUED
THIS DEVICE IS NOT RECOMMENDED FOR NEW DESIGN
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION

TYPICAL PERFORMANCE CURVES (unless otherwise specified) (continued)



Figure 11. TURN−OFF DELAY TIME vs. COLLECTOR TO EMITTER CURRENT



Figure 12. FALL TIME vs. COLLECTOR TO EMITTER CURRENT



Figure 13. TRANSFER CHARACTERISTIC



Figure 14. GATE CHARGE WAVEFORMS



Figure 15. TOTAL SWITCHING LOSS vs. CASE TEMPERATURE



Figure 16. TOTAL SWITCHING LOSS vs. GATE RESISTANCE

DISCONTINUED
THIS DEVICE IS NOT RECOMMENDED FOR NEW DESIGN
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION

TYPICAL PERFORMANCE CURVES (unless otherwise specified) (continued)



Figure 17. CAPACITANCE vs. COLLECTOR TO EMITTER VOLTAGE



Figure 18. COLLECTOR TO EMITTER ON−STATE VOLTAGE vs. GATE TO EMITTER VOLTAGE



Figure 19. DIODE FORWARD CURRENT vs. FORWARD VOLTAGE DROP



Figure 20. RECOVERY TIMES vs. FORWARD CURRENT



Figure 21. RECOVERY TIMES vs. RATE OF CHANGE OF CURRENT



Figure 22. STORED CHARGE vs. RATE OF CHANGE OF CURRENT

DISCONTINUED
THIS DEVICE IS NOT RECOMMENDED FOR NEW DESIGN
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION

TYPICAL PERFORMANCE CURVES (unless otherwise specified) (continued)



Figure 23. IGBT NORMALIZED TRANSIENT THERMAL RESPONSE, JUNCTION TO CASE

TEST CIRCUIT AND WAVEFORMS



Figure 24. INDUCTIVE SWITCHING TEST CIRCUIT



Figure 25. SWITCHING TEST WAVEFORMS

DISCONTINUED
THIS DEVICE IS NOT RECOMMENDED FOR NEW DESIGN
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION

HANDLING PRECAUTIONS FOR IGBTs

Insulated Gate Bipolar Transistors are susceptible to gate−insulation damage by the electrostatic discharge of energy through the devices. When handling these devices, care should be exercised to assure that the static charge built in the handler's body capacitance is not discharged through the device. With proper handling and application procedures, however, IGBTs are currently being extensively used in production by numerous equipment manufacturers in military, industrial and consumer applications, with virtually no damage problems due to electrostatic discharge. IGBTs can be handled safely if the following basic precautions are taken:

1. Prior to assembly into a circuit, all leads should be kept shorted together either by the use of metal shorting springs or by the insertion into conductive material such as "ECCOSORBD™ LD26" or equivalent.
2. When devices are removed by hand from their carriers, the hand being used should be grounded by any suitable means − for example, with a metallic wristband.
3. Tips of soldering irons should be grounded.
4. Devices should never be inserted into or removed from circuits with power on.
5. *Gate Voltage Rating* − Never exceed the gate−voltage rating of V_{GEM}. Exceeding the rated V_{GE} can result in permanent damage to the oxide layer in the gate region.
6. *Gate Termination* − The gates of these devices are essentially capacitors. Circuits that leave the gate open− circuited or floating should be avoided. These conditions can result in turn−on of the device due to voltage buildup on the input capacitor due to leakage currents or pickup.
7. *Gate Protection* - These devices do not have an internal monolithic Zener diode from gate to emitter. If gate protection is required an external Zener is recommended.

OPERATING FREQUENCY INFORMATION

Operating frequency information for a typical device (Figure 3) is presented as a guide for estimating device performance for a specific application. Other typical frequency vs collector current (I_{CE}) plots are possible using the information shown for a typical unit in Figures 5, 6, 7, 8, 9 and 11. The operating frequency plot (Figure 3) of a typical device shows f_{MAX1} or f_{MAX2}; whichever is smaller at each point. The information is based on measurements of a typical device and is bounded by the maximum rated junction temperature.

f_{MAX1} is defined by $f_{MAX1} = 0.05 / (t_{d(OFF)I} + t_{d(ON)I})$. Deadtime (the denominator) has been arbitrarily held to 10% of the on−state time for a 50% duty factor. Other definitions are possible. $t_{d(OFF)I}$ and $t_{d(ON)I}$ are defined in Figure 25. Device turn−off delay can establish an additional frequency limiting condition for an application other than T_{JM}. $t_{d(OFF)I}$ is important when controlling output ripple under a lightly loaded condition.

f_{MAX2} is defined by $f_{MAX2} = (P_D - P_C) / (E_{OFF} + E_{ON2})$. The allowable dissipation (P_D) is defined by $P_D = (T_{JM} - T_C) / R_{\theta JC}$. The sum of device switching and conduction losses must not exceed P_D. A 50% duty factor was used (Figure 3) and the conduction losses (P_C) are approximated by $P_C = (V_{CE} \times I_{CE}) / 2$.

E_{ON2} and E_{OFF} are defined in the switching waveforms shown in Figure 25. E_{ON2} is the integral of the instantaneous power loss ($I_{CE} \times V_{CE}$) during turn−on and E_{OFF} is the integral of the instantaneous power loss ($I_{CE} \times V_{CE}$) during turn−off. All tail losses are included in the calculation for E_{OFF}; i.e., the collector current equals zero ($I_{CE} = 0$).

DISCONTINUED
THIS DEVICE IS NOT RECOMMENDED FOR NEW DESIGN
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION

ORDERING INFORMATION

Part Number	Package	Brand	Shipping†
HGTG30N60A4D	TO−247	30N60A4D	450 Units / Tube

NOTE: When ordering, use the entire part number.

Saber is a registered trademark of Sabremark Limited Partnership.
All brand names and product names appearing in this document are registered trademarks or trademarks of their respective holders.

TO−247−3LD SHORT LEAD
CASE 340CK
ISSUE A

DATE 31 JAN 2019



DIM	MILLIMETERS		
	MIN	NOM	MAX
A	4.58	4.70	4.82
A1	2.20	2.40	2.60
A2	1.40	1.50	1.60
b	1.17	1.26	1.35
b2	1.53	1.65	1.77
b4	2.42	2.54	2.66
c	0.51	0.61	0.71
D	20.32	20.57	20.82
D1	13.08	~	~
D2	0.51	0.93	1.35
E	15.37	15.62	15.87
E1	12.81	~	~
E2	4.96	5.08	5.20
e	~	5.56	~
L	15.75	16.00	16.25
L1	3.69	3.81	3.93
ØP	3.51	3.58	3.65
ØP1	6.60	6.80	7.00
Q	5.34	5.46	5.58
S	5.34	5.46	5.58

NOTES: UNLESS OTHERWISE SPECIFIED.

A. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.
B. ALL DIMENSIONS ARE IN MILLIMETERS.
C. DRAWING CONFORMS TO ASME Y14.5 - 2009.
D. DIMENSION A1 TO BE MEASURED IN THE REGION DEFINED BY L1.
E. LEAD FINISH IS UNCONTROLLED IN THE REGION DEFINED BY L1.

GENERIC MARKING DIAGRAM*

AYWWZZ
XXXXXXX
XXXXXXX
o

XXXX = Specific Device Code
A = Assembly Location
Y = Year
WW = Work Week
ZZ = Assembly Lot Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	98AON13851G	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	TO−247−3LD SHORT LEAD	PAGE 1 OF 1

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, onsemi, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales