NDD01N60, NDT01N60

N-Channel Power MOSFET 600 V, 8.5 Ω

Features

- 100% Avalanche Tested
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant

ON Semiconductor®

http://onsemi.com

$V_{(BR)DSS}$	$R_{DS(ON)}$ MAX
600 V	8.5 Ω @ 10 V

N−Channel MOSFET



ABSOLUTE MAXIMUM RATINGS (T_J = 25°C unless otherwise noted)

Parameter	Symbol	NDD	NDT	Unit
Drain−to−Source Voltage	V_{DSS}	600		V
Continuous Drain Current $R_{\theta JC}$ Steady State, T_C = 25°C (Note 1)	I_D	1.5	0.4	A
Continuous Drain Current $R_{\theta JC}$ Steady State, T_C = 100°C (Note 1)	I_D	1.0	0.25	A
Pulsed Drain Current, t_p = 10 μs	I_{DM}	6.0	1.5	A
Power Dissipation − $R_{\theta JC}$ Steady State, T_C = 25°C	P_D	46	2.5	W
Gate−to−Source Voltage	V_{GS}	±30		V
Single Pulse Drain−to−Source Avalanche Energy (I_{PK} = 1.0 A)	EAS	13		mJ
Peak Diode Recovery (Note 2)	dv/dt	4.5		V/ns
Source Current (Body Diode)	I_S	1.5	0.4	A
Lead Temperature for Soldering Leads	T_L	260		°C
Operating Junction and Storage Temperature	T_J, T_{STG}	−55 to +150		°C

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. Limited by maximum junction temperature
2. I_S = 1.5 A, di/dt ≤ 100 A/μs, $V_{DD} \le BV_{DSS}$

THERMAL RESISTANCE

Parameter		Symbol	Value	Unit
Junction−to−Case (Drain)	NDD01N60	$R_{\theta JC}$	2.7	°C/W
Junction−to−Ambient	(Note 4) NDD01N60	$R_{\theta JA}$	38	°C/W
	(Note 3) NDD01N60−1		96	
	(Note 4) NDT01N60		58	
	(Note 5) NDT01N60		141	

3. Insertion mounted.
4. Surface−mounted on FR4 board using 1" sq. pad size (Cu area = 1.127" sq. [2 oz] including traces).
5. Surface−mounted on FR4 board using minimum recommended pad size (Cu area = 0.026" sq. [2 oz]).

MARKING DIAGRAMS



DPAK
CASE 369C
STYLE 2





IPAK
CASE 369D
STYLE 2



Y = Year
WW = Work Week
G = Pb−Free Package



SOT−223
CASE 318E
STYLE 3



A = Assembly Location
Y = Year
W = Work Week
01N60 = Specific Device Code
▪ = Pb−Free Package

(Note: Microdot may be in either location)

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 2 of this data sheet.

© Semiconductor Components Industries, LLC, 2013

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

Characteristic	Symbol	Test Conditions		Min	Typ	Max	Unit
OFF CHARACTERISTICS							
Drain−to−Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS} = 0 V, I_D = 1 mA		600			V
Drain−to−Source Breakdown Voltage Temperature Coefficient	$V_{(BR)DSS}/T_J$	Reference to 25°C, I_D = 1 mA			660		mV/°C
Drain−to−Source Leakage Current	I_{DSS}	V_{DS} = 600 V, V_{GS} = 0 V	T_J = 25°C			1	μA
			T_J = 125°C			50	
Gate−to−Source Leakage Current	I_{GSS}	V_{GS} = ±20 V				±100	nA
ON CHARACTERISTICS (Note 6)							
Gate Threshold Voltage	$V_{GS(TH)}$	V_{DS} = V_{GS}, I_D = 50 μA		2.2	3.3	3.7	V
Negative Threshold Temperature Coefficient	$V_{GS(TH)}/T_J$				7.0		mV/°C
Static Drain-to-Source On Resistance	$R_{DS(on)}$	V_{GS} = 10 V, I_D = 0.2 A			8.0	8.5	Ω
Forward Transconductance	g_{FS}	V_{DS} = 15 V, I_D = 0.2 A			0.9		S
CHARGES, CAPACITANCES & GATE RESISTANCES							
Input Capacitance (Note 7)	C_{iss}	V_{DS} = 25 V, V_{GS} = 0 V, f = 1 MHz			160		pF
Output Capacitance (Note 7)	C_{oss}				22		
Reverse Transfer Capacitance (Note 7)	C_{rss}				4.0		
Total Gate Charge (Note 7)	Q_g	V_{DS} = 300 V, I_D = 0.4 A, V_{GS} = 10 V			7.2		nC
Gate-to-Source Charge (Note 7)	Q_{gs}				1.2		
Gate-to-Drain Charge (Note 7)	Q_{gd}				3.1		
Plateau Voltage	V_{GP}				4.5		V
Gate Resistance	R_g				6.7		Ω
SWITCHING CHARACTERISTICS (Note 8)							
Turn-on Delay Time	$t_{d(on)}$	V_{DD} = 300 V, I_D = 0.4 A, V_{GS} = 10 V, R_G = 0 Ω			8.0		ns
Rise Time	t_r				5.1		
Turn-off Delay Time	$t_{d(off)}$				16.5		
Fall Time	t_f				21.3		
DRAIN−SOURCE DIODE CHARACTERISTICS							
Diode Forward Voltage	V_{SD}	I_S = 0.4 A, V_{GS} = 0 V	T_J = 25°C		0.78	1.6	V
			T_J = 125°C		0.63		
Reverse Recovery Time	t_{rr}	V_{GS} = 0 V, V_{DD} = 30 V, I_S = 1.0 A, d_i/d_t = 100 A/μs			179		ns
Charge Time	t_a				37		
Discharge Time	t_b				141		
Reverse Recovery Charge	Q_{rr}				288		nC

6. Pulse Width ≤ 300 μs, Duty Cycle ≤ 2%.
7. Guaranteed by design.
8. Switching characteristics are independent of operating junction temperatures.

ORDERING INFORMATION

Device	Package	Shipping†
NDD01N60−1G	IPAK (Pb-Free, Halogen-Free)	75 Units / Rail
NDD01N60T4G	DPAK (Pb-Free, Halogen-Free)	2500 / Tape & Reel
NDT01N60T1G	SOT−223 (Pb-Free, Halogen-Free)	1000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

TYPICAL CHARACTERISTICS



Figure 1. On−Region Characteristics



Figure 2. Transfer Characteristics



Figure 3. On−Resistance vs. Gate Voltage



Figure 4. On−Resistance vs. Drain Current and Gate Voltage



Figure 5. On−Resistance Variation with Temperature



Figure 6. Drain−to−Source Leakage Current vs. Voltage

TYPICAL CHARACTERISTICS



Figure 7. Capacitance Variation



Figure 8. Gate−to−Source and Drain−to−Source Voltage vs. Total Charge



Figure 9. Resistive Switching Time Variation vs. Gate Resistance



Figure 10. Diode Forward Voltage vs. Current



Figure 11. Maximum Rated Forward Biased Safe Operating Area NDD01N60



Figure 12. Maximum Rated Forward Biased Safe Operating Area NDT01N60

TYPICAL CHARACTERISTICS



Figure 13. Thermal Impedance (Junction−to−Case) for NDD01N60



Figure 14. Thermal Impedance (Junction−to−Ambient) for NDT01N60



SCALE 1:1

DPAK−3 6.10x6.54x2.28, 2.29P
CASE 369C
ISSUE L

DATE 24 AUG 2026



TOP VIEW



SIDE VIEW

MILLIMETERS			
DIM	MIN	NOM	MAX
A	2.18	2.28	2.38
A1	0.00	−−−	0.13
b	0.63	0.76	0.89
b2	0.72	0.93	1.14
b3	4.57	5.02	5.46
c	0.46	0.54	0.61
c2	0.46	0.54	0.61
D	5.97	6.10	6.22
E	6.35	6.54	6.73
e	2.29 BSC		
H	9.40	9.91	10.41
L	1.40	1.59	1.78
L1	2.90 REF		
L2	0.51 BSC		
L3	0.89	−−−	1.27
L4	−−−	−−−	1.01
Z	3.93	−−−	−−−



BOTTOM VIEW

ALTERNATE CONSTRUCTIONS

NOTES:

1. DIMENSIONING AND TOLERANCING ASME Y14.5M, 2018.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. THERMAL PAD CONTOUR OPTIONAL WITHIN DIMENSIONS b3, L3, AND Z.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR BURRS.
5. DIMENSIONS D AND E ARE DETERMINED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY.
6. DATUMS A AND B ARE DETERMINED AT DATUM PLANE H.
7. OPTIONAL MOLD FEATURE.



DETAIL A
ROTATED 90° CW



RECOMMENDED MOUNTING FOOTPRINT*
*For additional information on our Pb−Free strategy and soldering details, please download the onsemi Soldering and Mounting Techniques reference manual, SOLDERRM/D.

DOCUMENT NUMBER:	**98AON10527D**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	**DPAK−3 6.10x6.54x2.28, 2.29P**	**PAGE 1 OF 2**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

DPAK−3 6.10x6.54x2.28, 2.29P
CASE 369C
ISSUE L

DATE 24 AUG 2026

GENERIC MARKING DIAGRAM*



IC **Discrete**

XXXXXX	= Device Code
A	= Assembly Location
L	= Wafer Lot
Y	= Year
WW	= Work Week
G	= Pb−Free Package

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

STYLE 1:
PIN 1. BASE
2. COLLECTOR
3. EMITTER
4. COLLECTOR

STYLE 2:
PIN 1. GATE
2. DRAIN
3. SOURCE
4. DRAIN

STYLE 3:
PIN 1. ANODE
2. CATHODE
3. ANODE
4. CATHODE

STYLE 4:
PIN 1. CATHODE
2. ANODE
3. GATE
4. ANODE

STYLE 5:
PIN 1. GATE
2. ANODE
3. CATHODE
4. ANODE

STYLE 6:
PIN 1. MT1
2. MT2
3. GATE
4. MT2

STYLE 7:
PIN 1. GATE
2. COLLECTOR
3. EMITTER
4. COLLECTOR

STYLE 8:
PIN 1. N/C
2. CATHODE
3. ANODE
4. CATHODE

STYLE 9:
PIN 1. ANODE
2. CATHODE
3. RESISTOR ADJUST
4. CATHODE

STYLE 10:
PIN 1. CATHODE
2. ANODE
3. CATHODE
4. ANODE

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2011

onsemi, ONSEMI , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales