ON Semiconductor

Is Now

OBSOLETE
THIS DEVICE IS OBSOLETE
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION

To learn more about onsemi™, please visit our website at

www.onsemi.com

onsemi and onsemi and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi** product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner. Other names and brands may be claimed as the property of others.

NDF06N62Z

N-Channel Power MOSFET 620 V, 1.2 Ω

Features

- Low ON Resistance
- Low Gate Charge
- ESD Diode−Protected Gate
- 100% Avalanche Tested
- These Devices are Pb−Free, Halogen Free/BFR Free and are RoHS Compliant

ABSOLUTE MAXIMUM RATINGS (T_C = 25°C unless otherwise noted)

Rating	Symbol	NDF06N62Z	Unit
Drain−to−Source Voltage	V_{DSS}	620	V
Continuous Drain Current $R_{\theta JC}$ (Note 1)	I_D	6.0	A
Continuous Drain Current $R_{\theta JC}$, T_A = 100°C (Note 1)	I_D	3.8	A
Pulsed Drain Current, V_{GS} @ 10 V	I_{DM}	20	A
Power Dissipation $R_{\theta JC}$	P_D	31	W
Gate−to−Source Voltage	V_{GS}	±30	V
Single Pulse Avalanche Energy, I_D = 6.0 A	E_{AS}	113	mJ
ESD (HBM) (JESD 22−A114)	V_{esd}	3000	V
RMS Isolation Voltage (t = 0.3 sec., R.H. ≤ 30%, T_A = 25°C) (Figure 14)	V_{ISO}	4500	V
Peak Diode Recovery (Note 2)	dv/dt	4.5	V/ns
Continuous Source Current (Body Diode)	I_S	6.0	A
Maximum Temperature for Soldering Leads	T_L	260	°C
Operating Junction and Storage Temperature Range	T_J, T_{stg}	−55 to 150	°C

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. Limited by maximum junction temperature
2. I_{SD} = 6.0 A, di/dt ≤ 100 A/μs, $V_{DD} \le BV_{DSS}$, T_J = +150°C

ON Semiconductor®

http://onsemi.com

V_{DSS}	$R_{DS(ON)}$ (MAX) @ 3 A
620 V	1.2 Ω

N−Channel



TO−220FP
CASE 221D
STYLE 1

MARKING DIAGRAM



A = Location Code
Y = Year
WW = Work Week
G = Pb−Free, Halogen−Free Package

ORDERING INFORMATION

Device	Package	Shipping
NDF06N62ZG	TO−220FP (Pb−Free, Halogen−Free)	50 Units / Rail

OBSOLETE
THIS DEVICE IS OBSOLETE
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION

© Semiconductor Components Industries, LLC, 2011

THERMAL RESISTANCE

Parameter	Symbol	NDF06N62Z	Unit
Junction−to−Case (Drain)	$R_{\theta JC}$	4.0	°C/W
Junction−to−Ambient Steady State (Note 3)	$R_{\theta JA}$	50	

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

Characteristic	Test Conditions		Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS							
Drain−to−Source Breakdown Voltage	V_{GS} = 0 V, I_D = 1 mA		BV_{DSS}	620			V
Breakdown Voltage Temperature Coefficient	Reference to 25°C, I_D = 1 mA		$\Delta BV_{DSS}/\Delta T_J$		0.6		V/°C
Drain−to−Source Leakage Current	V_{DS} = 620 V, V_{GS} = 0 V	25°C	I_{DSS}			1	μA
		125°C				50	
Gate−to−Source Forward Leakage	V_{GS} = ±20 V		I_{GSS}			±10	μA
ON CHARACTERISTICS (Note 4)							
Static Drain−to−Source On−Resistance	V_{GS} = 10 V, I_D = 3.0 A		$R_{DS(on)}$		0.98	1.2	Ω
Gate Threshold Voltage	V_{DS} = V_{GS}, I_D = 100 μA		$V_{GS(th)}$	3.0		4.5	V
Forward Transconductance	V_{DS} = 15 V, I_D = 3.0 A		g_{FS}		5.0		S
DYNAMIC CHARACTERISTICS							
Input Capacitance	V_{DS} = 25 V, V_{GS} = 0 V, f = 1.0 MHz		C_{iss}		923		pF
Output Capacitance			C_{oss}		106		
Reverse Transfer Capacitance			C_{rss}		23		
Total Gate Charge	V_{DD} = 310 V, I_D = 6.0 A, V_{GS} = 10 V		Q_g		32		nC
Gate−to−Source Charge			Q_{gs}		6.3		
Gate−to−Drain (“Miller”) Charge			Q_{gd}		17		
Plateau Voltage			V_{gp}		6.3		V
Gate Resistance			R_g		3.2		Ω
RESISTIVE SWITCHING CHARACTERISTICS							
Turn−On Delay Time	V_{DD} = 310 V, I_D = 6.0 A, V_{GS} = 10 V, R_G = 5 Ω		$t_{d(on)}$		13		ns
Rise Time			t_r		19		
Turn−Off Delay Time			$t_{d(off)}$		32		
Fall Time			t_f		28		
SOURCE−DRAIN DIODE CHARACTERISTICS (T_C = 25°C unless otherwise noted)							
Diode Forward Voltage	I_S = 6.0 A, V_{GS} = 0 V		V_{SD}			1.6	V
Reverse Recovery Time	V_{GS} = 0 V, V_{DD} = 30 V, I_S = 6.0 A, di/dt = 100 A/μs		t_{rr}		338		ns
Reverse Recovery Charge			Q_{rr}		2.0		μC

3. Insertion mounted
4. Pulse Width ≤ 380 μs, Duty Cycle ≤ 2%.

OBSOLETE
THIS DEVICE IS OBSOLETE
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION

TYPICAL CHARACTERISTICS



Figure 1. On−Region Characteristics



Figure 2. Transfer Characteristics



Figure 3. On−Resistance vs. V_{GS}



Figure 4. On−Resistance vs. Drain Current and Gate Voltage



Figure 5. On−Resistance Variation with Temperature



Figure 6. BVDSS Variation with Temperature

OBSOLETE
THIS DEVICE IS OBSOLETE
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION

TYPICAL CHARACTERISTICS



Figure 7. Drain−to−Source Leakage Current vs. Voltage



Figure 8. Capacitance Variation



Figure 9. Gate−to−Source and Drain−to−Source Voltage vs. Total Charge



Figure 10. Resistive Switching Time Variation vs. Gate Resistance



Figure 11. Diode Forward Voltage vs. Current



Figure 12. Maximum Rated Forward Biased Safe Operating Area for NDF06N62Z

OBSOLETE
THIS DEVICE IS OBSOLETE
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION

TYPICAL CHARACTERISTICS



Figure 13. Thermal Impedance for NDF06N62Z



Figure 14. Isolation Test Diagram

Measurement made between leads and heatsink with all leads shorted together.

*For additional mounting information, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

OBSOLETE
THIS DEVICE IS OBSOLETE
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION

PACKAGE DIMENSIONS

TO−220FP
CASE 221D−03
ISSUE K



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH
3. 221D−01 THRU 221D−02 OBSOLETE, NEW STANDARD 221D−03.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	0.617	0.635	15.67	16.12
B	0.392	0.419	9.96	10.63
C	0.177	0.193	4.50	4.90
D	0.024	0.039	0.60	1.00
F	0.116	0.129	2.95	3.28
G	0.100 BSC		2.54 BSC	
H	0.118	0.135	3.00	3.43
J	0.018	0.025	0.45	0.63
K	0.503	0.541	12.78	13.73
L	0.048	0.058	1.23	1.47
N	0.200 BSC		5.08 BSC	
Q	0.122	0.138	3.10	3.50
R	0.099	0.117	2.51	2.96
S	0.092	0.113	2.34	2.87
U	0.239	0.271	6.06	6.88

STYLE 1:
PIN 1. GATE
2. DRAIN
3. SOURCE

OBSOLETE
THIS DEVICE IS OBSOLETE
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION

ON Semiconductor and ON are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5773−3850

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative