

Silicon Carbide (SiC) MOSFET - EliteSiC, 12.2 mohm, 650 V, M3S, TO-247-3L

NTHL012N065M3S

Features

- Typical $R_{DS(ON)} = 12.2 \text{ m}\Omega @ V_{GS} = 18 \text{ V}$
- Ultra Low Gate Charge ($Q_{G(tot)} = 135 \text{ nC}$)
- High Speed Switching with Low Capacitance ($C_{OSS} = 281 \text{ pF}$)
- 100% Avalanche Tested
- This Device is Halide Free and RoHS Compliant with Exemption 7a, Pb-Free 2LI (on second level interconnection)

Applications

- SMPS, Solar Inverters, UPS, Energy Storage, EV Charging Infrastructure


MAXIMUM RATINGS ($T_J = 25 \text{ }^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-to-Source Voltage	V_{DSS}	650	V
Dynamic Gate-to-Source Voltage	V_{GS}	-10/22.6	V
Continuous Drain Current	$T_C = 25 \text{ }^\circ\text{C}$	I_D	123 A
Power Dissipation		P_D	428 W
Continuous Drain Current	$T_C = 100 \text{ }^\circ\text{C}$	I_D	87 A
Power Dissipation		P_D	214 W
Pulsed Drain Current (Note 1)	$T_C = 25 \text{ }^\circ\text{C}$ $t_p = 100 \text{ }\mu\text{s}$	I_{DM}	327 A
Continuous Source-Drain Current (Body Diode)	$T_C = 25 \text{ }^\circ\text{C}$ $V_{GS} = -3 \text{ V}$	I_S	71 A
	$T_C = 100 \text{ }^\circ\text{C}$ $V_{GS} = -3 \text{ V}$		40
Pulsed Source-Drain Current (Body Diode) (Note 1)	$T_C = 25 \text{ }^\circ\text{C}$ $V_{GS} = -3 \text{ V}$ $t_p = 100 \text{ }\mu\text{s}$	I_{SM}	389 A
Single Pulse Avalanche Energy ($I_{LPK} = 72 \text{ A}$, $L = 0.1 \text{ mH}$) (Note 2)	E_{AS}	259	mJ
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55 to +175	$^\circ\text{C}$
Lead Temperature for Soldering Purposes (1/8" from case for 10 seconds)	T_L	268	$^\circ\text{C}$


Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Single pulse, limited by max junction temperature.
2. E_{AS} of 259 mJ is based on starting $T_J = 25 \text{ }^\circ\text{C}$, $L = 0.1 \text{ mH}$, $I_{AS} = 72 \text{ A}$, $V_{DD} = 100 \text{ V}$, $V_{GS} = 18 \text{ V}$.

$V_{(BR)DSS}$	$R_{DS(ON)}$ TYP	I_D MAX
650 V	12.2 m Ω @ 18 V	123 A




N-CHANNEL MOSFET



**TO-247-3LD
CASE 340CX**

MARKING DIAGRAM



HL012N065M3S = Specific Device Code
 A = Assembly Location
 Y = Year
 WW = Work Week
 ZZ = Lot Traceability

ORDERING INFORMATION

Device	Package	Shipping
NTHL012N065M3S	TO-247-3L	30 Units / Tube

NTHL012N065M3S

THERMAL CHARACTERISTICS

Parameter	Symbol	Value	Unit
Thermal Resistance, Junction-to-Case (Note 3)	$R_{\theta JC}$	0.35	$^{\circ}\text{C}/\text{W}$

3. The entire application environment impacts the thermal resistance values shown, they are not constants and are only valid for the particular conditions noted.

RECOMMENDED OPERATING CONDITIONS

Parameter	Symbol	Value	Unit
Operation Values of Gate-to-Source Voltage	V_{GSop}	-3/+18	V

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

ELECTRICAL CHARACTERISTICS ($T_J = 25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
-----------	--------	-----------------	-----	-----	-----	------

OFF CHARACTERISTICS

Drain-to-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS} = 0\text{ V}, I_D = 1\text{ mA}, T_J = 25^{\circ}\text{C}$	650	-	-	V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 650\text{ V}, T_J = 25^{\circ}\text{C}$	-	-	10	μA
		$V_{DS} = 650\text{ V}, T_J = 175^{\circ}\text{C}$ (Note 5)	-	-	500	μA
Gate-to-Source Leakage Current	I_{GSS}	$V_{GS} = -10\text{ V}, V_{DS} = 0\text{ V}$	-1	-	-	μA
		$V_{GS} = +22.6\text{ V}, V_{DS} = 0\text{ V}$	-	-	1	

ON CHARACTERISTICS

Drain-to-Source On Resistance	$R_{DS(on)}$	$V_{GS} = 18\text{ V}, I_D = 40\text{ A}, T_J = 25^{\circ}\text{C}$	-	12.2	17	m Ω
		$V_{GS} = 18\text{ V}, I_D = 40\text{ A}, T_J = 175^{\circ}\text{C}$ (Note 5)	-	19	-	
		$V_{GS} = 15\text{ V}, I_D = 40\text{ A}, T_J = 25^{\circ}\text{C}$	-	15	-	
		$V_{GS} = 15\text{ V}, I_D = 40\text{ A}, T_J = 175^{\circ}\text{C}$ (Note 5)	-	20.4	-	
Gate Threshold Voltage	$V_{GS(TH)}$	$V_{GS} = V_{DS}, I_D = 20\text{ mA}, T_J = 25^{\circ}\text{C}$	2.0	2.7	4.0	V
Forward Transconductance	g_{FS}	$V_{DS} = 10\text{ V}, I_D = 40\text{ A}$ (Note 5)	-	45	-	S

CHARGES, CAPACITANCES & GATE RESISTANCE

Input Capacitance	C_{ISS}	$V_{DS} = 400\text{ V}, V_{GS} = 0\text{ V}, f = 1\text{ MHz}$ (Note 5)	-	3772	-	pF
Output Capacitance	C_{OSS}		-	281	-	
Reverse Transfer Capacitance	C_{RSS}		-	25	-	
Total Gate Charge	$Q_G(TOT)$	$V_{DD} = 400\text{ V}, I_D = 40\text{ A}, V_{GS} = -3/18\text{ V}$ (Note 5)	-	135	-	nC
Gate-to-Source Charge	Q_{GS}		-	35	-	
Gate-to-Drain Charge	Q_{GD}		-	29	-	
Gate Resistance	R_G	$f = 1\text{ MHz}$	-	1.76	-	Ω

SWITCHING CHARACTERISTICS

Turn-On Delay Time	$t_{d(ON)}$	$V_{GS} = -3/18\text{ V}, I_D = 40\text{ A}, V_{DD} = 400\text{ V}, R_G = 4.7\text{ }\Omega, L_{stray} = 18\text{ nH}, T_J = 25^{\circ}\text{C}$ (Notes 4, 5)	-	43	-	ns
Turn-Off Delay Time	$t_{d(OFF)}$		-	49	-	
Rise Time	t_r		-	18	-	
Fall Time	t_f		-	15	-	μJ
Turn-On Switching Loss	E_{ON}		-	455	-	
Turn-Off Switching Loss	E_{OFF}		-	151	-	
Total Switching Loss	E_{TOT}		-	606	-	

NTHL012N065M3S

ELECTRICAL CHARACTERISTICS ($T_J = 25\text{ }^\circ\text{C}$ unless otherwise specified) (continued)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
SWITCHING CHARACTERISTICS						
Turn-On Delay Time	$t_{d(ON)}$	$V_{GS} = -3/18\text{ V}$, $I_D = 40\text{ A}$, $V_{DD} = 400\text{ V}$, $R_G = 4.7\ \Omega$, $L_{stray} = 18\text{ nH}$, $T_J = 175\text{ }^\circ\text{C}$ (Notes 4, 5)	-	15	-	ns
Turn-Off Delay Time	$t_{d(OFF)}$		-	60	-	
Rise Time	t_r		-	43	-	
Fall Time	t_f		-	17	-	
Turn-On Switching Loss	E_{ON}		-	463	-	μJ
Turn-Off Switching Loss	E_{OFF}		-	200	-	
Total Switching Loss	E_{TOT}		-	663	-	

SOURCE-TO-DRAIN DIODE CHARACTERISTICS

Forward Diode Voltage	V_{SD}	$I_{SD} = 40\text{ A}$, $V_{GS} = -3\text{ V}$, $T_J = 25\text{ }^\circ\text{C}$	-	4.5	6.0	V
		$I_{SD} = 40\text{ A}$, $V_{GS} = -3\text{ V}$, $T_J = 175\text{ }^\circ\text{C}$ (Note 5)	-	4.2	-	
Reverse Recovery Time	t_{RR}	$V_{GS} = -3\text{ V}$, $I_S = 40\text{ A}$, $di/dt = 1000\text{ A}/\mu\text{s}$, $V_{DS} = 400\text{ V}$, $T_J = 25\text{ }^\circ\text{C}$ (Note 5)	-	28	-	ns
Charge Time	t_a		-	15	-	
Discharge Time	t_b		-	11	-	
Reverse Recovery Charge	Q_{RR}		-	261	-	nC
Reverse Recovery Energy	E_{REC}		-	39	-	μJ
Peak Reverse Recovery Current	I_{RRM}		-	12	-	A

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

4. E_{ON}/E_{OFF} result is with body diode.

5. Defined by design, not subject to production test.

TYPICAL CHARACTERISTICS




Figure 1. Output Characteristics




Figure 2. Output Characteristics




Figure 3. Output Characteristics




Figure 4. Transfer Characteristics




Figure 5. On-Resistance vs. Gate Voltage




Figure 6. On-Resistance vs. Drain Current

TYPICAL CHARACTERISTICS (continued)




Figure 7. On-Resistance vs. Drain Current




Figure 8. On-Resistance vs. Junction Temperature




Figure 9. Gate Charge Characteristics




Figure 10. Capacitance Characteristics




Figure 11. Stored Energy vs. Drain to Source Voltage




Figure 12. Reverse Conduction Characteristics

TYPICAL CHARACTERISTICS (continued)




Figure 13. Reverse Conduction Characteristics




Figure 14. Maximum Power Dissipation vs. Case Temperature




Figure 15. Safe Operating Area




Figure 16. Avalanche Current vs. Pulse Time (UIS)




Figure 17. Inductive Switching Loss vs. Drain Current




Figure 18. Inductive Switching Loss vs. Drain Current

TYPICAL CHARACTERISTICS (continued)




Figure 19. Inductive Switching Loss vs. Gate Resistance




Figure 20. Inductive Switching Loss vs. Gate Resistance




Figure 21. Inductive Switching Loss vs. Gate Resistance




Figure 22. Inductive Switching Loss vs. Gate Resistance




Figure 23. Inductive Switching Loss vs. Drain-to-Source Voltage




Figure 24. Inductive Switching Loss vs. Junction Temperature

NTHL012N065M3S

TYPICAL CHARACTERISTICS (continued)




Figure 25. Thermal Response Characteristics

NTHL012N065M3S


REVISION HISTORY

Revision	Description of Changes	Date
0	Initial document version release	2/10/2026

NTHL012N065M3S

PACKAGE DIMENSIONS

TO-247-3LD
CASE 340CX
ISSUE A



NOTES: UNLESS OTHERWISE SPECIFIED.

- A. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.
- B. ALL DIMENSIONS ARE IN MILLIMETERS.
- C. DRAWING CONFORMS TO ASME Y14.5 - 2009.
- D. DIMENSION A1 TO BE MEASURED IN THE REGION DEFINED BY L1.
- E. LEAD FINISH IS UNCONTROLLED IN THE REGION DEFINED BY L1.

onsemi, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:

Technical Library: www.onsemi.com/design/resources/technical-documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support

For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales

