


E-PKG AXIAL-LEADED GLASS DIODE

CASE 017AE

ISSUE O

DATE 10 AUG 2012



NOTES:

1. CONTROLLING DIMENSION: INCHES
2. PACKAGE CONTOUR IS OPTIONAL WITHIN DIMENSIONS A AND B. HEAT SLUGS, IF ANY, SHALL BE WITHIN DIMENSION B BUT NOT SUBJECT TO ITS MINIMUM VALUE.
3. DIMENSION A DEFINES THE ENTIRE BODY INCLUDING HEAT SLUGS AND SECTIONS OF THE LEAD OVER WHICH THE DIAMETER IS UNCONTROLLED. DIMENSION F DEFINES THESE SECTIONS OF THE LEAD.
4. DIMENSION B IS MEASURED AT THE MAXIMUM DIAMETER OF THE BODY.
5. POLARITY SHALL BE DENOTED BY A CATHODE BAND.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.130	0.300	3.30	7.62
B	0.115	0.142	2.92	3.61
D	0.036	0.042	0.91	1.07
F	---	0.050	---	1.27
K	0.900	1.300	22.86	33.02

DOCUMENT NUMBER: 98AON81693E

Electronic versions are uncontrolled except when accessed directly from the Document Repository.
Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.

DESCRIPTION: E-PKG AXIAL-LEADED GLASS DIODE

PAGE 1 OF 1

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.