




TO-92 (TO-226) CASE 182-06 **ISSUE L**

DATE 04/18/1998







SECTION X-X

- OTES:
 1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
 2. CONTROLLING DIMENSION: INCH.
 3. CONTOUR OF PACKAGE BEYOND ZONE R IS UNCONTROLLED.
 4. LEAD DIMENSION IS UNCONTROLLED IN P AND

- BEYOND DIMENSION K MINIMUM.

	INCHES MILLIMETE		IETERS	
DIM	MIN	MAX	MIN	MAX
Α	0.175	0.205	4.45	5.21
В	0.170	0.210	4.32	5.33
С	0.125	0.165	3.18	4.19
D	0.016	0.021	0.407	0.533
G	0.050	BSC	1.27	BSC
Н	0.100	BSC	2.54	BSC
J	0.014	0.016	0.36	0.41
K	0.500		12.70	
L	0.250	-	6.35	
N	0.080	0.105	2.03	2.66
Р		0.050		1.27
R	0.115	-	2.93	
۸	0 135		3 43	

STYLE 1: PIN 1. ANODE 2. CATHODE STYLE 2: PIN 1. CATHODE 2. ANODE

STYLE 3: PIN 1. MAIN TERMINAL 1 2. MAIN TERMINAL 2 STYLE 4: CANCELLED STYLE 5: PIN 1. INPUT 2. OUTPUT

DOCUMENT NUMBER:	98ASB42118B	Electronic versions are uncontrolled except when accessed directly from the Document Repository Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	TO-92 (TO-226)		PAGE 1 OF 1

onsemi and ONSEMi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.