






WLCSP6, 1.46x0.96 CASE 567BB ISSUE O

**DATE 26 JUL 2010** 

- NOTES: 1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
- 2. CONTROLLING DIMENSION: MILLIMETERS.
  3. COPLANARITY APPLIES TO SPHERICAL CROWNS OF SOLDER BALLS.


	MILLIMETERS		
DIM	MIN	MAX	
Α	0.56	0.72	
A1	0.21	0.27	
A2	0.42 REF		
b	0.29	0.35	
D	1.46 BSC		
E	0.96 BSC		
-	0.50 BSC		


## **RECOMMENDED SOLDERING FOOTPRINT\***



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

PIN A1 REFERENCE		A B
2X 🔼 0.05 C		<u> </u>
2X 0.05 C	TOP VIEW	





DOCUMENT NUMBER:	98AON49811E	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	WLCSP6, 1.46X0.96		PAGE 1 OF 1

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.