Isemi

PAD A1 CORNER

5.000 ± 0.075 NOTE 9

(1.450)

 10.000 ± 0.075

PIN 1 ID

5.000 ± 0.075 — NOTE 9

- (1.455)

ILCC48 10x10 CASE 847AH

В

A

PIXEL NOTE 8


FIRST ACTIVE

ISSUE A

DATE 25 MAR 2020



- 1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
- CONTROLLING DIMENSION: MILLIMETERS [mm]. 2.
- COPLANARITY APPLIES TO THE PLATED LAND PADS. 3. GLASS: 0.400 THICKNESS; REFRACTIVE INDEX = 1.52. 4.
- 5. AIR GAP BETWEEN GLASS AND PIXEL ARRAY: 0.125 THICKNESS.
- 6. PARALLELISM APPLIES ONLY TO THE ACTIVE ARRAY.
- MAXIMUM ROTATION OF ACTIVE ARRAY RELATIVE TO DATUMS A AND B IS + 1°. 7.
- REFER TO THE DEVICE DATA SHEET FOR TOTAL PIXEL ARRAY DEFINITIONS.
- 8.



onsemi and ONSEMi. are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.