



PIN ONE -REFERENCE

0.20 С

NOTE 4

0.10


0.08 C

PIN 1 INDICATOR

4X M

е

0.20 C



Α

E1

В

Ε

C SEATING PLANE

4X M

32X L

A B

NOTE 3

32X **b**

 \oplus

0.10 C

0.05 C

D

D1

TOP VIEW

SIDE VIEW

BOTTOM VIEW


DATE 27 JAN 2009

- NOTES:

 1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
 2. CONTROLLING DIMENSIONS: MILLIMETERS.
 3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.30mm FROM THE TERMINAL TIP.
 4. COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.

	MILLIMETERS		
DIM	MIN	MAX	
Α	0.80	1.00	
A1	0.00	0.05	
A3	0.20 REF		
b	0.18	0.30	
D	5.00 BSC		
D1	4.75 BSC		
D2	2.95	3.25	
E	5.00 BSC		
E1	4.75 BSC		
E2	2.95	3.25	
е	0.50 BSC		
Н		12°	
K	0.20		
L	0.30	0.50	
M		0.60	

SOLDERING FOOTPRINT*



*For additional information on our Pb-Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

DOCUMENT NUMBER:	98AON26684D	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	LFCSP32, 5x5, 0.5P		PAGE 1 OF 1

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves brisefin and of 160 m are trademarks of defined values of services and of the confined values and of the values of the confined values and of the values of the confined values and of the values of the va special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.