

Dual Boost Power Module

Product Preview

NXH80B120MNQ0SNG

The NXH80B120MNQ0SNG is a power module containing a dual boost stage. The integrated SiC MOSFETs and SiC Diodes provide lower conduction losses and switching losses, enabling designers to achieve high efficiency and superior reliability.

Features

- 1200 V 80 mΩ SiC MOSFETs
- Low Reverse Recovery and Fast Switching SiC Diodes
- 1600 V Bypass and Anti-parallel Diodes
- Low Inductive Layout
- Solderable Pins
- Thermistor
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant

Typical Applications

- Solar Inverters
- Uninterruptable Power Supplies





Figure 1. NXH80B120MNQ0SNG Schematic Diagram




ON Semiconductor®

www.onsemi.com




Q0BOOST
CASE 180AJ
SOLDER PINS

MARKING DIAGRAM



G = Pb-Free Package
AT = Assembly & Test Site Code
YYWW = Year and Work Week Code

PIN CONNECTIONS



ORDERING INFORMATION

See detailed ordering and shipping information on page 4 of this data sheet.

This document contains information on a product under development. ON Semiconductor reserves the right to change or discontinue this product without notice.

NXH80B120MNQ0SNG

ABSOLUTE MAXIMUM RATINGS (Note 1) $T_J = 25^\circ\text{C}$ unless otherwise noted

| Rating | Symbol | Value | Unit |
|---|-----------------------|---------|------------------|
| BOOST MOSFET | | | |
| Drain–Source Voltage | V_{DS} | 1200 | V |
| Gate–Source Voltage | V_{GS} | -15/+25 | V |
| Continuous Drain Current (@ $V_{GS} = 20\text{ V}$, $T_C = 80^\circ\text{C}$) | I_D | 23 | A |
| Pulsed Drain Current @ $T_C = 80^\circ\text{C}$ ($T_J = 175^\circ\text{C}$) | $I_{D(\text{Pulse})}$ | 69 | A |
| Maximum Power Dissipation @ $T_C = 80^\circ\text{C}$ | P_{tot} | 69 | W |
| Minimum Operating Junction Temperature | $T_{J\text{MIN}}$ | -40 | $^\circ\text{C}$ |
| Maximum Operating Junction Temperature | $T_{J\text{MAX}}$ | 175 | $^\circ\text{C}$ |

BOOST DIODE

| | | | |
|--|-------------------|------|----------------------|
| Peak Repetitive Reverse Voltage | V_{RRM} | 1200 | V |
| Continuous Forward Current @ $T_C = 80^\circ\text{C}$ | I_F | 31 | A |
| Surge Forward Current (60 Hz single half–sine wave) | I_{FSM} | 93 | A |
| Maximum Power Dissipation @ $T_C = 80^\circ\text{C}$ ($T_J = 175^\circ\text{C}$) | P_{tot} | 97 | W |
| I^2t – value (60 Hz single half–sine wave) | I^2t | 19 | A^2s |
| Minimum Operating Junction Temperature | $T_{J\text{MIN}}$ | -40 | $^\circ\text{C}$ |
| Maximum Operating Junction Temperature | $T_{J\text{MAX}}$ | 175 | $^\circ\text{C}$ |

BYPASS DIODE

| | | | |
|---|-------------------|------|------------------|
| Peak Repetitive Reverse Voltage | V_{RRM} | 1600 | V |
| Continuous Forward Current @ $T_C = 80^\circ\text{C}$ ($T_J = 150^\circ\text{C}$) | I_F | 44 | A |
| Repetitive Peak Forward Current ($T_C = 80^\circ\text{C}$, t_p limited by $T_{J\text{max}}$) | I_{FRM} | 132 | A |
| Power Dissipation Per Diode @ $T_C = 80^\circ\text{C}$ ($T_J = 150^\circ\text{C}$) | P_{tot} | 63 | W |
| Minimum Operating Junction Temperature | $T_{J\text{MIN}}$ | -40 | $^\circ\text{C}$ |
| Maximum Operating Junction Temperature | $T_{J\text{MAX}}$ | 150 | $^\circ\text{C}$ |

THERMAL PROPERTIES

| | | | |
|---------------------------|------------------|------------|------------------|
| Storage Temperature range | T_{stg} | -40 to 125 | $^\circ\text{C}$ |
|---------------------------|------------------|------------|------------------|

INSULATION PROPERTIES

| | | | |
|--|-----------------|------|------------------|
| Isolation test voltage, $t = 1\text{ sec}$, 60 Hz | V_{is} | 3000 | V_{RMS} |
| Creepage distance | | 12.7 | mm |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Refer to [ELECTRICAL CHARACTERISTICS](#), [RECOMMENDED OPERATING RANGES](#) and/or APPLICATION INFORMATION for Safe Operating parameters.

RECOMMENDED OPERATING RANGES

| Parameter | Symbol | Min | Max | Unit |
|---------------------------------------|--------|-----|----------------------------|------------------|
| Module Operating Junction Temperature | T_J | -40 | ($T_{J\text{MAX}} - 25$) | $^\circ\text{C}$ |

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

NXH80B120MNQ0SNG

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise specified)

| Characteristic | Test Conditions | Symbol | Min | Typ | Max | Unit |
|----------------|-----------------|--------|-----|-----|-----|------|
|----------------|-----------------|--------|-----|-----|-----|------|

BOOST MOSFET CHARACTERISTICS

| | | | | | | | |
|---------------------------------------|---|--|--------------------|-------|--------|-----|----|
| Zero Gate Voltage Drain Current | V _{GS} = 0 V, V _{DS} = 1200 V, T _J = 25°C | I _{DSS} | – | – | 100 | μA | |
| Static Drain-to-Source On Resistance | V _{GS} = 20 V, I _D = 20 A, T _J = 25°C | R _{DS(on)} | – | 80 | 110 | mΩ | |
| | V _{GS} = 20 V, I _D = 20 A, T _J = 150°C | | – | 114 | 162 | | |
| Gate-Source Threshold Voltage | V _{GS} = V _{DS} , I _D = 5 mA | V _{GS(th)} | 1.8 | 2.0 | 4.3 | V | |
| Gate-Source Leakage Current | V _{GS} = 25 V, V _{DS} = 0 V | I _{GSS} | – | – | 1 | μA | |
| Turn-on Delay Time | T _J = 25°C V _{DS} = 700 V, V _{GS} = 20 V, -5 V I _D = 30 A, R _G = 4.7 Ω | t _{d(on)} | – | 13.4 | – | ns | |
| Rise Time | | t _r | – | 3.6 | – | | |
| Turn-off Delay Time | | t _{d(off)} | – | 27.6 | – | | |
| Fall Time | | t _f | – | 10.3 | – | | |
| Turn-on Switching Loss per Pulse | | E _{on} | – | 166 | – | | μJ |
| Turn-off Switching Loss per Pulse | | E _{off} | – | 49.2 | – | | |
| Turn-on Delay Time | | T _J = 125°C V _{DS} = 700 V, V _{GS} = 20 V, -5 V I _D = 30 A, R _G = 4.7 Ω | t _{d(on)} | – | 13.7 | | – |
| Rise Time | t _r | | – | 3.5 | – | | |
| Turn-off Delay Time | t _{d(off)} | | – | 29.56 | – | | |
| Fall Time | t _f | | – | 10.36 | – | | |
| Turn-on Switching Loss per Pulse | E _{on} | | – | 154 | – | μJ | |
| Turn-off Switching Loss per Pulse | E _{off} | | – | 46.65 | – | | |
| Input Capacitance | V _{DS} = 800 V, V _{GS} = 0 V, f = 1 MHz | | C _{iss} | – | 1038.7 | – | pF |
| Output Capacitance | | C _{oss} | – | 95.5 | – | | |
| Reverse Transfer Capacitance | | C _{rss} | – | 10.9 | – | | |
| Total Gate Charge | V _{DS} = 600 V, I _D = 20 A, V _{GS} = 20 V, -5 V | Q _g | – | 74.72 | – | nC | |
| Thermal Resistance – chip-to-case | Thermal grease, Thickness = 2.1 Mil ±2% λ = 2.9 W/mK | R _{thJC} | – | 1.37 | – | K/W | |
| Thermal Resistance – chip-to-heatsink | | R _{thJH} | – | 1.94 | – | K/W | |

BOOST DIODE CHARACTERISTICS

| | | | | | | | |
|---------------------------------------|---|--|-----------------|------|------|------|----|
| Diode Reverse Leakage Current | V _R = 1200 V | I _R | – | – | 300 | μA | |
| Diode Forward Voltage | I _F = 20 A, T _J = 25°C | V _F | – | 1.49 | 1.7 | V | |
| | I _F = 20 A, T _J = 150°C | | – | 2.17 | – | | |
| Reverse Recovery Time | T _J = 25°C V _{DS} = 700 V, V _{GS} = 20 V, -5 V I _D = 30 A, R _G = 4.7 Ω | t _{rr} | – | 12 | – | ns | |
| Reverse Recovery Charge | | Q _{rr} | – | 159 | – | nC | |
| Peak Reverse Recovery Current | | I _{RRM} | – | 21.2 | – | A | |
| Peak Rate of Fall of Recovery Current | | di/dt | – | 7240 | – | A/μs | |
| Reverse Recovery Energy | | E _{rr} | – | 70 | – | μJ | |
| Reverse Recovery Time | | T _J = 125°C V _{DS} = 700 V, V _{GS} = 20 V, -5 V I _D = 30 A, R _G = 4.7 Ω | t _{rr} | – | 11.7 | – | ns |
| Reverse Recovery Charge | | | Q _{rr} | – | 153 | – | nC |
| Peak Reverse Recovery Current | I _{RRM} | | – | 23.8 | – | A | |
| Peak Rate of Fall of Recovery Current | di/dt | | – | 8068 | – | A/μs | |
| Reverse Recovery Energy | E _{rr} | | – | 66.3 | – | μJ | |

NXH80B120MNQ0SNG

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise specified) (continued)

| Characteristic | Test Conditions | Symbol | Min | Typ | Max | Unit |
|----------------|-----------------|--------|-----|-----|-----|------|
|----------------|-----------------|--------|-----|-----|-----|------|

BOOST DIODE CHARACTERISTICS

| | | | | | | |
|---------------------------------------|--|-------------------|---|------|---|-----|
| Thermal Resistance – chip-to-case | Thermal grease, Thickness = 2.1 Mil ±2% | R _{thJC} | – | 0.98 | – | K/W |
| Thermal Resistance – chip-to-heatsink | λ = 2.9 W/mK | R _{thJH} | – | 1.33 | – | K/W |

BYPASS DIODE CHARACTERISTICS

| | | | | | | |
|---------------------------------------|--|-------------------|---|------|-----|-----|
| Diode Reverse Leakage Current | V _R = 1600 V, T _J = 25°C | I _R | – | – | 100 | μA |
| Diode Forward Voltage | I _F = 30 A, T _J = 25°C | V _F | – | 1.04 | 1.4 | V |
| | I _F = 30 A, T _J = 150°C | | – | 0.94 | – | |
| Thermal Resistance – chip-to-case | Thermal grease, Thickness = 2.1 Mil ±2% | R _{thJC} | – | 1.12 | – | K/W |
| Thermal Resistance – chip-to-heatsink | λ = 2.9 W/mK | R _{thJH} | – | 1.56 | – | K/W |

THERMISTOR CHARACTERISTICS

| | | | | | | |
|----------------------------|--------------------------|------------------|----|------|---|------|
| Nominal resistance | | R ₂₅ | – | 22 | – | kΩ |
| Nominal resistance | T = 100°C | R ₁₀₀ | – | 1486 | – | Ω |
| Deviation of R25 | | ΔR/R | –5 | – | 5 | % |
| Power dissipation | | P _D | – | 200 | – | mW |
| Power dissipation constant | | | – | 2 | – | mW/K |
| B-value | B(25/50), tolerance ±3% | | – | 3950 | – | K |
| B-value | B(25/100), tolerance ±3% | | – | 3998 | – | K |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

ORDERING INFORMATION

| Part Number | Marking | Package | Shipping |
|------------------|------------------|---|-------------------------|
| NXH80B120MNQ0SNG | NXH80B120MNQ0SNG | Q0BOOST – Case 180AJ (Pb-Free and Halide-Free Solder Pins) | 24 Units / Blister Tray |

NXH80B120MNQ0SNG

TYPICAL CHARACTERISTICS – MOSFET, BOOST DIODE AND BYPASS DIODE




Figure 2. MOSFET On Region Characteristics




Figure 3. MOSFET On Region Characteristics




Figure 4. MOSFET Transfer Characteristics




Figure 5. Boost Diode Forward Characteristics




Figure 6. Bypass Diode Forward Characteristics

NXH80B120MNQ0SNG

TYPICAL SWITCHING CHARACTERISTICS – MOSFET




Figure 7. Typical Turn On Loss vs. I_D




Figure 8. Typical Turn Off Loss vs. I_D




Figure 9. Typical Turn On Loss vs. R_G




Figure 10. Typical Turn Off Loss vs. R_G




Figure 11. Typical Turn On Switching Time vs. I_D




Figure 12. Typical Turn Off Switching Time vs. I_D

NXH80B120MNQ0SNG

TYPICAL CHARACTERISTICS – MOSFET




Figure 13. Typical Turn On Switching Time vs. R_G




Figure 14. Typical Turn Off Switching Time vs. R_G

TYPICAL CHARACTERISTICS – BOOST DIODE




Figure 15. Typical Reverse Recovery Energy Loss vs. I_D




Figure 16. Typical Reverse Recovery Energy Loss vs. R_G




Figure 17. Typical Reverse Recovery Time vs. I_D




Figure 18. Typical Reverse Recovery Time vs. R_G

NXH80B120MNQ0SNG

TYPICAL SWITCHING CHARACTERISTICS – BOOST DIODE




Figure 19. Typical Reverse Recovery Charge vs. I_D




Figure 20. Typical Reverse Recovery Charge vs. R_G




Figure 21. Typical Reverse Recovery Peak Current vs. I_D




Figure 22. Typical Reverse Recovery Peak Current vs. R_G




Figure 23. Typical di/dt vs. I_D




Figure 24. Typical di/dt vs. R_G

TRANSIENT THERMAL IMPEDANCE – MOSFET, BOOST DIODE AND BYPASS DIODE




Figure 25. MOSFET Transient Thermal Impedance




Figure 26. Boost Diode Transient Thermal Impedance




Figure 27. Bypass Diode Transient Thermal Impedance

NXH80B120MNQ0SNG

GATE CHARGE, CAPACITANCE CHARGE, SOA AND THERMISTOR CHARACTERISTICS




Figure 28. Gate Voltage vs. Gate Charge




Figure 29. Capacitance Charge




Figure 30. FBSOA




Figure 31. RBSOA




Figure 32. Thermistor Characteristics

MECHANICAL CASE OUTLINE



PACKAGE DIMENSIONS

ON Semiconductor®



PIM22, 55x32.5 / Q0BOOST CASE 180AJ ISSUE B

DATE 08 NOV 2017



NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2009.
2. CONTROLLING DIMENSION: MILLIMETERS
3. DIMENSION b APPLIES TO THE PLATED TERMINALS AND IS MEASURED BETWEEN 1.00 AND 3.00 FROM THE TERMINAL TIP.
4. POSITION OF THE CENTER OF THE TERMINALS IS DETERMINED FROM DATUM B THE CENTER OF DIMENSION D, X DIRECTION, AND FROM DATUM A, Y DIRECTION. POSITIONAL TOLERANCE, AS NOTED IN DRAWING, APPLIES TO EACH TERMINAL IN BOTH DIRECTIONS.
5. PACKAGE MARKING IS LOCATED AS SHOWN ON THE SIDE OPPOSITE THE PACKAGE ORIENTATION FEATURES.


| DIM | MILLIMETERS | |
|-----|-------------|-------|
| | MIN. | NDM. |
| A | 13.50 | 13.90 |
| A1 | 0.10 | 0.30 |
| A2 | 11.50 | 11.90 |
| A3 | 15.65 | 16.05 |
| A4 | 16.35 | REF |
| b | 0.95 | 1.05 |
| D | 54.80 | 55.20 |
| D1 | 65.60 | 66.20 |
| E | 32.20 | 32.80 |
| P | 4.20 | 4.40 |
| P1 | 8.90 | 9.10 |

MOUNTING HOLE POSITION

NOTE 4

| PIN | HOLE POSITION | | PIN | PIN POSITION | | PIN | PIN POSITION | | PIN | PIN POSITION | |
|-----|---------------|--------|-----|--------------|-------|-----|--------------|-------|-----|--------------|--------|
| | X | Y | | X | Y | | X | Y | | X | Y |
| 1 | -16.75 | -11.25 | 12 | 16.75 | 6.55 | 1 | -16.75 | 11.25 | 12 | 16.75 | -6.55 |
| 2 | -13.85 | -11.25 | 13 | 15.25 | 11.25 | 2 | -13.85 | 11.25 | 13 | 15.25 | -11.25 |
| 3 | -8.45 | -11.25 | 14 | 12.35 | 11.25 | 3 | -8.45 | 11.25 | 14 | 12.35 | -11.25 |
| 4 | -5.95 | -11.25 | 15 | 5.35 | 11.25 | 4 | -5.95 | 11.25 | 15 | 5.35 | -11.25 |
| 5 | 2.85 | -11.25 | 16 | 2.85 | 11.25 | 5 | 2.85 | 11.25 | 16 | 2.85 | -11.25 |
| 6 | 5.35 | -11.25 | 17 | -5.95 | 11.25 | 6 | 5.35 | 11.25 | 17 | -5.95 | -11.25 |
| 7 | 12.35 | -11.25 | 18 | -8.45 | 11.25 | 7 | 12.35 | 11.25 | 18 | -8.45 | -11.25 |
| 8 | 15.25 | -11.25 | 19 | -13.85 | 11.25 | 8 | 15.25 | 11.25 | 19 | -13.85 | -11.25 |
| 9 | 16.75 | -6.55 | 20 | -16.75 | 11.25 | 9 | 16.75 | 6.55 | 20 | -16.75 | -11.25 |
| 10 | 16.75 | -4.05 | 21 | -16.75 | 3.25 | 10 | 16.75 | 4.05 | 21 | -16.75 | -3.25 |
| 11 | 16.75 | 4.05 | 22 | -16.75 | -3.25 | 11 | 16.75 | -4.05 | 22 | -16.75 | 3.25 |

GENERIC MARKING DIAGRAM*



XXXXX = Specific Device Code
 G = Pb-Free Package
 AT = Assembly & Test Site Code
 YYWW = Year and Work Week Code





*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "•", may or may not be present. Some products may not follow the Generic Marking.

| | | |
|-------------------------|---|--|
| DOCUMENT NUMBER: | 98AON63481G | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION: | PIM22 55X32.5 / Q0BOOST (SOLDER PIN) | PAGE 1 OF 2 |

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.


PIM22, 55x32.5 / Q0BOOST
CASE 180AJ
ISSUE B

DATE 08 NOV 2017



MOUNTING HOLE DETAIL

| | | |
|-------------------------|---|--|
| DOCUMENT NUMBER: | 98AON63481G | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION: | PIM22 55X32.5 / Q0BOOST (SOLDER PIN) | PAGE 2 OF 2 |

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

onsemi, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Email Requests to: orderlit@onsemi.com

onsemi Website: www.onsemi.com

TECHNICAL SUPPORT

North American Technical Support:

Voice Mail: 1 800-282-9855 Toll Free USA/Canada

Phone: 011 421 33 790 2910

Europe, Middle East and Africa Technical Support:

Phone: 00421 33 790 2910

For additional information, please contact your local Sales Representative