












MMBT3906L

PNP

PNP SOT-23

- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant
- S Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable

	Pricing (\$/Unit)	Compliance	Status	Polarity	Type	$V_{CE(sat)}$ Max (V)	I_C Cont. (A)	V_{CE0} Min (V)	V_{CBO} (V)	V_{EBO} (V)	$V_{BE(sat)}$ (V)	$V_{BE(o)}$ (V)	h_{FE} Min	h_{FE} Max	f_T Min (MHz)	P_{TM} Max (W)	Package Type
MMBT3906LT1G	0.014	 	Active	PNP	General Purpose	0.4	0.2	40	40	5	0.95	-	100	300	250	0.225	SOT-23-3
MMBT3906LT3G	0.014	 	Active	PNP	General Purpose	0.4	0.2	40	40	5	0.95	-	100	300	250	0.225	SOT-23-3
SMMBT3906LT1G	0.0293	   	Active	PNP	General Purpose	0.4	0.2	40	40	5	0.95	-	100	300	250	0.225	SOT-23-3
SMMBT3906LT3G	0.0293	   	Active	PNP	General Purpose	0.4	0.2	40	40	5	0.95	-	100	300	250	0.225	SOT-23-3