

製品概要

1SS400: Switching Diode, 100 V

技術情報は、データシートをご参照ください。

The switching diode is designed for high speed switching applications.

特長

- Lead Finish: 100% Matte Sn (Tin)
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant
- NSV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AECQ101 Qualified and PPAP Capable

電氣的仕様

製品	Compliance	Status	Configuration	V_R Min (V)	V_F Max (V)	I_R Max (μ A)	I_F Max (A)	t_{rr} Max (ns)	C_D Max (pF)	Package Type
1SS400T1G	Pb-free Halide free	Active	Single	100	1.2	0.1	0.2	4	3	SOD-523-2
1SS400T5G	Pb-free Halide free	Active	Single	100	1.2	0.1	0.2	4	3	SOD-523-2
NSV1SS400T1G	AEC Qualified PPAP Capable Pb-free Halide free	Active	Single	100	1.2	0.1	0.2	4	3	SOD-523-2
NSV1SS400T5G	AEC Qualified PPAP Capable Pb-free Halide free	Active	Single	100	1.2	0.1	0.2	4	3	SOD-523-2

詳細は、弊社 www.onsemi.jp の営業または販売代理店にお問い合わせください。

8/20/2019 作成