

製品概要

BAS19L: Switching Diode, High Voltage 120 V

技術情報は、データシートをご参照ください。

The high voltage switching diode is designed for high voltage, high speed switching applications. This dual diode device contains two electrically isolated high voltage switching diodes encapsulated in a SOT-23 surface mount package.

特長

- Pb-Free Package is Available.
- NSV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AECQ101 Qualified and PPAP Capable

電氣的仕様										
製品	Compliance	Status	Configuration	V_R Min (V)	V_F Max (V)	I_R Max (μ A)	I_F Max (A)	t_{rr} Max (ns)	C_D Max (pF)	Package Type
BAS19LT1G	Pb-free	Active	Single	120	1	0.1	0.2	50	5	SOT-23-3
	Halide free									
BAS19LT3G	Pb-free	Active	Single	120	1	0.1	0.2	50	5	SOT-23-3
	Halide free									
NSVBAS19LT1G	AEC Qualified	Active	Single	120	1	0.1	0.2	50	5	SOT-23-3
	PPAP Capable									
	Pb-free									
	Halide free									

詳細は、弊社 www.onsemi.jp の営業または販売代理店にお問い合わせください。

8/24/2019 作成